



a vital part of your world

Find Answers:

Sunday, 20 November, 2005

CATALOG

• **Cross Reference**

- [Competitive Products](#)
- [Military Spec P/Ns](#)
- [Tyco Brand P/Ns](#)

- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

Home

e-bulletin newsletter
SUBSCRIBE NOW!
 click here

Circuit Breakers

↳ **Thermal Circuit Breakers**



W58-XB1A4A-8 **Active**

Not ELV or RoHS Compliant

(Tyco Electronics P/N: 2-1393249-2)

Search for Compliant (RoHS/ELV)

Alternates

Search for Parts

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

Related Part Information

| General Information | eCommerce | Related Part Information |
|--|---|---|
| <ul style="list-style-type: none"> ➤ General Info ➤ Sales Info | <ul style="list-style-type: none"> ➤ Pricing ➤ Product Availability | <ul style="list-style-type: none"> ➤ Tooling |

Searchable Features:

| | |
|-------------------------------------|--|
| Brand: | Potter & Brumfield |
| RoHS/ELV Compliance: | Not ELV/RoHS compliant |
| Lead Free Solder Processes: | Not relevant for lead free process |
| Series: | W58 |
| Actuator Style: | Push to Reset |
| Number of Poles: | 1 |
| Current Rating (Amps.): | 8 |
| Button Color: | White with Red Rate Marking, Red Trip Band |
| Circuit Function: | Series Trip |
| Operating Voltage, Max.: | 50 VDC, 250 VAC |
| Trip Time at 200%: | 6 to 30 Seconds |
| Interrupt Capacity: | 2,000 A @ 50 VDC or 1,000 A @ 250 VAC |
| Mounting Options: | Knurled Nut/Hex Nut |
| Mounting Hardware Packaging: | Assembled to Bushing |

Other Properties:

| | |
|----------------------------|---------------|
| Approved Standards: | CSA Certified |
|----------------------------|---------------|

| | |
|--------------------------|--|
| Termination Type: | 6.35 [.250] Straight Quick Connect Tab |
| Mounting Bushing: | 7/16" x .500" [12.70 mm] Long |

[Copyright and Privacy Statement](#)
Visit [Tyco International Ltd.](#)

[[Products](#) | [Catalog](#) | [Brands](#) | [Industries](#) | [Commerce](#) | [Supplier](#) | [Contact Us](#) | [About](#) | [Home](#)]