



ABSOLUTE MAXIMUM RATINGS

Power dissipation
Input-Output Voltage Differential
Operating Junction Temperature Range
Storage Temperature
Lead Temperature(Soldering, 4seconds)
Output is Short Circuit Protected
ESD rating to be determined

Internally limited
38V
-20°C to +85°C
-55°C to +150°C
260°C



ELECTRICAL CHARACTERISTICS

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
Line Regulation	$3V \leq (V_{IN}-V_{OUT}) \leq 40V, I_L \leq 20mA$		0.02	0.07	%/V
Load Regulation	$5mA \leq I_{OUT} \leq 100mA$		0.3	1.5	%
Reference Voltage	$5mA \leq I_{OUT} \leq 100mA$ $P \leq 625mW$ $3V \leq (V_{IN}-V_{OUT}) \leq 40V$	1.20	1.25	1.30	V
Adjustment Pin Current			50	100	μA
Adjustment Pin Current Change	$5mA \leq I_L \leq 100mA$, $3V \leq (VIN-VOUT) \leq 40V$ $P \leq 625mW$		0.2	5	μA
Minimum Load Current	$(V_{IN}-V_{OUT}) \leq 40V$ $3V \leq (V_{IN}-V_{OUT}) \leq 15V$		3.5 1.5	5	mA
Current Limit	$3V \leq (V_{IN}-V_{OUT}) \leq 13V$ $(V_{IN}-V_{OUT})=40V$	90 25	200 50	300 120	mA
RMS Output Noise % of V_{OUT}	$T_J=25, 10Hz \leq F \leq 10KHz$		0.03		%
Ripple Rejection Ratio	$V_{OUT}=10V, F=120Hz, C_{ADJ}=10F$	58	65 80		dB

Note1: Unless otherwise noted, these specifications apply: $0^\circ C \leq T_J \leq 70^\circ C$ for the WS317L; $V_{IN}-V_{OUT}=5V$ and $I_{OUT}=40mA$. Although power dissipation is internally limited, these specifications are applicable for power dissipation up to 625mW. I_{MAX} is 100mA

Note2: Regulation is measured at constant junction temperature, using pulse testing with a low duty cycle. Changes in output voltage due to heating effects are covered under the specification for thermal regulation.

Note3: Thermal resistance of the TO-92 package is $180^\circ C/W$ junction to ambient with 0.4" leads from a PC board and $160^\circ C/W$ junction to ambient with 0.125" length to a PC board