

SONY

CXA1846AM/AN

Electronic volume control

Description

The CXA1846AM/AN is an electrical volume control IC for use in car radios/stereos and radio-cassette recorders featuring serial data control. It has improved over the CXA1846M/N by reducing the 'pop' noise during volume level-switchings.


Features

- Volume adjustment (0dB to -87dB, -∞dB)
- Balance
- Serial data control (DATA, CLK, CE)
- Single 8V power supply
- Zero-cross detection circuit


Structure

Bipolar silicon monolithic IC

CXA1846AM
20 pin SOP (Plastic)



CXA1846AN
20 pin SSOP (Plastic)




Absolute Maximum Ratings (Ta=25 °C)

• Supply voltage	V _{CC}	13	V
• Operating temperature	T _{opr}	-40 to +85	°C
• Storage temperature	T _{stg}	-65 to +150	°C
• Allowable power dissipation	P _D		
	SOP	350 (75°C)	mW
	SSOP	220 (75°C)	mW

Recommended Supply Voltage Range






Supply voltage	V _{CC}	6 to 12	V
----------------	-----------------	---------	---






Block Diagram and Pin Configuration



Sony reserves the right to change products and specifications without prior notice. This information does not convey any license by any implication or otherwise under any patents or other right. Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits.

Pin Description

Pin No.	Symbol	I/O resistance voltage	Equivalent circuit	Description
1 20	INP2 INP1	50kΩ VCT		Input operational amplifier positive phase input
2 19	INN2 INN1	— VCT		Input operational amplifier reversed phase input
3 18	VCT2 VCT1	— VCT		VCT buffer output
4 17	INAO2 INAO1	— VCT		Input operational amplifier
5 16	VRIN2 VRIN1	8.2kΩ VCT		Volume input

Pin No.	Symbol	I/O resistance voltage	Equivalent circuit	Description
6 15	OUT2 OUT1	— VCT		Volume output
7	CE	∞		Latch enable
8	DATA	∞		Serial data input
9	CLK	∞		Serial clock
10	INIT	—		System reset
11	Vcc	—		+ power supply
12	VCT	VCT		Mid-point potential
13	GND	—		GND

Electrical Characteristics(Unless otherwise specified $V_{CC} = 8V$, $T_a = 25^{\circ}C$)

Item		Symbol	Measurement Condition	Min.	Typ.	Max.	Unit
Circuit current		I_{CC}	No signal	5	8	12	mA
Total harmonic distortion		THD	1kHz, 5dBm	—	0.003	0.01	%
Output noise voltage		V_n	Input shorted	—	5	7	μV_{rms}
Maximum output voltage		V_{om}	1kHz	8	—	—	dBm
Separation		CS	1kHz	85	90	—	dB
Maximum attenuation		ATTm		85	90	—	dB
Input voltage	High	V_{sh}	Data, INIT	3	—	6	V
	Low	V_{sl}	CLK, CE	0	—	1.5	V
Input voltage range		V_{in}		1	—	$V_{CC} - 1$	V
Maximum output current		I_{max}	Input buffer amplifier output current	—	—	1	mA

RESET

The IC is reset by reducing the voltage at the INIT pin to 1V or less when CLK is high. Reset can not be performed when CLK is low. The table below shows the status when the IC has been reset.

MODE	Setting
VRC1	$-\infty$
VRF1	-7dB
VRC2	$-\infty$
VRF2	-7dB

Data Allocation

Fast bit	D1	NOP	MSB
	D2 D3 D4 D5	VRC1	
	D6 D7 D8	VRF1	
	D9	NOP	
	D10 D11 D12 D13	VRC2	
	D14 D15 D16	VRF2	LSB


VRC1/VRC2

Setting	D2/D10	D3/D11	D4/D12	D5/D13
0	1	1	1	1
-8	1	1	1	0
-16	1	1	0	1
-24	1	1	0	0
-32	1	0	1	1
-40	1	0	1	0
-48	1	0	0	1
-56	1	0	0	0
-64	0	1	1	1
-72	0	1	1	0
-80	0	1	0	1
-∞	0	1	0	0
-∞	0	0	0	0


VRF1/VRF2

Setting	D6/D14	D7/D15	D8/D16
0	1	1	1
-1	1	1	0
-2	1	0	1
-3	1	0	0
-4	0	1	1
-5	0	1	0
-6	0	0	1
-7	0	0	0


Data Timing




Test Circuit



Application Circuit



Application circuits shown are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits or for any infringement of third party patent and other right due to same.




CXA1846AM

SONY CODE	SOP-20P-L01
EIAJ CODE	SOP020-P-0300
JEDEC CODE	_____

PACKAGE MATERIAL	EPOXY RESIN
LEAD TREATMENT	SOLDER PLATING
LEAD MATERIAL	COPPER ALLOY
PACKAGE MASS	0.3g

20PIN SSOP (PLASTIC)



SONY CODE	SSOP-20P-L01
EIAJ CODE	SSOP020-P-0044
JEDEC CODE	_____

PACKAGE MATERIAL	EPOXY RESIN
LEAD TREATMENT	SOLDER / PALLADIUM PLATING
LEAD MATERIAL	42/COPPER ALLOY
PACKAGE MASS	0.1g

This product uses S-PdPPF (Sony Spec.-Palladium Pre-Plated Lead Frame).