

CXA2586M

PDIC for CD-ROM/DVD-ROM

Description

CXA2586M is a PDIC (photodetector IC) developed as a photodetector for the optical pickup of CD-ROM/DVD-ROM.

The photodiode and circuit blocks operate at high speed. (Typ. 100MHz)

- Focus servo : astigmatic method
- Tracking servo (CD)
 - : three-spot method
- Tracking servo (DVD)
 - : differential phase detection method

Features

- High-speed I-V amplifier
- (current-voltage conversion circuit)
- High-speed photodiode
- Adding amplifier (addition of A to D)
- Compact transparent molded package (SOP)

Applications

Optical pickup for CD-ROM/DVD-ROM



Absolute Maximum Ratings (Ta=25 °C)

 Supply voltage 	Vcc	5.5	V
Operating temperature	Topr	-10 to +70	°C
 Storage temperature 	Tstg	-40 to +100	°C
• Allowable power dissipa	tion		
	Pp	300	mW

Operating Conditions

 Supply voltage1 	Vcc	4.5 to 5.5	V
 Supply voltage2 	Vc	1.5 to Vcc-1.5	V

Structure

Bipolar silicon monolithic IC



* The components marked by A, B, C, D, E and F are the photodiodes

(photo sensitivity. About 0.4A/W @650nm, 780nm)

Sony reserves the right to change products and specifications without prior notice. This information does not convey any license by any implication or otherwise under any patents or other right. Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony cannot assume responsibility for any problems arising out of the use of these circuits.

Pin Description

Pin No.	Symbol	I/O	Equivalent circuit	Description	
2 4 1 5	Ao Bo Co Do	0		Output of voltage signals converted from optical signals	
6 10	Eo Fo	0	6 300 10 200µA 37k≶ 37k≶ Vc ⊠	Output of voltage signals converted from optical signals	
3	RF	0		Output of addition of Ao to Do	
7	GND	I		For dual power supply : negative power supply For a single power supply : GND	
8	Vc	I		For dual power supply : GND For a single power supply : center voltage input	
9	Vcc	I		Positive power supply	

Electrical and Optical Characteristics

(Vcc=5.0 V, Vc=2.5 V, Ta=25 °C)

Item	Symbol	Conditions	Min.	Тур.	Max.	Unit
Current consumption	Icc	In the dark		15	20	mA
Output offset voltage (A to D)	Voff	In the dark, Vc reference	-25	0	25	mV
Output offset voltage (E, F)	Voff	In the dark, Vc reference	-15	0	15	mV
Output offset voltage (RF)	Voff	In the dark, GND reference	1.25	1.4	1.55	V
		A-B, in the dark	-20	0	20	mV
Quitaut voltage difference	A)/off	C-D, in the dark	-20	0	20	mV
		(A+C) – (B+D), in the dark	-20	0	20	mV
		E-F, in the dark	-15	0	15	mV
Sum of output offset voltages	Voffs	A+B+C+D, in the dark	-100	0	100	mV
Output voltage (A to D)	Vo	λ=650 nm, 780 nm, Po=10 μW	180	246	312	mV
Output voltage (E, F)	Vo	λ=650 nm, 780 nm, Po=10 μW	312	447	581	mV
Output voltage (RF)	Vo	λ=650 nm, 780 nm, Po=10 μW	302	432	561	mV
Output voltage ratio (E, F/A to D)	Vor	λ=650 nm, 780 nm, Po=10 μW	1.71	1.81	1.90	—
Output voltage ratio (RF/A to D)	(RF/A to D) Vor λ=650 nm, 780 nm, Po=10 μW		1.67	1.76	1.84	—
Maximum output voltage (A to D)	Vo	λ=650 nm, 780 nm, Po=100 μW	3.8	4.0	—	V
Maximum output voltage (E, F)	Vo	λ=650 nm, 780 nm, Po=100 μW	3.8	4.0	—	V
Maximum output voltage (RF)	Vo	λ=650 nm, 780 nm, Po=100 μW	3.8	4.0	—	V
		λ=650 nm, 780 nm				
Frequency response (A to D)	fc	Po=10 μWoc, 4 μWp-p	70	100		MHz
		100 kHz reference, –3 dB				
		λ=650 nm,780 nm				
Frequency response (E, F)	fc	Po=10 μWoc, 4 μWp-p	1	5	—	MHz
		100 kHz reference, –3 dB				
		λ=650 nm, 780 nm				
Frequency response (RF)	fc	Po=10 μWbc, 4 μWp-p	80	105	_	MHz
		100 kHz reference, –3 dB				
Group delay difference (A to D)	ΔGd	100 kHz to 50 MHz		1	5	ns
Group delay difference (RF)	ΔGd	100 kHz to 50 MHz	—	1	5	ns
Output noise level (A to D)	evel (A to D) Vn f=50 MHz, RBW=30 kHz		—	-87	-82	dBm
Output noise level (RF)	Vn	f=50 MHz, RBW=30 kHz		-76	-71	dBm

Note 1) Output offset voltage: Vc is the reference for A to F, GND for RF.

Note 2) Output voltage: Vc is the reference for A to F, GND for RF. However, the offset voltage is excluded.

Note 3) Output voltage, frequency response, group delay, output noise level: Confirmation of design.

Note 4) Measurement by the optical input: Measurement is made by emitting the light to the center of each photodiode.

In regard of the frequency response of A to D and RF, the same response can be obtained by emitting the light to the A to D photodiodes evenly.

Measurement Circuit



* All loads are 10 kΩ//10 pF. For RF, the DC current is cut by 1 $\mu F.$

Reference Surface and Photodetector Position



-4-

 (0.03 ± 0.02) is not included.

Deviation from the center of photodetector

(Unit : mm)

Photodetector Pattern Dimensions



Example of Representative Characteristics



Note on Operation

1. Power supply

The CXA2586M can be used with a single power supply or dual power supply. However, this IC is not provided with a center voltage generating circuit, and so when used with a single power supply the center voltage must be supplied from the RF amplifier or some other device.

The connection of the power supply for each case is as shown.

	(9) Vcc	(8) Vc	(7) GND
Dual power	Positive power	CND	Negative power
supply	supply	GND	supply
Single power	Positive power	Contor voltago	CND
supply	supply	Center voltage	GND

The potential difference between the Vcc pin and GND should be in the range of 4.5 to 5.5 V in both of a single power supply and dual power supply.

2. Soldering

The reflow soldering is not guaranteed for the CXA2586M.

3. Mechanical strength for package

The mechanical strength for the package is not guaranteed for the CXA2586M. Do not employ the mounting method which gives much weight to the package.

4. Visual inspection standard

Separate specifications and limit samples must be exchanged regarding visual inspection standards for the photodetector.

5. Bypass capacitor

The 0.1 μ F capacitor is connected between the Vcc and Vc pins, and the Vc and GND pins respectively to lower the power supply line impedance.

Take the FPC (flexible printed circuit) pattern and the like into consideration so that the bypass capacitor is located close to the PDIC.

Package Outline Unit : mm

PD-S-19-B





SONY CODE	PD-S-19-B		
EIAJ CODE			
JEDEC CODE		PACKAGE WEIGHT	0.06g

—8—