

High Power

Power Splitter/Combiner

ZB4CS-700-10W

4 Way-0°

400 to 700 MHz

Maximum Ratings


Operating Temperature	-55°C to 90°C
Storage Temperature	-55°C to 100°C
Power Input (as a combiner)	10W max.
Internal Dissipation	8W max.

Features

- high isolation, 25 dB typ.
- good input matching VSWR, 1.14 typ.
- good output matching VSWR, 1.1 typ.


Applications

- UHF-TV/DTV



CASE STYLE: Z689
PRICE: \$134.95 ea.
QTY.: (1-9)

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H
7.06	3.13	1.00	.250	1.430	5.630	6.810	.250
179.32	79.50	25.40	6.35	36.32	143.00	172.97	6.35

J	K	L	M	N	P	wt.
2.875	.156	3.53	.44	.73	1.40	grams
73.03	3.96	89.66	11.18	18.54	35.56	810

Electrical Specifications





FREQ. (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) ABOVE 6 dB		PHASE UNBALANCE (Deg.)		AMPLITUDE UNBALANCE (dB)		POWER INPUT, W ¹	
fl - fu	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.	as combiner ² Max.	as splitter Max.
400 - 700	25	20	0.35	0.8	0.6	4	0.1	0.3	10	20

¹ Over -55°C to +55°C. Derate linearly to 20% of rating at 90°C.

² As a combiner of noncoherent signals, max. power per port is power rating divided by number of ports.

Typical Performance Data

Frequency (MHz)	Insertion Loss				Amplitude Unbalance (dB)	Isolation			Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2	VSWR 3	VSWR 4
	(dB) S-1	(dB) S-2	(dB) S-3	(dB) S-4		(dB) 1-2	(dB) 2-3	(dB) 3-4						
400.00	6.41	6.26	6.30	6.34	0.15	28.12	36.59	27.11	0.21	1.29	1.14	1.15	1.15	1.16
425.00	6.40	6.27	6.31	6.35	0.14	34.17	45.74	31.85	0.10	1.19	1.13	1.14	1.14	1.15
450.00	6.37	6.25	6.27	6.30	0.12	36.86	47.56	33.26	0.11	1.09	1.11	1.13	1.12	1.13
470.00	6.40	6.26	6.29	6.31	0.14	32.20	39.98	30.16	0.23	1.03	1.10	1.11	1.10	1.11
490.00	6.37	6.24	6.26	6.29	0.14	29.04	36.31	27.51	0.30	1.03	1.09	1.10	1.08	1.09
510.00	6.42	6.29	6.31	6.33	0.13	27.29	34.09	25.82	0.31	1.07	1.08	1.09	1.06	1.07
530.00	6.42	6.31	6.32	6.34	0.11	26.42	32.68	24.87	0.40	1.10	1.08	1.10	1.06	1.07
550.00	6.42	6.29	6.32	6.33	0.13	26.18	31.64	24.46	0.52	1.12	1.09	1.11	1.06	1.07
570.00	6.42	6.30	6.34	6.34	0.12	26.52	31.14	24.60	0.43	1.13	1.10	1.12	1.08	1.08
590.00	6.45	6.33	6.38	6.38	0.13	27.38	30.88	25.19	0.36	1.14	1.11	1.13	1.09	1.09
610.00	6.46	6.36	6.38	6.40	0.10	28.66	30.96	26.30	0.50	1.14	1.11	1.14	1.10	1.10
630.00	6.48	6.36	6.40	6.41	0.11	30.13	31.33	27.92	0.50	1.13	1.11	1.14	1.11	1.11
640.00	6.49	6.38	6.41	6.40	0.11	30.79	31.58	28.98	0.43	1.13	1.11	1.13	1.11	1.11
650.00	6.48	6.37	6.40	6.40	0.11	31.26	31.99	30.22	0.36	1.13	1.11	1.13	1.11	1.11
700.00	6.51	6.40	6.43	6.42	0.11	29.24	35.91	35.01	0.41	1.10	1.08	1.10	1.10	1.10



Mini-Circuits®

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

REV. OR
M72650
ED-8021
ZB4CS-700-10W
HY/ID/CP
000627