



ZTX689B

NPN SILICON PLANAR MEDIUM POWER HIGH GAIN TRANSISTOR

ZTX689B

ISSUE 1 - MAY 94

ELECTRICAL CHARACTERISTICS (at T_{amb} = 25°C)


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Transition Frequency	f _T	150			MHz	I _C =50mA, V _{CE} =5V f=50MHz
Input Capacitance	C _{ibo}		200		pF	V _{EB} =0.5V, f=1MHz
Output Capacitance	C _{obo}		16		pF	V _{CB} =10V, f=1MHz
Switching Times	t _{on}		30		ns	I _C =500mA, I _B =50mA I _{BZ} =50mA, V _{CC} =10V
	t _{off}		800		ns	

Measured under pulsed conditions. Pulse width=300us. Duty cycle ≤2%


HERMAL CHARACTERISTICS

PARAMETER	SYMBOL	MAX.	UNIT
Thermal Resistance: Junction to Ambient ₁	R _{th(j-amb)1}	175	°CW
Junction to Ambient ₂	R _{th(j-amb)2}	116	°CW
Junction to Case	R _{th(j-case)}	70	°CW

Device mounted on P.C.B. with copper equal to 1 sq. Inch minimum.



Derating curve




Maximum transient thermal impedance

FEATURES

- * 20 Volt V_{CEO}
- * Gain of 400 at I_C=2 Amps
- * Very low saturation voltage

APPLICATIONS

- * Darlington replacement
- * Flash gun converters
- * Battery powered circuits
- * Motor drivers



**E-Line
TO92 Compatible**

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V _{CBO}	20	V
Collector-Emitter Voltage	V _{CEO}	20	V
Emitter-Base Voltage	V _{EBO}	5	V
Peak Pulse Current	I _{CM}	8	A
Continuous Collector Current	I _C	3	A
Practical Power Dissipation*	P _{totp}	1.5	W
Power Dissipation at T _{amb} =25°C derate above 25°C	P _{tot}	1 5.7	W mW/°C
Operating and Storage Temperature Range	T _J ; T _{stg}	-55 to +200	°C

*The power which can be dissipated assuming the device is mounted in a typical manner on a P.C.B. with copper equal to 1 inch square minimum

ELECTRICAL CHARACTERISTICS (at T_{amb} = 25°C)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	V _{(BR)CBO}	20			V	I _C =100μA
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}	20			V	I _C =10mA*
Emitter-Base Breakdown Voltage	V _{(BR)EBO}	5			V	I _E =100μA
Collector Cut-Off Current	I _{CBO}			0.1	μA	V _{CB} =16V
Emitter Cut-Off Current	I _{EBO}			0.1	μA	V _{EB} =4V
Collector-Emitter Saturation Voltage	V _{CE(sat)}	0.1			V	I _C =0.1A, I _B =0.5mA*
		0.5			V	I _C =2A, I _B =10mA*
Base-Emitter Saturation Voltage	V _{BE(sat)}			0.9	V	I _C =1A, I _B =10mA*
Base-Emitter Turn-On Voltage	V _{BE(on)}			0.9	V	I _C =1A, V _{CE} =2V*
Static Forward Current Transfer Ratio	h _{FE}	500				I _C =0.1A, V _{CE} =2V*
		400				I _C =2A, V _{CE} =2V*
		150				I _C =6A, V _{CE} =2V*

[查询ZTX689B供应商](#)

[捷多邦, 专业PCB打样工厂, 24小时加急出货](#)

ZTX689B

NPN SILICON PLANAR MEDIUM POWER HIGH GAIN TRANSISTOR

ZTX689B

ISSUE 1 - MAY 94

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Transition Frequency	f_T	150			MHz	$I_C=50\text{mA}$, $V_{CE}=5\text{V}$ $f=50\text{MHz}$
Input Capacitance	C_{ibo}		200		pF	$V_{EB}=0.5\text{V}$, $f=1\text{MHz}$
Output Capacitance	C_{obo}		16		pF	$V_{CB}=10\text{V}$, $f=1\text{MHz}$
Switching Times	t_{on}		30		ns	$I_C=500\text{mA}$, $I_B=50\text{mA}$
	t_{off}		800		ns	$I_B=50\text{mA}$, $V_{CC}=10\text{V}$

Measured under pulsed conditions. Pulse width=300 μ s. Duty cycle $\leq 2\%$


HERMAL CHARACTERISTICS

PARAMETER	SYMBOL	MAX.	UNIT
Thermal Resistance: Junction to Ambient ₁	$R_{th(j-amb)1}$	175	$^{\circ}\text{C/W}$
Junction to Ambient ₂	$R_{th(j-amb)2}$	116	$^{\circ}\text{C/W}$
Junction to Case	$R_{th(j-case)}$	70	$^{\circ}\text{C/W}$

Device mounted on P.C.B. with copper equal to 1 sq. Inch minimum.

FEATURES

- * 20 Volt V_{CEO}
 - * Gain of 400 at $I_C=2$ Amps
 - * Very low saturation voltage
- APPLICATIONS
- * Darlington replacement
 - * Flash gun converters
 - * Battery powered circuits
 - * Motor drivers



E-Line
TO92 Compatible


ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	20	V
Collector-Emitter Voltage	V_{CEO}	20	V
Emitter-Base Voltage	V_{EBO}	5	V
Peak Pulse Current	I_{CM}	8	A
Continuous Collector Current	I_C	3	A
Practical Power Dissipation*	P_{totp}	1.5	W
Power Dissipation at $T_{amb}=25^{\circ}\text{C}$ derate above 25°C	P_{tot}	1	W
	$T_j: T_{stg}$	5.7	$\text{mW}/^{\circ}\text{C}$
Operating and Storage Temperature Range		-55 to +200	$^{\circ}\text{C}$


*The power which can be dissipated assuming the device is mounted in a typical manner on a P.C.B. with copper equal to 1 inch square minimum

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^{\circ}\text{C}$)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	20			V	$I_C=100\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	20			V	$I_C=10\text{mA}^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	5			V	$I_E=100\mu\text{A}$
Collector Cut-Off Current	I_{CBO}			0.1	μA	$V_{CB}=16\text{V}$
Emitter Cut-Off Current	I_{EBO}			0.1	μA	$V_{EB}=4\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		0.1		V	$I_C=0.1\text{A}$, $I_B=0.5\text{mA}^*$
			0.5		V	$I_C=2\text{A}$, $I_B=10\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$			0.9	V	$I_C=1\text{A}$, $I_B=10\text{mA}^*$
Base-Emitter Turn-On Voltage	$V_{BE(on)}$			0.9	V	$I_C=1\text{A}$, $V_{CE}=2\text{V}^*$
Static Forward Current Transfer Ratio	h_{FE}	500				$I_C=0.1\text{A}$, $V_{CE}=2\text{V}^*$
		400				$I_C=2\text{A}$, $V_{CE}=2\text{V}^*$
		150				$I_C=6\text{A}$, $V_{CE}=2\text{V}^*$





Derating curve



Maximum transient thermal impedance



ZTX689B

TYPICAL CHARACTERISTICS





VCE(sat) v IC

VCE(sat) v IC



hFE v IC

VBE(sat) v IC



VBE(on) v IC

Safe Operating Area