

查询ZVN3310F供应商

捷多邦，专业PCB打样工厂

, 24小时加急出货

SOT23 N-CHANNEL ENHANCEMENT MODE VERTICAL DMOS FET

ZVN3310F


ISSUE 3 – OCTOBER 1995 ★

FEATURES

- * 100 Volt V_{DS}
- * $R_{DS(on)} = 10\Omega$

COMPLEMENTARY TYPE - ZVP3310F

PART MARKING DETAIL - MF



SOT23

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE		UNIT
Drain-Source Voltage	V_{DS}	100		V
Continuous Drain Current at $T_{amb}=25^\circ C$	I_D	100		mA
Pulsed Drain Current	I_{DM}	2		A
Gate-Source Voltage	V_{GS}	± 20		V
Power Dissipation at $T_{amb}=25^\circ C$	P_{tot}	330		mW
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150		°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Drain-Source Breakdown Voltage	BV_{DSS}	100		V	$I_D=1mA, V_{GS}=0V$
Gate-Source Threshold Voltage	$V_{GS(th)}$	0.8	2.4	V	$I_D=1mA, V_{DS}=V_{GS}$
Gate-Body Leakage	I_{GSS}		20	nA	$V_{GS}=\pm 20V, V_{DS}=0V$
Zero Gate Voltage Drain Current	I_{DSS}		1 50	μA μA	$V_{DS}=100V, V_{GS}=0$ $V_{DS}=80V, V_{GS}=0V, T=125^\circ C$ (2)
On-State Drain Current(1)	$I_{D(on)}$	500		mA	$V_{DS}=25V, V_{GS}=10V$
Static Drain-Source On-State Resistance (1)	$R_{DS(on)}$		10	Ω	$V_{GS}=10V, I_D=500mA$
Forward Transconductance (1)(2)	g_{fs}	100		mS	$V_{DS}=25V, I_D=500mA$
Input Capacitance (2)	C_{iss}		40	pF	$V_{DS}=25V, V_{GS}=0V, f=1MHz$
Common Source Output Capacitance (2)	C_{oss}		15	pF	
Reverse Transfer Capacitance (2)	C_{rss}		5	pF	
Turn-On Delay Time (2)(3)	$t_{d(on)}$	3 typ	5	ns	$V_{DD} \approx 25V, I_D=500mA$
Rise Time (2)(3)	t_r	5 typ	7	ns	
Turn-Off Delay Time (2)(3)	$t_{d(off)}$	4 typ	6	ns	
Fall Time (2)(3)	t_f	5 typ	7	ns	

(1) Measured under pulsed conditions. Width=300μs. Duty cycle ≤2% (2) Sample test.

(3) Pulse Test Conditions: $V_{GS}=10V, V_{DS}=25V, I_D=500mA, t_{on}=t_{off}=10\mu s, t_{off}=10ms$

ZVN3310F

TYPICAL CHARACTERISTICS

