


查询"CT1008LSE-103J"供应商

CT1008LS Series

From 1.0 μH to 15 μH 


SPECIFICATIONS

Please specify tolerance code when ordering.
 CT1008LS-122 J = $\pm 5\%$, K = $\pm 10\%$, M = $\pm 20\%$
 CT1008LSE Please specify "F" for RoHS compliant

Part Number	Inductance (μH)	L Test Freq. (MHz)	Q Fact. Min.	Q Test Freq. (MHz)	SRF Min. (MHz)	DCR Max. (Ω)	Rated DC (mA)
CT1008LS_-102_	1.0	7.9	48	50	230	0.62	700
CT1008LS_-122_	1.2	7.9	48	50	210	0.68	650
CT1008LS_-152_	1.5	7.9	41	50	190	0.76	630
CT1008LS_-182_	1.8	7.9	39	50	170	0.84	600
CT1008LS_-222_	2.2	7.9	34	50	150	1.10	520
CT1008LS_-272_	2.7	7.9	34	50	135	1.28	490
CT1008LS_-332_	3.3	7.9	32	50	120	1.46	450
CT1008LS_-392_	3.9	7.9	32	7.9	105	1.56	420
CT1008LS_-472_	4.7	7.9	31	7.9	90	1.68	400
CT1008LS_-562_	5.6	7.9	31	7.9	80	1.82	380
CT1008LS_-682_	6.8	7.9	31	7.9	70	2.00	360
CT1008LS_-822_	8.2	7.9	23	7.9	65	2.65	330
CT1008LS_-103_	10	7.9	31	7.9	60	2.95	300
CT1008LS_-153_	15	7.9	35	7.9	38	2.40	450

PHYSICAL DIMENSIONS

Size	A Max.	B Max.	C Max.	D	E	F	G
mm	2.99	2.79	2.2	0.70	1.52	0.51	2.03
inches	0.118	0.110	0.087	0.028	0.060	0.020	0.080



CHARACTERISTICS

Description: SMD ferrite core wire-wound chip inductor

Applications: LC resonant circuits such as oscillator and signal generators, impedance matching, circuit isolation, RF filters, disk drives and computer peripherals, audio and video equipment, TV, radio and telecommunication equipment

Operating Temperature: -25°C to $+85^{\circ}\text{C}$

Inductance Tolerance: $\pm 5\%$, $\pm 10\%$, $\pm 20\%$

Testing: Inductance and Q are tested on an HP4286A at specified frequency

Packaging: Tape & Reel, 2,000 parts per reel


Miscellaneous: RoHS Compliant available.

Marking: Parts are marked with color dots (nH)

Additional Information: Additional electrical & physical information available upon request

Samples available. See website for ordering information.

PAD LAYOUT



03.09.09

Manufacturer of Passive Components

800-684-5322 Inside US

949-453-1811 Outside US

Copyright © 2009 by CT Magnetics, DBA Central Technologies. All rights reserved.

CT Magnetics reserves the right to make improvements or change specifications without notice