

Endured high voltage fixed thick film chip resistors

KTR18 (1206 size: 1 / 4W)

●Features

- 1) Power rating of 1 / 4W
- 2) Limiting element voltage of KTR series is 2.5 times compared with that of MCR series.
- 3) Highly reliable chip resistor Ruthenium oxide dielectric offers superior resistance to the elements.
- 4) ROHM resistors have approved ISO-9001 certification.

Design and specifications are subject to change without notice. Carefully check the specification sheet before using or ordering it.

●Ratings


Item	Conditions	Specifications	
Rated power	Power must be derated according to the power derating curve in Figure 1 when ambient temperature exceeds 70°C.	0.25W (1 / 4W) at 70°C	
	 <p>Fig.1</p>		
Rated voltage	The voltage rating is calculated by the following equation. If the value obtained exceeds the limiting element voltage, the voltage rating is equal to the maximum operating voltage.		
	$E = \sqrt{P \times R}$ <p>E: Rated voltage (V) P: Rated power (W) R: Nominal resistance (Ω)</p>	Limiting element voltage	500V
Nominal resistance	See Table 1.		
Operating temperature		-55°C to +155°C	

Table 1

Resistance tolerance	Resistance range (Ω)	Resistance temperature coefficient (ppm / °C)
F ($\pm 1\%$)	$1 \leq R \leq 10M$ (E24)	± 100
J ($\pm 5\%$)	$1 \leq R \leq 10M$ (E24)	± 200


- Before using components in circuits where they will be exposed to transients such as pulse loads (short-duration, high-level loads), be certain to evaluate the component in the mounted state. In addition, the reliability and performance of this component cannot be guaranteed if it is used with a steady state voltage that is greater than its rated voltage.

Resistors

●Characteristics



Item	Guaranteed value	Test conditions (JIS C 5201-1)
	Resistor type	
Resistance	J : $\pm 5\%$ F : $\pm 1\%$	JIS C 5201-1 4.5
Variation of resistance with temperature	See Table.1	JIS C 5201-1 4.8 Measurement : $-55 / +25 / +125^{\circ}\text{C}$
Overload	$\pm (2.0\% + 0.1\Omega)$	JIS C 5201-1 4.13 Rated voltage (current) $\times 2.5$, 2s. Limiting Element Voltage $\times 2$: 1000V
Solderability	A new uniform coating of minimum of 95% of the surface being immersed and no soldering damage.	JIS C 5201-1 4.17 Rosin-Ethanol (25%WT) Soldering condition : $235 \pm 5^{\circ}\text{C}$ Duration of immersion : $2.0 \pm 0.5\text{s.}$
Resistance to soldering heat	$\pm (1.0\% + 0.05\Omega)$ No remarkable abnormality on the appearance.	JIS C 5201-1 4.18 Soldering condition : $260 \pm 5^{\circ}\text{C}$ Duration of immersion : $10 \pm 1\text{s.}$
Rapid change of temperature	$\pm (1.0\% + 0.05\Omega)$	JIS C 5201-1 4.19 Test temp. : $-55^{\circ}\text{C} \text{ to } +125^{\circ}\text{C}$ 5cyc
Damp heat, steady state	$\pm (3.0\% + 0.1\Omega)$	JIS C 5201-1 4.24 40°C , 93%RH Test time : 1,000h to 1,048h
Endurance at 70°C	$\pm (3.0\% + 0.1\Omega)$	JIS C 5201-1 4.25.1 Rated voltage (current), 70°C 1.5h : ON – 0.5h : OFF Test time : 1,000h to 1,048h
Endurance	$\pm (3.0\% + 0.1\Omega)$	JIS C 5201-1 4.25.3 155°C Test time : 1,000h to 1,048h
Resistance to solvent	$\pm (1.0\% + 0.05\Omega)$	JIS C 5201-1 4.29 $23 \pm 5^{\circ}\text{C}$, Immersion cleaning, $5 \pm 0.5\text{min.}$ Solvent : 2-propanol
Bend strength of the end face plating	$\pm (1.0\% + 0.05\Omega)$ Without mechanical damage such as breaks.	JIS C 5201-1 4.33

●External dimensions (Unit : mm)




Resistors

●Packaging

Reel	Taping																												
 <p>(Unit: mm)</p> <table border="1"> <tr> <th>A</th><th>B</th><th>C</th><th>D</th></tr> <tr> <td>$\phi 180$ -1.5</td><td>$\phi 60$ 0</td><td>9 +1.0 0</td><td>$\phi 13$ ±0.2</td></tr> </table>	A	B	C	D	$\phi 180$ -1.5	$\phi 60$ 0	9 +1.0 0	$\phi 13$ ±0.2	 <table border="1"> <tr> <th>W</th><th>F</th><th>E</th><th>A₂</th><th>B₂</th></tr> <tr> <td>8.0 ± 0.3</td><td>3.5 ± 0.05</td><td>1.75 ± 0.1</td><td>1.95 ± 0.1 -0.05</td><td>3.5 ± 0.05</td></tr> <tr> <th>D₂</th><th>P₂</th><th>P₂</th><th>P₂</th><th>T₂</th></tr> <tr> <td>$\phi 1.5$ +0.1 0</td><td>4.0 ± 0.1</td><td>4.0 ± 0.1</td><td>2.0 ± 0.05</td><td>Max. 1.1</td></tr> </table>	W	F	E	A ₂	B ₂	8.0 ± 0.3	3.5 ± 0.05	1.75 ± 0.1	1.95 ± 0.1 -0.05	3.5 ± 0.05	D ₂	P ₂	P ₂	P ₂	T ₂	$\phi 1.5$ +0.1 0	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	Max. 1.1
A	B	C	D																										
$\phi 180$ -1.5	$\phi 60$ 0	9 +1.0 0	$\phi 13$ ±0.2																										
W	F	E	A ₂	B ₂																									
8.0 ± 0.3	3.5 ± 0.05	1.75 ± 0.1	1.95 ± 0.1 -0.05	3.5 ± 0.05																									
D ₂	P ₂	P ₂	P ₂	T ₂																									
$\phi 1.5$ +0.1 0	4.0 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	Max. 1.1																									

●Makeup of the part number



Packaging Specifications Code

Part No.	Code	Resistance tolerance		Packaging specifications	Reel	Basic ordering unit(pcs)
		J(±5%)	F(±1%)			
KTR18	EZP	◎	◎	Paper tape (4mm Pitch)	φ180mm (7in.)	5,000

Reel (φ180) : JEITA ET-7200B

◎ : Standard product

Resistors

●Dimensions




Fig.2 Dimensions (length)




Fig.3 Dimensions (width)




Fig.4 Dimensions (thickness)

●Electrical characteristics




Fig.5 Resistance (J class)




Fig.6 Resistance (F class)




Fig.7 Variation resistance with temperature (J class)




Fig.8 Variation resistance with temperature (F class)




Fig.9 Overload




Fig.10 Solderability

Resistors




Fig.11 Resistance to soldering heat




Fig.12 Rapid change of temperature




Fig.13 Damp heat , Steady state




Fig.14 Endurance (at70°C)




Fig.15 Endurance




Fig.16 Component solvent resistance




Fig.17 Bend strength of the end face plating

Appendix

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.