

M815

## Technical Data for Cellular Phone Battery Pack

NiCd

Specifications:

M815 Model No

Nickel Cadmium Battery Type

Panasonic J/EB-KJ3650 For use with

Black (B) Color

4 x GP90AAS Battery 4.8V

Nominal Voltage 4.0V Cut Off Voltage

900 mAh at 0.2C Capacity

90 minutes (estimated) Continuous Talk Time" 15 hours (estimated) Stand-by Time\*

: 0 - 45°C Charge Temperature Range

Discharge: -20 - 50°C Storage : -20 ~ 50℃

Casing Material ABS 115g Typical Weight

Battery should be charged in a GP or an Original Charging

Manufacturer charger.

First Charge Rate : 0.1C

Subsequent Charge Rate: 0.1C = 1C

Each battery is equipped with a polyswitch to protect Safety

battery from high temperature or short circuit. Each cell is also equipped with a safety vent system

in case abuses occur.

Six (6) months limited warranty from date of purchase. Warranty

"data valid only when the battery pack is on fully charged condition.

Panasonic is a registered trademerk of MATASUSHITA COMMUNICATION INDUSTRIAL CO.LTD

A product of the Gold Peak Industries Group

SYLVA PRODUCT SPEC : RWIS9823 RD

denutecturer reserves the right to atter or emend the design, model and specification without prior notice.

PAGE 2 OF 4