



SAW Components

SAW CELL / GPS / PCS Triplexer

Series/type:	B9100
Ordering code:	B39162B9100L410
Date:	October 16, 2009
Version:	2.1



SAW Components	B9100
SAW CELL / GPS / PCS Triplexer	859.0 / 1575.42 / 1920.0 MHz

Data Sheet




Application

- Low loss LTCC Triplexer for mobile phones covering Cellular, GPS and PCS band
- Usable passbands 70 MHz (CELL), 2 MHz (GPS), 140 MHz (PCS)
- Very low insertion attenuation in CELL, GPS and PCS band
- Very low amplitude ripple in all bands
- Integrated low loss GPS filter with single ended output 50 Ω
- Diversity antenna pinning
- No switches and control lines required
- Shunt inductor from ANT pin to ground used for ESD protection and matching




Features

- Package size 2.5 x 2.0 x 1.34 mm³
- Package code DCS6W
- RoHS compatible
- Approximate weight 0.022 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**



Pin configuration

- 1 ANT Input
- 3 GPS Output
- 4 CELL Output
- 6 PCS Output
- 2,5 Ground





SAW Components	B9100
SAW CELL / GPS / PCS Triplexer	859.0 / 1575.42 / 1920.0 MHz

Data Sheet



Characteristics

Temperature range for specification: T = -30 °C to +85 °C
 Terminating source impedance: Z_S = 50 Ω || 6.8 nH (ANT)
 Terminating load impedance: Z_L = 50 Ω (CELL, GPS + 1.5 nH or || 20n H, PCS)

		B9100			
		min.	typ. @ 25 °C	max.	
ANT - CELL					
Center frequency	f_C	—	859.0	—	MHz
Maximum insertion attenuation	α_{max}	—	0.6	0.8	dB
	824.0 ... 894.0 MHz				
VSWR		—	1.25	1.6	
	824.0 ... 894.0 MHz				
ANT - PCS					
Center frequency	f_C	—	1920.0	—	MHz
Maximum insertion attenuation	α_{max}	—	0.65	0.9	dB
	1850.0 ... 1990.0 MHz				
VSWR		—	1.25	1.6	
	1850.0 ... 1990.0 MHz				
ANT - GPS					
Center frequency	f_C	—	1575.42	—	MHz
Maximum insertion attenuation	α_{max}	—	1.25	1.8	dB
	1574.42 ... 1576.42 MHz				
VSWR		—	1.5	1.8	
	1574.42 ... 1576.42 MHz				
Attenuation	α				
	824.0 ... 849.0 MHz	32	45	—	dB
	1495.0 ... 1515.0 MHz	25	37	—	dB
	1610.0 ... 1625.0 MHz	10	25	—	dB
	1635.0 ... 1655.0 MHz	25	40	—	dB
	1710.0 ... 1755.0 MHz	35	42	—	dB
	1850.0 ... 1980.0 MHz	32	40	—	dB
	2400.0 ... 2500.0 MHz	23	29	—	dB
CELL - GPS					
Attenuation	α				
	1574.42 ... 1576.42 MHz	20	35	—	dB
	824.0 ... 849.0 MHz	42	46	—	dB
PCS - GPS					
Attenuation	α				
	1574.42 ... 1576.42 MHz	14	23	—	dB
	1850.0 ... 1910.0 MHz	42	46	—	dB



SAW Components	B9100
SAW CELL / GPS / PCS Triplexer	859.0 / 1575.42 / 1920.0 MHz

Data Sheet



Characteristics

Temperature range for specification: T = -30 °C to +85 °C
 Terminating source impedance: Z_S = 50 Ω || 6.8 nH (ANT)
 Terminating load impedance: Z_L = 50 Ω (CELL, GPS, PCS)

		B9100			
		min.	typ. @ 25 °C	max.	
ANT - CELL					
Center frequency	f_C	—	859.0	—	MHz
Maximum insertion attenuation	α_{max}	—	0.6	0.8	dB
824.0 ... 894.0 MHz					
VSWR		—	1.25	1.6	
824.0 ... 894.0 MHz					
ANT - PCS					
Center frequency	f_C	—	1920.0	—	MHz
Maximum insertion attenuation	α_{max}	—	0.65	0.9	dB
1850.0 ... 1990.0 MHz					
VSWR		—	1.25	1.6	
1850.0 ... 1990.0 MHz					
ANT - GPS					
Center frequency	f_C	—	1575.42	—	MHz
Maximum insertion attenuation	α_{max}	—	1.25	2.0	dB
1574.42 ... 1576.42 MHz					
VSWR		—	1.5	2.1	
1574.42 ... 1576.42 MHz					
Attenuation	α				
824.0 ... 849.0 MHz		32	45	—	dB
1495.0 ... 1515.0 MHz		25	37	—	dB
1610.0 ... 1625.0 MHz		10	24	—	dB
1635.0 ... 1655.0 MHz		25	39	—	dB
1710.0 ... 1755.0 MHz		35	41	—	dB
1850.0 ... 1980.0 MHz		32	39	—	dB
2400.0 ... 2500.0 MHz		23	29	—	dB
CELL - GPS					
Attenuation	α				
1574.42 ... 1576.42 MHz		20	35	—	dB
824.0 ... 849.0 MHz		42	46	—	dB
PCS - GPS					
Attenuation	α				
1574.42 ... 1576.42 MHz		14	23	—	dB
1850.0 ... 1910.0 MHz		42	46	—	dB



SAW Components	B9100
SAW CELL / GPS / PCS Triplexer	859.0 / 1575.42 / 1920.0 MHz
Data Sheet	SMD

Maximum ratings

Operable temperature range	T	-30/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	at GPS port
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 10 pulses
Input power at				
CELL port				effective power in the on-state
824 ... 849 MHz	P _{IN}	31	dBm	continuous wave signal
PCS port				
1850 ... 1910 MHz	P _{IN}	31	dBm	

¹⁾ acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses.



SAW Components

B9100


SAW CELL / GPS / PCS Triplexer

859.0 / 1575.42 / 1920.0 MHz


Data Sheet



ANT - CELL (transfer function, including PCB loss):



ANT - PCS (transfer function, including PCB loss):






SAW Components	B9100
SAW CELL / GPS / PCS Triplexer	859.0 / 1575.42 / 1920.0 MHz


Data Sheet



ANT - GPS (transfer function, including PCB loss):



CELL - GPS (transfer function, including PCB loss):





SAW Components

B9100


SAW CELL / GPS / PCS Triplexer

859.0 / 1575.42 / 1920.0 MHz

Data Sheet



PCS - GPS (transfer function, including PCB loss):







SAW Components	B9100
SAW CELL / GPS / PCS Triplexer	859.0 / 1575.42 / 1920.0 MHz

Data Sheet





Smith charts / VSWR

S₁₁ Antenna (matched with shunt inductor)



S₂₂ GPS



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B9100

SAW CELL / GPS / PCS Triplexer



859.0 / 1575.42 / 1920.0 MHz

Data Sheet





Smith charts / VSWR

S₃₃ CELL



S₄₄ PCS



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components	B9100
SAW CELL / GPS / PCS Triplexer	859.0 / 1575.42 / 1920.0 MHz
Data Sheet	

References

Type	B9100
Ordering code	B39162B9100L410
Marking and package	C61157-A3-A30
Packaging	F61074-V8225-Z000
Date codes	L_1126
S-parameters (6.8 nH ANT)	B9100_NB.s4p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2009. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DSSP, MiniBlue, MiniCell, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.