

查询"5962-87792012A"供应商

[illegible]

DESC FORM 193
SEP 87

* U.S. GOVERNMENT PRINTING OFFICE: 1987 — 748-129/60911
5962-E756

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:

5962-87792	01	E	X
Drawing number	Device type (1.2.1)	Case outline (1.2.2)	Lead finish per MIL-M-38510

1.2.1 Device type. The device type shall identify the circuit function as follows:

Device type	Generic number	Circuit function
01	10558	Quad 2-input multiplexer, noninverting

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

Outline letter	Case outline
E	D-2 (16-lead, .840" x .310" x .200"), dual-in-line package
F	F-5 (16-lead, .440" x .285" x .085"), flat package
2	C-2 (20-terminal, .358" x .358" x .100"), square chip carrier package

1.3 Absolute maximum ratings.

Supply voltage range ($V_{CC} = 0.0$ V) - - - - -	-8.0 V dc to 0.0 V dc
Input voltage range ($V_{CC} = 0.0$ V) - - - - -	0.0 V dc to -5.2 V dc
Output current (I_{OUT}):	
Continuous - - - - -	50 mA
Surge - - - - -	100 mA
Storage temperature range - - - - -	-65°C to +165°C
Lead temperature (soldering, 10 seconds) - - -	+300°C
Junction temperature (T_J) - - - - -	+165°C
Maximum power dissipation (P_D) - - - - -	319 mW
Thermal resistance, junction-to-case (θ_{JC}) - -	See MIL-M-38510, appendix C

1.4 Recommended operating conditions.

Supply voltage (V_{EE}) - - - - -	-5.46 V dc minimum to -4.94 V dc maximum
Ambient operating temperature range (T_A) - - -	-55°C to +125°C
Minimum high level input voltage (V_{IH}):	
$T_A = +25^\circ\text{C}$ - - - - -	-1.105 V
$T_A = +125^\circ\text{C}$ - - - - -	-1.000 V
$T_A = -55^\circ\text{C}$ - - - - -	-1.255 V
Maximum low-level input voltage (V_{IL}):	
$T_A = +25^\circ\text{C}$ - - - - -	-1.475 V
$T_A = +125^\circ\text{C}$ - - - - -	-1.400 V
$T_A = -55^\circ\text{C}$ - - - - -	-1.510 V

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-87792	
	REVISION LEVEL		SHEET 2

2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

SPECIFICATION

MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

STANDARD

MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Truth table. The truth table shall be as specified on figure 2.

3.2.3 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full ambient operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-87792	
		REVISION LEVEL	SHEET 3

TABLE I. Electrical performance characteristics.								
Test	Symbol	Conditions -55°C < T _A < +125°C unless otherwise specified	Group A subgroups	Limits		Unit		
				Min	Max			
Cases E, F, and 2 Quiescent tests 1/ 2/								
High level output voltage	V _{OH}	Outputs terminated through 100Ω to -2 V V _{CC} = 0.0 V V _{EE} = -5.2 V 3/	V _{IH}	V _{IL}				
			-0.780	-1.850	1	-0.930	-0.780	V
			-0.630	-1.820	2	-0.825	-0.630	
			-0.880	-1.920	3	-1.080	-0.880	
Low level output voltage	V _{OL}		-0.780	-1.850	1	-1.850	-1.620	V
			-0.630	-1.820	2	-1.820	-1.545	
				-0.880	-1.920	3	-1.920	-1.655
High level threshold output voltage	V _{OHA}		-1.105	-1.475	1	-0.950	-0.780	V
			-1.000	-1.400	2	-0.845	-0.630	
				-1.255	-1.510	3	-1.100	-0.880
Low level threshold output voltage	V _{OLA}		-1.105	-1.475	1	-1.850	-1.600	V
			-1.000	-1.400	2	-1.820	-1.525	
				-1.255	-1.510	3	-1.920	-1.635
Power supply drain current	I _{EE}	V _{EE} = -5.46 V V _{CC} = 0.0 V V _{IH} = -0.780 V at +25°C -0.630 V at +125°C -0.880 V at -55°C			1 2,3		-48 -53	mA
High level input current	I _{IH1}		Select		1 2,3		225 385	μA
	I _{IH2}		Inputs A and B		1 2,3		250 425	
Low level input current	I _{IL}	V _{EE} = -4.94 V V _{CC} = 0.0 V V _{IL} = -1.850 V at +25°C = -1.820 V at +125°C = -1.920 V at -55°C			1,3 2		0.5 0.3	μA
See footnotes at end of table.								
STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444			SIZE A		5962-87792			
				REVISION LEVEL	SHEET 4			

DESC FORM 193A
SEP 87

☆ U.S. GOVERNMENT PRINTING OFFICE: 1987-549-096

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C ≤ T _A ≤ +125°C unless otherwise specified	Group A subgroups	Limits		Unit
				Min	Max	
Cases E, F, and 2 AC tests						
Transition time	t _{TLH}	V _{EE} = -3.2 V V _{CC} = +2.0 V C _L ≤ 5 pF ±10% R _L = 100Ω 4/	9	1.5	3.3	ns
	t _{THL}		10	1.6	3.5	
			11	1.6	3.5	
Propagation delay time, A, B to Y	t _{PLH}		9	1.2	3.0	ns
	t _{PHL}		10	1.5	3.5	
	t _{PHH1}		11	1.5	3.5	
	t _{PLL1}					
Propagation delay time, Select to Y	t _{PHH2}		9	2.4	4.5	ns
	t _{PLL2}		10	2.5	5.0	
			11	2.5	5.0	

- 1/ The quiescent limits are determined after a device has reached thermal equilibrium. This is defined as the reading taken with the device in a socket with > 500 LFPM of +25°C, +125°C or -55°C (as applicable) air blowing on the unit in a transverse direction with power applied for at least 4 minutes before the reading is taken. This method was used for theoretical limit establishment only.
- 2/ The ΔT test method creates the limits and test conditions to be used after an increased ambient temperature has been stabilized by external thermal sources. This adjusted temperature simulates the quiescent method by increasing the specified case temperature (+25°C, +125°C, -55°C) with a ΔT. The ΔT is theoretically determined based on the power dissipation and thermal characteristics of the device and package used.
- 3/ The high and low level output current varies with temperature, and can be calculated using the following formula: I_{OH} = (V_{OH} - 2 V)/100Ω, I_{OL} = (V_{OL} - 2 V)/100Ω.
- 4/ The load circuit shall consist of the output under test going through R_L to GND and through C_L to the tester. C_L includes the scope probe, wiring, and stray capacitance without the package in the test fixture. t_{PHH} is measured from the midpoint of a high input to the midpoint of a high output. t_{PLL} is measured from the midpoint of a low input to the midpoint of a low output. Voltage waveforms for t_{PLH} and t_{PHL} shall be in accordance with method 3003 of MIL-STD-883 with the transition point being 50 percent of the maximum input or output voltage. Voltage waveforms for t_{TLH} and t_{THL} shall be in accordance with method 3004 of MIL-STD-883, with measurement points at 20 percent and 80 percent.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-87792
		REVISION LEVEL	SHEET 5

DESC FORM 193A
SEP 87

☆ U.S. GOVERNMENT PRINTING OFFICE: 1987-549-096

Terminal number	Terminal symbol		
	Case E	Case F	Case Z
1	Y1	B3	NC
2	Y2	Y4	Y1
3	A2	Y3	Y2
4	B2	V _{CC}	A2
5	A1	Y1	B2
6	B1	Y2	NC
7	NC	A2	A1
8	V _{EE}	B2	B1
9	SELECT	A1	NC
10	A4	B1	V _{EE}
11	B4	NC	SELECT
12	A3	V _{EE}	A4
13	B3	SELECT	B4
14	Y4	A4	A3
15	Y3	B4	B3
16	V _{CC}	A3	NC
17	---	---	Y4
18	---	---	Y3
19	---	---	V _{CC}
20	---	---	NC

NC = No connection

FIGURE 1. Terminal connections.

SELECT	Inputs		Output
	A	B	Y
L	L	X	L
L	H	X	H
H	X	L	L
H	X	H	H

H = High voltage level
L = Low voltage level
X = Irrelevant

FIGURE 2. Truth table.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A	5962-87792	
		REVISION LEVEL	SHEET 6

DESC FORM 193A
SEP 87

☆ U.S. GOVERNMENT PRINTING OFFICE: 1987-549-096

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition D, or E using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) $T_A = +125^{\circ}\text{C}$, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 4, 5, and 6 in table I, method 5005 of MIL-STD-883 shall be omitted.

c. Subgroups 7 and 8 tests shall verify the truth table specified on figure 2 herein.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-87792
		REVISION LEVEL	SHEET 7

DESC FORM 193A
SEP 87

☆ U.S. GOVERNMENT PRINTING OFFICE: 1987-549-096

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
 - (1) Test condition D, or E using the circuit submitted with the certificate of compliance (see 3.5 herein).
 - (2) $T_A = +125^{\circ}\text{C}$, minimum.
 - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	1
Final electrical test parameters (method 5004)	1*, 2, 3, 7*, 8, 9
Group A test requirements (method 5005)	1, 2, 3, 7, 8, 9, 10, 11
Groups C and D end-point electrical parameters (method 5005)	1, 2, 3

* PDA applies to subgroups 1 and 7.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

STANDARDIZED MILITARY DRAWING DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE A		5962-87792
		REVISION LEVEL	SHEET 8

DESC FORM 193A
SEP 87

☆ U.S. GOVERNMENT PRINTING OFFICE: 1967-549-096

查询"5962-87792012A"供应商

6.4 Approved source of supply. An approved source of supply is listed herein. Additional sources will be added as they become available. The vendor listed herein has agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number <u>1/</u>
5962-8779201EX	04713	10558/BEAJC
5962-8779201FX	04713	10558/BFAJC
5962-87792012X	04713	10558M/B2AJC

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE
number

04713

Vendor name
and address

Motorola, Incorporated
7402 South Price Road
Tempe, AZ 85283

**STANDARDIZED
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER
DAYTON, OHIO 45444

SIZE
A

5962-87792

REVISION LEVEL

SHEET 9

DESC FORM 193A
SEP 87

☆ U.S. GOVERNMENT PRINTING OFFICE: 1987-549-096