




### Ultrabright LED, Ø 5 mm Untinted Non-Diffused



#### FEATURES

- Untinted non diffused lens
- Utilizing ultrabright AllnGaP (AS)
- High luminous intensity
- High operating temperature:  
T<sub>j</sub> (chip junction temperature) up to 125 °C for AllnGaP devices
- Luminous intensity and color categorized for each packing unit
- ESD-withstand voltage: up to 2 kV according to JESD22-A114-B
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



RoHS COMPLIANT

#### DESCRIPTION

The TLC.51.. series is a clear, non diffused 5 mm LED for high end applications where supreme luminous intensity required.

These lamps with clear untinted plastic case utilize the highly developed ultrabright AllnGaP (AS).

The lens and the viewing angle is optimized to achieve best performance of light output and visibility.

#### PRODUCT GROUP AND PACKAGE DATA

- Product group: LED
- Package: 5 mm
- Product series: power
- Angle of half intensity: ± 9°

#### APPLICATIONS

- Interior and exterior lighting
- Outdoor LED panels
- Instrumentation and front panel indicators
- Central high mounted stop lights (CHMSL) for motor vehicles
- Replaces incandescent lamps
- Traffic signals
- Light guide design

#### PARTS TABLE

PART	COLOR, LUMINOUS INTENSITY	TECHNOLOGY
TLCR5100	Red, I <sub>v</sub> ≥ 4300 mcd	AllnGaP on GaAs
TLCY5100	Yellow, I <sub>v</sub> ≥ 3200 mcd	AllnGaP on GaAs
TLCY5100-ASZ	Yellow, I <sub>v</sub> ≥ 3200 mcd	AllnGaP on GaAs
TLCY5101	Yellow, I <sub>v</sub> = (5750 to 20 000) mcd	AllnGaP on GaAs
TLCY5101-AS12Z	Yellow, I <sub>v</sub> = (5750 to 20 000) mcd	AllnGaP on GaAs
TLCS5100	Super red, I <sub>v</sub> ≥ 2400 mcd	AllnGaP on GaAs
TLCO5100	Soft orange, I <sub>v</sub> ≥ 4300 mcd	AllnGaP on GaAs
TLCYG5100	Yellow green, I <sub>v</sub> ≥ 1350 mcd	AllnGaP on GaAs
TLCPG5100	Pure green, I <sub>v</sub> ≥ 430 mcd	AllnGaP on GaAs





ABSOLUTE MAXIMUM RATINGS <sup>1)</sup> TLCS/R/O/Y/YG/PG510.				
PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Reverse voltage <sup>2)</sup>		$V_R$	5	V
DC Forward current	$T_{amb} \leq 85\text{ }^\circ\text{C}$	$I_F$	50	mA
Surge forward current	$t_p \leq 10\text{ }\mu\text{s}$	$I_{FSM}$	1	A
Power dissipation		$P_V$	135	mW
Junction temperature		$T_j$	125	$^\circ\text{C}$
Operating temperature range		$T_{amb}$	- 40 to + 100	$^\circ\text{C}$
Storage temperature range		$T_{stg}$	- 40 to + 100	$^\circ\text{C}$
Soldering temperature	$t \leq 5\text{ s}$ , 2 mm from body	$T_{sd}$	260	$^\circ\text{C}$
Thermal resistance junction/ambient		$R_{thJA}$	300	K/W

Note:

- 1)  $T_{amb} = 25\text{ }^\circ\text{C}$ , unless otherwise specified
- 2) Driving the LED in reverse direction is suitable for a short term application

OPTICAL AND ELECTRICAL CHARACTERISTICS <sup>1)</sup> TLCS5100, SUPER RED							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous intensity <sup>2)</sup>	$I_F = 50\text{ mA}$	TLCS5100	$I_V$	2400	7500		mcd
Dominant wavelength	$I_F = 50\text{ mA}$		$\lambda_d$	626	630	638	nm
Peak wavelength	$I_F = 50\text{ mA}$		$\lambda_p$		641		nm
Spectral bandwidth at 50 % $I_{rel\ max.}$	$I_F = 50\text{ mA}$		$\Delta\lambda$		20		nm
Angle of half intensity	$I_F = 50\text{ mA}$		$\phi$		$\pm 9$		deg
Forward voltage	$I_F = 50\text{ mA}$		$V_F$		2.1	2.7	V
Reverse voltage	$I_R = 10\text{ }\mu\text{A}$		$V_R$	5			V
Temperature coefficient of $V_F$	$I_F = 50\text{ mA}$		$TC_{V_F}$		- 2		mV/K
Temperature coefficient of $\lambda_d$	$I_F = 50\text{ mA}$		$TC_{\lambda_d}$		0.04		nm/K

Note:

- 1)  $T_{amb} = 25\text{ }^\circ\text{C}$ , unless otherwise specified
- 2) In one packing unit  $I_{Vmax.}/I_{Vmin.} \leq 2.0$

OPTICAL AND ELECTRICAL CHARACTERISTICS <sup>1)</sup> TCR5100, RED							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous intensity <sup>2)</sup>	$I_F = 50\text{ mA}$	TCR5100	$I_V$	4300	11 000		mcd
Dominant wavelength	$I_F = 50\text{ mA}$		$\lambda_d$	611	616	622	nm
Peak wavelength	$I_F = 50\text{ mA}$		$\lambda_p$		622		nm
Spectral bandwidth at 50 % $I_{rel\ max.}$	$I_F = 50\text{ mA}$		$\Delta\lambda$		18		nm
Angle of half intensity	$I_F = 50\text{ mA}$		$\phi$		$\pm 9$		deg
Forward voltage	$I_F = 50\text{ mA}$		$V_F$		2.1	2.7	V
Reverse voltage	$I_R = 10\text{ }\mu\text{A}$		$V_R$	5			V
Temperature coefficient of $V_F$	$I_F = 50\text{ mA}$		$TC_{V_F}$		- 3.5		mV/K
Temperature coefficient of $\lambda_d$	$I_F = 50\text{ mA}$		$TC_{\lambda_d}$		0.05		nm/K

Note:

- 1)  $T_{amb} = 25\text{ }^\circ\text{C}$ , unless otherwise specified
- 2) In one packing unit  $I_{Vmax.}/I_{Vmin.} \leq 2.0$



<b>OPTICAL AND ELECTRICAL CHARACTERISTICS <sup>1)</sup> TLCO5100, SOFT ORANGE</b>							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous intensity <sup>2)</sup>	I <sub>F</sub> = 50 mA	TLCO5100	I <sub>V</sub>	4300	12 000		mcd
Dominant wavelength	I <sub>F</sub> = 50 mA		λ <sub>d</sub>	600	605	611	nm
Peak wavelength	I <sub>F</sub> = 50 mA		λ <sub>p</sub>		611		nm
Spectral bandwidth at 50 % I <sub>rel max.</sub>	I <sub>F</sub> = 50 mA		Δλ		17		nm
Angle of half intensity	I <sub>F</sub> = 50 mA		φ		± 9		deg
Forward voltage	I <sub>F</sub> = 50 mA		V <sub>F</sub>		2.1	2.7	V
Reverse voltage	I <sub>R</sub> = 10 μA		V <sub>R</sub>	5			V
Temperature coefficient of V <sub>F</sub>	I <sub>F</sub> = 50 mA		TC <sub>V<sub>F</sub></sub>		- 2.5		mV/K
Temperature coefficient of λ <sub>d</sub>	I <sub>F</sub> = 50 mA		TCλ <sub>d</sub>		0.08		nm/K

Note:

<sup>1)</sup> T<sub>amb</sub> = 25 °C, unless otherwise specified

<sup>2)</sup> In one packing unit I<sub>Vmax.</sub>/I<sub>Vmin.</sub> ≤ 2.0

<b>OPTICAL AND ELECTRICAL CHARACTERISTICS <sup>1)</sup> TLCY5100, TLCY5101, YELLOW</b>							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous intensity <sup>2)</sup>	I <sub>F</sub> = 50 mA	TLCY5100	I <sub>V</sub>	3200	7500		mcd
		TLCY5101	I <sub>V</sub>	5750		20 000	mcd
Dominant wavelength	I <sub>F</sub> = 50 mA		λ <sub>d</sub>	585	590	597	nm
Peak wavelength	I <sub>F</sub> = 50 mA		λ <sub>p</sub>		593		nm
Spectral bandwidth at 50 % I <sub>rel max.</sub>	I <sub>F</sub> = 50 mA		Δλ		17		nm
Angle of half intensity	I <sub>F</sub> = 50 mA		φ		± 9		deg
Forward voltage	I <sub>F</sub> = 50 mA		V <sub>F</sub>		2.1	2.7	V
Reverse voltage	I <sub>R</sub> = 10 μA		V <sub>R</sub>	5			V
Temperature coefficient of V <sub>F</sub>	I <sub>F</sub> = 50 mA		TC <sub>V<sub>F</sub></sub>		- 3.5		mV/K
Temperature coefficient of λ <sub>d</sub>	I <sub>F</sub> = 50 mA		TCλ <sub>d</sub>		0.1		nm/K

Note:

<sup>1)</sup> T<sub>amb</sub> = 25 °C, unless otherwise specified

<sup>2)</sup> In one packing unit I<sub>Vmax.</sub>/I<sub>Vmin.</sub> ≤ 2.0

<b>OPTICAL AND ELECTRICAL CHARACTERISTICS <sup>1)</sup> TLCYG5100, YELLOW GREEN</b>							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous intensity <sup>2)</sup>	I <sub>F</sub> = 50 mA	TLCYG5100	I <sub>V</sub>	1350	3500		mcd
Dominant wavelength	I <sub>F</sub> = 50 mA		λ <sub>d</sub>	565	572	576	nm
Peak wavelength	I <sub>F</sub> = 50 mA		λ <sub>p</sub>		574		nm
Spectral bandwidth at 50 % I <sub>rel max.</sub>	I <sub>F</sub> = 50 mA		Δλ		15		nm
Angle of half intensity	I <sub>F</sub> = 50 mA		φ		± 9		deg
Forward voltage	I <sub>F</sub> = 50 mA		V <sub>F</sub>		2.2	2.7	V
Reverse voltage	I <sub>R</sub> = 10 μA		V <sub>R</sub>	5			V
Temperature coefficient of V <sub>F</sub>	I <sub>F</sub> = 50 mA		TC <sub>V<sub>F</sub></sub>		- 4.5		mV/K
Temperature coefficient of λ <sub>d</sub>	I <sub>F</sub> = 50 mA		TCλ <sub>d</sub>		0.1		nm/K

Note:

<sup>1)</sup> T<sub>amb</sub> = 25 °C, unless otherwise specified

<sup>2)</sup> In one packing unit I<sub>Vmax.</sub>/I<sub>Vmin.</sub> ≤ 2.0



OPTICAL AND ELECTRICAL CHARACTERISTICS <sup>1)</sup> TLCPG5100, PURE GREEN							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Luminous intensity <sup>2)</sup>	$I_F = 50 \text{ mA}$	TLCPG5100	$I_V$	430	1250		mcd
Dominant wavelength	$I_F = 50 \text{ mA}$		$\lambda_d$	555	562	567	nm
Peak wavelength	$I_F = 50 \text{ mA}$		$\lambda_p$		563		nm
Spectral bandwidth at 50 % $I_{rel \text{ max.}}$	$I_F = 50 \text{ mA}$		$\Delta\lambda$		20		nm
Angle of half intensity	$I_F = 50 \text{ mA}$		$\varphi$		$\pm 9$		deg
Forward voltage	$I_F = 50 \text{ mA}$		$V_F$		2.2	2.7	V
Reverse voltage	$I_R = 10 \mu\text{A}$		$V_R$	5			V
Temperature coefficient of $V_F$	$I_F = 50 \text{ mA}$		$TC_{V_F}$		- 3.5		mV/K
Temperature coefficient of $\lambda_d$	$I_F = 50 \text{ mA}$		$TC_{\lambda_d}$		0.1		nm/K

Note:

<sup>1)</sup>  $T_{amb} = 25 \text{ }^\circ\text{C}$ , unless otherwise specified

<sup>2)</sup> In one packing unit  $I_{Vmax.}/I_{Vmin.} \leq 2.0$

LUMINOUS INTENSITY CLASSIFICATION		
GROUP	LUMINOUS INTENSITY (mcd)	
	MIN.	MAX.
STANDARD		
BB	430	860
CC	575	1150
DD	750	1500
EE	1000	2000
FF	1350	2700
GG	1800	3600
HH	2400	4800
II	3200	6400
KK	4300	8600
LL	5750	11 500
MM	7500	15 000
NN	10 000	20 000
PP	13 500	27 000
QQ	18 000	36 000
RR	24 000	48 000
SS	32 000	64 000
TT	43 000	86 000
UU	57 500	115 000

Note:

Luminous intensity is tested at a current pulse duration of 25 ms and an accuracy of  $\pm 11 \%$ .

The above type numbers represent the order groups which include only a few brightness groups. Only one group will be shipped on each bag (there will be no mixing of two groups on each bag).

In order to ensure availability, single brightness groups will not be orderable.

In a similar manner for colors where wavelength groups are measured and binned, single wavelength groups will be shipped in any one bag.

In order to ensure availability, single wavelength groups will not be orderable.


COLOR CLASSIFICATION										
GROUP	DOM. WAVELENGTH (nm)									
	RED		SOFT ORANGE		YELLOW		YELLOW GREEN		PURE GREEN	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
0					585	588			555	559
1	611	618			587	591			558	561
2	614	622	600	603	589	594			560	563
3			602	605	592	597			562	565
4			604	607					564	567
5			606	609			565	570		
6			608	611			567	572		
7							569	574		
8							571	576		

Note:


Wavelengths are tested at a current pulse duration of 25 ms and an accuracy of ± 1 nm.

**TYPICAL CHARACTERISTICS**


T<sub>amb</sub> = 25 °C, unless otherwise specified




16710\_1  
Figure 1. Forward Current vs. Ambient Temperature



94 8351  
Figure 3. Relative Radiant Sensitivity vs. Angular Displacement



17045\_1  
Figure 2. Relative Intensity vs. Wavelength



15974\_1  
Figure 4. Forward Current vs. Forward Voltage




Figure 5. Forward Current vs. Forward Voltage




Figure 8. Relative Luminous Intensity vs. Ambient Temperature




Figure 6. Relative Luminous Flux vs. Forward Current




Figure 9. Change of Forward Voltage vs. Ambient Temperature




Figure 7. Change of Dominant Wavelength vs. Ambient Temperature




Figure 10. Relative Intensity vs. Wavelength




Figure 11. Relative Luminous Flux vs. Forward Current




Figure 14. Change of Forward Voltage vs. Ambient Temperature




Figure 12. Changes of Dominant Wavelength vs. Forward Current




Figure 15. Change of Dominant Wavelength vs. Ambient Temperature




Figure 13. Relative Luminous Intensity vs. Ambient Temperature




Figure 16. Relative Intensity vs. Wavelength




Figure 17. Relative Luminous Flux vs. Forward Current




Figure 20. Change of Forward Voltage vs. Ambient Temperature




Figure 18. Change of Dominant Wavelength vs. Forward Current




Figure 21. Change of Dominant Wavelength vs. Ambient Temperature




Figure 19. Relative Luminous Intensity vs. Ambient Temperature




Figure 22. Relative Intensity vs. Wavelength






Figure 23. Relative Luminous Flux vs. Forward Current




Figure 26. Change of Dominant Wavelength vs. Ambient Temperature




Figure 24. Change of Dominant Wavelength vs. Forward Current




Figure 27. Change of Forward Voltage vs. Ambient Temperature




Figure 25. Relative Luminous Intensity vs. Ambient Temperature




Figure 28. Relative Intensity vs. Wavelength




Figure 29. Relative Luminous Flux vs. Forward Current




Figure 32. Change of Dominant Wavelength vs. Ambient Temperature




Figure 30. Change of Dominant Wavelength vs. Forward Current




Figure 33. Change of Forward Voltage vs. Ambient Temperature




Figure 31. Relative Luminous Intensity vs. Ambient Temperature




Figure 34. Relative Intensity vs. Wavelength




Figure 35. Relative Luminous Flux vs. Forward Current




Figure 38. Change of Dominant Wavelength vs. Ambient Temperature




Figure 36. Change of Dominant Wavelength vs. Forward Current




Figure 39. Change of Forward Voltage vs. Ambient Temperature







Figure 37. Relative Luminous Intensity vs. Ambient Temperature

**PACKAGE DIMENSIONS** in millimeters



Drawing-No.: 6.544-5258.04-4  
Issue: 8; 19.05.09  
96 12121

**TAPE**




Figure 40. LED in Tape

94 8671

**AMMOPACK**





Figure 41. Tape Direction

94 8667-1

Note:  
AS12Z and AS21Z still valid for already existing types BUT NOT FOR NEW DESIGN



**TAPE DIMENSIONS** in millimeters



Quantity per:	Reel (Mat.-no. 1764)
	1000

94 8172

Option	Dim. "H" ± 0.5 mm
AS	17.3

## **Disclaimer**

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.