

# Switchmode Series NPN Silicon Power Transistor

Designed for high-speed applications.

## Features

- Switchmode Power Supplies
- High Frequency Converters
- Relay Drivers
- Driver
- Pb-Free Package is Available\*

## MAXIMUM RATINGS (T<sub>J</sub> = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V <sub>CEO(sus)</sub>	90	Vdc
Collector-Base Voltage	V <sub>CB0</sub>	180	Vdc
Emitter-Base Voltage	V <sub>EBO</sub>	7.0	Vdc
Collector Current – Continuous	I <sub>C</sub>	20	Adc
– Peak (pw 10 ms)	I <sub>CM</sub>	30	Apk
Base Current – Continuous	I <sub>B</sub>	4.0	Adc
	I <sub>BM</sub>	6.0	Adc
Total Power Dissipation @ T <sub>C</sub> = 25°C	P <sub>D</sub>	85	W
Total Power Dissipation @ T <sub>C</sub> = 60°C	P <sub>D</sub>	65	W
Operating and Storage Junction Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	- 65 to +150	°C

## THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction-to-Case	R <sub>θJC</sub>	1.76	°C/W

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.




**ON Semiconductor**®

<http://onsemi.com>

**12 AMPERES  
NPN SILICON  
POWER TRANSISTORS  
90 VOLTS, 85 WATTS**

## MARKING DIAGRAM



TO-220  
CASE 221A  
STYLE 1



BUV26 = Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
G = Pb-Free Package

## ORDERING INFORMATION

Device	Package	Shipping
BUV26	TO-220	50 Units/Rail
BUV26G	TO-220 (Pb-Free)	50 Units/Rail

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# BUV26

## 查问"BUV26G"供应商

ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

### OFF CHARACTERISTICS

Collector–Emitter Sustaining Voltage (I <sub>C</sub> = 200 mA, I <sub>B</sub> = 0, L = 25 mH)	V <sub>CEO(sus)</sub>	90	–	Vdc
Collector Cutoff Current at Reverse Bias (V <sub>CE</sub> = 180 V, V <sub>BE</sub> = –1.5 V, T <sub>C</sub> = 125°C)	I <sub>CEX</sub>	–	1.0	mAdc
Emitter Base Reverse Voltage (I <sub>E</sub> = 50 mA)	V <sub>EBO</sub>	7.0	30	V
Emitter Cutoff Current (V <sub>EB</sub> = 5.0 V)	I <sub>EBO</sub>	–	1.0	mAdc
Collector Cutoff Current (V <sub>CE</sub> = 180 V, R <sub>BE</sub> = 50 Ω, T <sub>C</sub> = 125°C)	I <sub>CER</sub>	–	3.0	mAdc

### ON CHARACTERISTICS

Collector–Emitter Saturation Voltage (I <sub>C</sub> = 6.0 A, I <sub>B</sub> = 0.4 A) (I <sub>C</sub> = 12 A, I <sub>B</sub> = 1.2 A)	V <sub>CE(sat)</sub>	– –	0.6 1.5	Vdc
Base–Emitter Saturation Voltage (I <sub>C</sub> = 12 A, I <sub>B</sub> = 1.2 A)	V <sub>BE(sat)</sub>	–	2.0	Vdc

### SWITCHING CHARACTERISTICS (Resistive Load)

Turn On Time	I <sub>C</sub> = 12 A, I <sub>B</sub> = 1.2 A V <sub>CC</sub> = 50 V, V <sub>BE</sub> = 6.0 V R <sub>B2</sub> = 2.5 Ω	t <sub>on</sub>	–	0.6	μs
Storage Time		t <sub>s</sub>	–	1.0	
Fall Time		t <sub>f</sub>	–	0.15	

### SWITCHING CHARACTERISTICS (Inductive Load)

Storage Time	V <sub>CC</sub> = 50 V, I <sub>C</sub> = 12 A I <sub>B(end)</sub> = 1.2 A, V <sub>B</sub> = 5.0 V L <sub>B</sub> = 0.5 μH, T <sub>J</sub> = 125°C	T <sub>s</sub>	–	2.0	μs
Fall Time		T <sub>f</sub>	–	.15	


1. Pulse Test: Pulse width ≤ 300 μs; Duty cycle ≤ 2%.

# BUV26

查询"BUV26G"供应商

## PACKAGE DIMENSIONS

TO-220  
CASE 221A-07  
ISSUE AA



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.570	0.620	14.48	15.75
B	0.380	0.405	9.66	10.28
C	0.160	0.190	4.07	4.82
D	0.025	0.035	0.64	0.88
F	0.142	0.147	3.61	3.73
G	0.095	0.105	2.42	2.66
H	0.110	0.155	2.80	3.93
J	0.014	0.022	0.36	0.55
K	0.500	0.562	12.70	14.27
L	0.045	0.060	1.15	1.52
N	0.190	0.210	4.83	5.33
Q	0.100	0.120	2.54	3.04
R	0.080	0.110	2.04	2.79
S	0.045	0.055	1.15	1.39
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	---	1.15	---
Z	---	0.080	---	2.04

STYLE 1:

1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.