



#### FEATURES:

- ✓ High temperature insulation material for use up to +428°F, (+220°C).
- ✓ Mounts in panels from .070" to .375" (1.60mm to 9.53mm).
- ✓ Mates with Pomona's MDP and all standard double banana plugs.
- ✓ Ideal for mounting to panels or chassis boxes.

#### MATERIALS:

**Banana Jack Insulation:** Polyphenylene Sulfide Molded to Banana Jack Bodies, Color Blue and Black

**Mounting Plate:** Polyphenylene Sulfide, Color Black

**Insulator:** Polyphenylene Sulfide

**Hex Nut:** 3/8" 1/4-32: Nickel Plated Brass

**Lockwasher:** 1/4 Internal Tooth, Nickel Plated Steel

**Banana Jack Body/Solder Turret:** Brass, H.H. per QQ-B-626, Alloy 360, 1/2 Hard.

**Finish, Banana Jack Body/Solder Turret:** Bright tin plated per MIL-T-10727.

#### RATINGS:

**Operating Voltage:** Hands free usage in controlled voltage environments: 2500 Vrms maximum. *For CE compliance:* not intended for hand-held use at voltages above 33 Vrms/70 Vdc.

**Current:** 15 Amperes

**Operating Temperature:** +428°F (+220°C).

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)

For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)



**Model 5233**  
**High Temperature Double**  
**Banana Jack** **CE**

---

**ORDERING INFORMATION:**

Model: 5233-0 (Black base with one black and one blue banana jack)

All dimensions are in inches. Tolerances (except noted): .xx =  $\pm .02$ " (.51 mm), .xxx =  $\pm .005$ " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

---

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)  
For "Where to Buy" information, visit the Pomona web site at [www.pomonaelectronics.com](http://www.pomonaelectronics.com)