




# 10x9.5 Square/Multiturn/Trimming Potentiometer


-- 3296X--

... Install dimension



↑ click for larger photo

... Mutual dimension



↑ click for larger photo

## Standard Resistance Table

Resistance Code	Resistance (Ohms)
100	10
200	20
500	50
101	100
201	200
501	500
102	1,000
202	2,000
502	5,000
103	10,000
203	20,000
503	50,000
104	100,000
204	200,000
504	500,000
105	1,000,000
205	2,000,000

Special resistances available

Electrical Characteristics  
Standard Resistance Range.....50Ω~2MΩ  
Resistance.....±10%  
Tolerance.....≤1%或

Absolute Minimum Resistance.....≤1%或

10Ω

Contact Resistance Variation.....CRV≤3%或

5Ω

Insulation Resistance.....R1≥1GΩ

(100Vac)

Withstand

Voltage.....640Vac

Effective Travel.....28 turns nom

## Environmental Characteristics

Power Rating, 315 volts max

0.5W@70°C, 0W@125°C

Temperature Range.....-55°C~125°C

Temperature Coefficient.....±50ppm/°C

Temperature Variation.....-55°C, 30min, +125°C

30min cycles

△R≤5%R, △(Uab/Uac)≤5%

Vibration.....10~500Hz, 0.75mm, 6h,

△R≤5%R, △(Uab/Uac)≤7.5%

Collision.....390m/s<sup>2</sup>, 400cycles, △R≤5%R

Electrical Endurance at

70°C.....0.5W@70°C

1000h, △R≤10%R, CRV≤3% or 5Ω

How To Order

3296 X 103

Model

Style

Resistance Code

[查询"3296X103"供应商](#)