

Poly-carbonmonofluoride (BR Series) and Manganese Dioxide (CR Series)

[查询"CR20321VS1"供应商](#)

COIN CELL TAB CONFIGURATIONS

Model Number	Tab Type		Configuration Diagram No.
	With Insulation Wrap	Without Insulation Wrap	
BR TYPE			
BR1220	/1HF	/1HE	1
BR1220	/1VC	/1VB	2
BR1225	/1HC	/1HB	3
BR1225	/1VC		4
BR1632	/1HF		5
BR2016	/1F2		6
BR2032	/1HM		7
BR2032		/1HG	8
BR2032	/1HS	/1HSE	9
BR2032	/1GUF	/1GU	10
BR2032	/1HF	/1HE	11
BR2032		/1VB	12
BR2032	/1GVF	/1GV	13
BR2032	/1F4		14
BR2032	/1F2		15
BR2325	/1HC	/1HB	16
BR2325	/1HM		17
BR2325		/1HG	18
BR2325	/2HC		19
BR2325		/1VG	20
BR2330	/1HF	/1HE	21
BR2330	/1GUF	/1GU	22
BR2330	/1VC	/1VB	23
BR2330	/1GVF	/1GV	24
BR2330	/1F3		25
BR2330	/1F4C		26
BR3032	/1VC		27
BR3032	/1F2		28

Model Number	Tab Type		Configuration Diagram No.
	With Insulation Wrap	Without Insulation Wrap	
CR TYPE			
CR1220	/1HF	/1HE	1
CR1220	/1VC	/1VB	2
CR1616		/1F2	29
CR1632	/1HF		5
CR1632		/1HE	30
CR2016	/1F2		6
CR2025	/1F2		31
CR2032		/1HU3	32
CR2032	/1VS1		33
CR2032		/1HG	8
CR2032	/1HS	/1HSE	9
CR2032	/1GUF	/1GU	10
CR2032	/1HF	/1HE	11
CR2032		/1VB	12
CR2032	/1GVF	/1GV	13
CR2032	/1F4		14
CR2032	/1F2		15
CR2330	/1HF	/1HE	21
CR2330	/1GUF	/1GU	22
CR2330	/1VC	/1VB	23
CR2330	/1GVF	/1GV	24
CR2330	/1F3		25
CR2330	/1F4C		26
CR2354	/1HF	/1HE	34
CR2354	/1GUF	/1GU	35
CR2354	/1VC	/1VB	36
CR3032	/1VC		27
CR3032	/1F2		28
CR2477	/1VC	/1VB	37
CR2477	/1HF	/1HE	38
CR2450	/H1A		39
CR2450	/G1A		40

* Refer to page 60 for BR "A" (High Temp) Tab configurations.
Please contact Panasonic for requests on custom Tab configurations. Minimum order requirements may apply



BR & CR Series Coin Cell Tab Configurations

[查询"CR20321VS1"供应商](#)

DIMENSIONS / MM (INCH)

Model No.	Dimensions/mm (inch)	Model No.	Dimensions/mm (inch)
BR/CR1220/1HF 1HE	①	BR/CR1220/1VC 1VB	②
BR1225/1HC 1HB	③	BR1225/1VC	④
BR/CR1632/1HF	⑤	BR/CR2016/1F2	⑥
BR2032/1HM	⑦	BR/CR2032/1HG	⑧

查询"CR20321VS1"供应商

Model No.	Dimensions/mm (inch)	Model No.	Dimensions/mm (inch)
BR/CR2032/1HS 1HSE	⑨ Insulation Wrap (yellow) 3.2(0.13) 20(0.79) 3.9(0.15) 0.75(0.03) 3.5(0.14) 15.2±0.5(0.60±0.02) 9.1(0.36) 0.2(0.008) 0.75(0.03) 3.5(0.14)	BR/CR2032/1GUF 1GU	⑩ 3.2(0.13) 20(0.79) 4.0(0.16) 3.5(0.14) 0.75(0.03) 17.8±0.5(0.70±0.02) 9.1(0.36) 0.2(0.008) 0.75(0.03) 3.5(0.14) 5.08(0.20) 10.16(0.40)
BR/CR2032/1HF 1HE	⑪ Insulation Wrap (yellow) 20.5(0.81) 20(0.79) 4.0(0.16) 3.5(0.14) 3.9(0.15) 0.75(0.03) 3.2(0.13) 0.2(0.008) 9.1(0.36) 0.75(0.03) 20.5±0.5(0.81±0.02)	BR/CR2032/1VB	⑫ Red terminal indicates positive 20 ± 0.2 (0.79 ± 0.01) 3.2 (0.13) 10.7 ± 0.5 (0.42) 0.75 (0.03) 0.2 (0.008) 3.9 (0.15) Pre-soldered A B
BR/CR2032/1GVF 1GV	⑬ 20(0.79) 3.2(0.13) 3.0(0.12) 3.5(0.14) 0.75(0.08) 10.16±0.3(0.40±0.01) 3.9(0.15) 0.2(0.008) 0.75(0.03) 5.08±1(0.20±0.04)	BR/CR2032/1F4	⑭ Insulation Wrap (yellow) 20(0.79) 3.2(0.13) 5.0(0.40) 0.15(0.006) 3.8(0.15) 7.45±0.5(0.29±0.02)
BR/CR2032/1F2	⑮ Insulation Wrap (yellow) 20(0.79) 3.0(0.13) 7.0±0.5(0.28±0.02) 7.0±1(0.28±0.04) 3.2(0.13) 5.0(0.20) 0.15(0.06) 3.8(0.15)	BR2325/1HC 1HB	⑯ Insulation Wrap (yellow) 2.5(0.10) 23(0.91) 9.9(0.39) 0.2(0.008) 0.75(0.03) 5.0(0.20) 20.5±1(0.81±0.04) 0.75(0.03) 5.0(0.20)

BR & CR Series Coin Cell Tab Configurations

[查询"CR20321VS1"供应商](#)

DIMENSIONS / MM (INCH) cont.

Model No.	Dimensions/mm (inch)	Model No.	Dimensions/mm (inch)
BR2325/1HM		BR2325/1HG	
BR2325/2HC (2 cells in series, 6V)		BR2325/1VG	
BR/CR2330/1HF 1HE		BR/CR2330/1GU 1GUF	
BR/CR2330/1VC 1VB		BR/CR2330/1GVF 1GV	

BR & CR Series Coin Cell Tab Configurations

[查询"CR20321VS1"供应商](#)

DIMENSIONS / MM (INCH) cont.

Model No.	Dimensions/mm (inch)	Model No.	Dimensions/mm (inch)
BR/CR2330/1F3		BR/CR2330/1F4C	
BR/CR3032/1VC		BR/CR3032/1F2	
CR1616/1F2		CR1632/1HE	
CR2025/1F2		CR2032/1HU3	

BR & CR Series Coin Cell Tab Configurations

[查询"CR20321VS1"供应商](#)

DIMENSIONS / MM (INCH) cont.

Model No.	Dimensions/mm (inch)	Model No.	Dimensions/mm (inch)
CR2032/1VS1	33 Insulation Wrap (yellow) 20(0.79) 3.2(0.13) MAX.0.5(0.02) 3.0(0.12) 1.8(0.07) 0.75(0.03) 4.0(0.16) 0.2(0.008) 3.9(0.15) 10.2±0.5(0.40±0.02)	CR2354/1HF 1HE	34 Insulation Wrap (yellow) 5.4(0.21) 23(0.91) 3.5(0.14) 6.1(0.24) 10.8(0.43) 20.5±0.5(0.81±0.02) 0.2(0.008) 2.8(0.11) 3.5(0.14)
CR2354/1GUF 1GU	35 5.4(0.21) 23(0.91) 3.5(0.14) 6.2(0.24) 10.3(0.41) 17.8±0.5(0.70±0.20) 0.2(0.008) 0.75(0.03) 3.5(0.14)	CR2354/1VC 1VB	36 Insulation Wrap (yellow) 5.4(0.21) 23(0.9) 3.5(0.14) 6.2(0.24) 10.3(0.41) 17.8±0.5(0.70±0.20) 0.2(0.008) 0.75(0.03) 3.5(0.14)
CR2477/1VC 1VB	37 Insulation Wrap (yellow) 24.5(0.96) 7.8(0.31) 3.5(0.14) 6.2(0.24) 10.3(0.41) 17.8±0.5(0.70±0.20) 0.2(0.008) 0.75(0.03) 3.5(0.14)	CR2477/1HF 1HE	38 Insulation Wrap (yellow) 24.5(0.96) 7.8(0.31) 3.5(0.14) 6.2(0.24) 10.3(0.41) 17.8±0.5(0.70±0.20) 0.2(0.008) 0.75(0.03) 3.5(0.14)
CR2450/H1A	39 Insulation Wrap (yellow) 25±1(1.0±0.04) 4±0.1(0.16±0.04) 24.5(0.96) 3.5(0.14) 6.2(0.24) 10.3(0.41) 17.8±0.5(0.70±0.20) 0.2(0.008) 0.75(0.03) 3.5(0.14)	CR2450/G1A	40 25±1(1.0±0.04) 4±0.1(0.16±0.04) 24.5(0.96) 3.5(0.14) 6.2(0.24) 10.3(0.41) 17.8±0.8(0.70±0.21) 0.2(0.008) 0.75(0.03) 3.5(0.14)