


SAW Bandpass Filter 271102B



1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters
Base : Fe(SPCC), Au plating over Ni plated
Cap : Cu & Cr Alloy, Ni Plated
Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271102B	
		Rev. Date	2008-12-24	
		Rev.	NM8044-CS01	1/5

SAW Bandpass Filter 271102B

3. Specifications

Fo = 70.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	70.0	-
Insertion Loss	dB	-	22.6	24.0
2dB Bandwidth	MHz	10.9	11.0	-
25dB Bandwidth	MHz	-	11.7	11.8
40dB Bandwidth	MHz	-	11.87	-
Amplitude Ripple (fo ± 5.25 MHz)	dB	-	0.55	1.0
Group Delay Variation (fo ± 5.25 MHz)	nsec	-	50	100
Absolute Delay	usec	-	3.31	-
Ultimate Rejection	dB	48	52	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271102B	
		Rev. Date	2008-12-24	
		Rev.	NM8044-CS01	2/5

SAW Bandpass Filter 271102B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$$L1 = 82\text{nH}, L2 = 68\text{nH}$$

$$C1 = C2 = 36\text{pF}$$

5. Marking Configuration

ITF¹⁾ 08A001²⁾

271102B³⁾

70⁴⁾ -11.0M⁵⁾

1) Manufacturer name

2) Lot Number

3) Part Number

4) Center Frequency



5) 2dB-Bandwidth

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271102B	
		Rev. Date	2008-12-24	
		Rev.	NM8044-CS01	3/5

SAW Bandpass Filter 271102B



6. Typical Performance (at +25°C)



	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809		Part No.		271102B	
			Rev. Date		2008-12-24	
			Rev.		NM8044-CS01	4/5

