查询"SLQ-K02"供应商

QUADRATURE HYBRID
MODEL SLQ-K02

OCTAVE BANDWIDTH 40 - 80 MHz

SPECIFICATIONS

Operating Frequency:	40 - 80 MHz	**Phase Unbalance:**	1º (Typ)/ 3º (Max)
Insertion Loss:	0.3 dB (Typ)/0.6 dB (Max)	**VSWR :**	1.1:1 (Max)
Isolation:	25 dB (Typ)/20 dB (Min)	**Power Rating:**	1 Watt (Max)
Amplitude Unbalance:	0.4 dB (Typ)/0.75 dB (Max)	**Impedance:**	50 Ohms
		Operating Temp. Range:	-20º to +70ºC



MECHANICAL OUTLINE: 159



PIN-OUT	
Input	**6**
+90º Output	**1**
0º Output	**2**
Isolated*	**5**
Ground**	**3,4**

** Terminate Isolated port in 50 Ohms*
** Ground Externally*

Copyright © 2004 Synergy Microwave Corporation
201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361
E-Mail: sales@synergymwave.com • World Wide Web: http://www.synergymwave.com

SYNERGY®
MICROWAVE CORPORATION

查询"SLQ-K02"供应商

QUADRATURE HYBRID MODEL SLQ-K02

OCTAVE BANDWIDTH 40 - 80 MHz

PERFORMANCE PLOTS











Copyright © 2004 Synergy Microwave Corporation

201 McLean Boulevard • Paterson, New Jersey 07504 • Tel: (973) 881-8800 • Fax: (973) 881-8361
E-Mail: sales@synergymwave.com • World Wide Web: http://www.synergymwave.com

SYNERGY® MICROWAVE CORPORATION