


**Silicon NPN Epitaxial Planar Phototransistor**

Applications: Detector in electronic control and drive circuits

Features:

- Plastic case  $\varnothing$  5 mm (T-1 $\frac{1}{2}$ )
- Suitable for visible and near infrared radiation
- High sensitivity
- Wide angle of half sensitivity
- Axial terminals

Dimensions in mm



Angle of half sensitivity  
 $\pm \varphi = 20^\circ$   
Special case  
Clear plastic  
Weight max. 0.4 g

Accessories

- Mounting clip Order No. 562136
- Retainer ring Order No. 562135


Absolute maximum ratings

Collector-emitter voltage	$V_{CEO}$	32	V
Emitter-collector voltage	$V_{ECO}$	5	V
Collector current	$I_C$	100	mA
Peak collector current $t_p = 0.5, t_p \leq 10 \text{ms}$	$I_{CM}$	200	mA
Total power dissipation $T_{amb} \leq 47^\circ\text{C}$	$P_{tot}$	150	mW
Junction temperature	$T_j$	100	$^\circ\text{C}$
Storage temperature range	$T_{stg}$	-25...+100	$^\circ\text{C}$
Soldering temperature $t \leq 3 \text{s}$	$T_{sd}^{1)}$	245	$^\circ\text{C}$

<sup>1)</sup> Distance from the touching border  $\geq 1.5 \text{ mm}$  with intermediate PC-board





# BPW 40

Thermal resistance		Min.	Typ.	Max.	
Junction ambient	$R_{thJA}$			350	K/W
<b>Optical and electrical characteristics</b>					
$T_{amb} = 25\text{ }^\circ\text{C}$					
Collector dark current			10	200	nA
$V_{CE} = 20\text{ V}, E = 0$	$I_{CEO}^{1)}$				
Collector light current		1	6		mA
$V_{CE} = 5\text{ V}, E_A = 1\text{ klx}$	$I_{CS}^{2)}$		2		mA
$V_{CE} = 5\text{ V}, E_e = 1\text{ mW/cm}^2, \lambda_p = 950\text{ nm}$					
Peak wavelength sensitivity	$\lambda_p$		780		nm
Range of spectral bandwidth (50%)	$\lambda_{0.5}$		520...950		nm
Collector-emitter breakdown voltage		32			V
$I_C = 1\text{ mA}$	$V_{(BR)CEO}^{1)}$				
Collector-Emitter saturation voltage				0.3	V
$I_C = 1\text{ mA}, E_e = 1\text{ mW/cm}^2, \lambda_p = 950\text{ nm}$	$V_{CEsat}^{1)}$				
Cut-off frequency			170		kHz
$V_S = 5\text{ V}, I_C = 5\text{ mA}, R_L = 100\text{ }\Omega$	$f_c$				
<b>Switching characteristics</b>					
$V_S = 5\text{ V}, I_C = 5\text{ mA}, R_L = 100\text{ }\Omega$ , see test circuit					
Delay time	$t_d$		1.8		$\mu\text{s}$
Rise time	$t_r$		1.6		$\mu\text{s}$
Turn-on time	$t_{on}$		3.4		$\mu\text{s}$
Storage time	$t_s$		0.3		$\mu\text{s}$
Fall time	$t_f$		1.7		$\mu\text{s}$
Turn-off time	$t_{off}$		2.0		$\mu\text{s}$



Test circuit

<sup>1)</sup>AQL = 0.65 %    <sup>2)</sup>Standard illuminant A (DIN 5033/IEC 306-1)



# BPW 40

