

29F52•29F53 8-Bit Registered Transceiver

General Description

The 29F52 and 29F53 are 8-bit registered transceivers. Two 8-bit back to back registers store data flowing in both directions between two bidirectional buses. Separate clock, clock enable and TRI-STATE® output enable signals are provided for each register. The A₀–A₇ output pins are guaranteed to sink 24 mA (20 mA mil.) while the B₀–B₇ output pins are designed for 64 mA.

The 29F53 is an inverting option of the 29F52. Both transceivers are AMD Am2952/2953 functional equivalents.

Features


- 8-bit registered transceivers
- Separate clock, clock enable and TRI-STATE output enable provided for each register
- AMD Am2952/2953 functional equivalents
- Both inverting and non-inverting options available
- 24-Pin slimline package

Ordering Code: See Section 11


Commercial	Package Number	Package Description
29F52SPC	N24C	24-Lead (0.300" Wide) Molded Dual-In-Line
29F52SC (Note 1)	M24B	24-Lead (0.300" Wide) Molded Small Outline, JEDEC
29F53SPC	N24C	24-Lead (0.300" Wide) Molded Dual-In-Line

Note 1: Devices also available in 13" reel. Use suffix = SCX.

Logic Symbols




TL/F/9606-1




TL/F/9606-7

Logic Symbols (Continued)

查询"29F52FOCOP"供应商




TL/F/9606-4



TL/F/9606-5


Connection Diagrams

Pin Assignment
for DIP and SOIC
29F52



TL/F/9606-2

Pin Assignment
for DIP
29F53



TL/F/9606-8


Unit Loading/Fan Out: See Section 2 for U.L. definitions

Pin Names	Description	54F/74F	
		U.L. HIGH/LOW	Input I_{IH}/I_{IL} Output I_{OH}/I_{OL}
A_0 – A_7	A-Register Inputs/ B-Register TRI-STATE Outputs	3.5/1.083	70 μ A/0.65 mA
B_0 – B_7	B-Register Inputs/ A-Register TRI-STATE Outputs	150/40 (33.3)	–3 mA/24 mA (20 mA)
$\overline{OEA}$	Output Enable A-Register	3.5/1.083	70 μ A/0.65 mA
CPA	A-Register Clock	600/106.6 (80)	–12 mA/64 mA (48 mA)
$\overline{CEA}$	A-Register Clock Enable	1.0/1.0	20 μ A/–0.6 mA
$\overline{OEB}$	Output Enable B-Register	1.0/1.0	20 μ A/–0.6 mA
CPB	B-Register Clock	1.0/1.0	20 μ A/–0.6 mA
$\overline{CEB}$	B-Register Clock Enable	1.0/1.0	20 μ A/–0.6 mA

Block Diagrams

[查询"29F52FCQR"供应商](#)

29F52




TL/F/9606-6

29F52•29F53

Block Diagrams (Continued)

[查询"29F52FCQR"供应商](#)

29F53



TL/F/9606-10

Output Control

OE	Internal Q	Y-Output		Function
		29F52	29F53	
H	X	Z	Z	Disable Outputs
L	L	L	H	Enable Outputs
L	H	H	L	

H = HIGH Voltage Level

L = LOW Voltage Level

X = Immaterial

Z = HIGH Impedance

/ = LOW-to-HIGH Transition

NC = No Change

Register Function Table (Applies to A or B Register)

Inputs			Internal Q	Function
D	CP	CE		
X	X	H	NC	Hold Data
L	/	L	L	Load Data
H	/	L	H	

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Storage Temperature	-65°C to +150°C
Ambient Temperature under Bias	-55°C to +125°C
Junction Temperature under Bias	-55°C to +175°C
Plastic	-55°C to +150°C
V _{CC} Pin Potential to Ground Pin	-0.5V to +7.0V
Input Voltage (Note 2)	-0.5V to +7.0V
Input Current (Note 2)	-30 mA to +5.0 mA
Voltage Applied to Output in HIGH State (with V _{CC} = 0V)	
Standard Output	-0.5V to V _{CC}
TRI-STATE Output	-0.5V to +5.5V

Current Applied to Output in LOW State (Max) twice the rated I_{OL} (mA)

Note 1: Absolute maximum ratings are values beyond which the device may be damaged or have its useful life impaired. Functional operation under these conditions is not implied.

Note 2: Either voltage limit or current limit is sufficient to protect inputs.

Recommended Operating Conditions

Free Air Ambient Temperature	
Military	-55°C to +125°C
Commercial	0°C to +70°C
Supply Voltage	
Military	+4.5V to +5.5V
Commercial	+4.5V to +5.5V

DC Electrical Characteristics

Symbol	Parameter	54F/74F			Units	V _{CC}	Conditions
		Min	Typ	Max			
V _{IH}	Input HIGH Voltage	2.0			V		Recognized as a HIGH Signal
V _{IL}	Input LOW Voltage			0.8	V		Recognized as a LOW Signal
V _{CD}	Input Clamp Diode Voltage			-1.2	V	Min	I _{IN} = -18 mA (Non I/O Pins)
V _{OH}	Output HIGH Voltage	54F 10% V _{CC} 54F 10% V _{CC} 54F 10% V _{CC} 74F 10% V _{CC} 74F 10% V _{CC} 74F 10% V _{CC} 74F 5% V _{CC} 74F 5% V _{CC}	2.5 2.4 2.0 2.5 2.4 2.0 2.7 2.7		V	Min	I _{OH} = -1 mA (A _N) I _{OH} = -3 mA (A _N , B _N) I _{OH} = -12 mA (B _N) I _{OH} = -1 mA (A _N) I _{OH} = -3 mA (A _N , B _N) I _{OH} = -15 mA (B _N) I _{OH} = -1 mA (A _N) I _{OH} = -3 mA (A _N , B _N)
V _{OL}	Output LOW Voltage	54F 10% V _{CC} 54F 10% V _{CC} 74F 10% V _{CC} 74F 10% V _{CC}		0.5 0.55 0.5 0.55	V	Min	I _{OL} = 20 mA (A _N) I _{OL} = 48 mA (B _N) I _{OL} = 24 mA (A _N) I _{OL} = 64 mA (B _N)
I _{IH}	Input HIGH Current			20	μA	Max	V _{IN} = 2.7V (Non-I/O Pins)
I _{BVI}	Input HIGH Current Breakdown Test			100	μA	Max	V _{IN} = 7.0V (Non-I/O Pins)
I _{BVIT}	Input HIGH Current Breakdown Test (I/O)			1.0	mA	Max	V _{IN} = 5.5V (A _N , B _N)
I _{IL}	Input LOW Current			-0.6	mA	Max	V _{IN} = 0.5V (Non-I/O Pins)
I _{IH} + I _{OZH}	Output Leakage Current			70	μA	Max	V _{OUT} = 2.7V (A _N , B _N)
I _{IL} + I _{OZL}	Output Leakage Current			-650	μA	Max	V _{OUT} = 0.5V (A _N , B _N)
I _{OS}	Output Short-Circuit Current	-60 -100		-150 -225	mA	Max	V _{OUT} = 0V (A _N) V _{OUT} = 0V (B _N)
I _{CEx}	Output HIGH Leakage Current			250	μA	Max	V _{OUT} = V _{CC} (A _N , B _N)
I _{ZZ}	Bus Drainage Test			500	μA	0.0V	V _{OUT} = 5.25V (A _N , B _N)
I _{CCH}	Power Supply Current		130	190	mA	Max	V _O = HIGH
I _{CCL}	Power Supply Current			190	mA	Max	V _O = LOW
I _{CCZ}	Power Supply Current			190	mA	Max	V _O = HIGH Z

AC Electrical Characteristics: See Section 2 for Waveforms and Load Configurations

查询"29F52FCQR"供应商

查询"29F52FCQR"供应商		74F			54F		74F		Units	Fig. No.
Symbol	Parameter	$T_A = +25^{\circ}\text{C}$ $V_{CC} = +5.0\text{V}$ $C_L = 50\text{ pF}$			$T_A, V_{CC} = \text{Mil}$ $C_L = 50\text{ pF}$		$T_A, V_{CC} = \text{Com}$ $C_L = 50\text{ pF}$			
		Min	Typ	Max	Min	Max	Min	Max		
t _{PLH}	Propagation Delay	3.0	5.5	7.5			2.5	8.5	ns	2-3
t _{PHL}	CPA or CPB to A _n or B _n	4.0	7.0	9.0			3.5	10.0		
t _{pZH}	Output Enable Time	2.5	5.5	7.5			2.0	8.5	ns	2-5
t _{pZL}	$\overline{\text{OEA}}$ or $\overline{\text{OEB}}$ to A _n or B _n	3.5	7.0	9.5			3.0	10.5		
t _{PHZ}	Output Disable Time	2.5	6.5	9.0			2.0	10.0	ns	2-5
t _{PLZ}	$\overline{\text{OEA}}$ or $\overline{\text{OEB}}$ to A _n or B _n	2.5	5.5	7.5			2.0	8.5		

AC Operating Requirements: See Section 2 for Waveforms

Symbol	Parameter	74F		54F		74F		Units	Fig. No.
		$T_A = +25^{\circ}\text{C}$ $V_{CC} = +5.0\text{V}$		$T_A, V_{CC} = \text{Mil}$		$T_A, V_{CC} = \text{Com}$			
		Min	Max	Min	Max	Min	Max		
$t_s(\text{H})$	Setup Time, HIGH or LOW	4.0				4.5		ns	2-6
$t_s(\text{L})$	A_n or B_n to CPA or CPB	4.0				4.5			
$t_h(\text{H})$	Hold Time, HIGH or LOW	2.0				2.5		ns	2-6
$t_h(\text{L})$	A_n or B_n to CPA or CPB	2.0				2.5			
$t_s(\text{H})$	Setup Time, HIGH or LOW	1.0				1.5		ns	2-6
$t_s(\text{L})$	$\overline{\text{CEA}}$ or $\overline{\text{CEB}}$ to CPA or CPB	4.0				4.5			
$t_h(\text{H})$	Hold Time, HIGH or LOW	2.0				2.5		ns	2-6
$t_h(\text{L})$	$\overline{\text{CEA}}$ or $\overline{\text{CEB}}$ to CPA or CPB	2.0				2.5			
$t_w(\text{H})$	Pulse Width, HIGH or LOW	3.0				3.5		ns	2-4
$t_w(\text{L})$	CPA or CPB	3.0				3.5			