




Features:

- All 12 adapters in kit are direct. **No intermediate couplers.**
- Reduced signal loss in adapters due to absence of couplers.
- Kit includes the most frequently used N Type adapters including N / N, N / SMA, N / BNC, and N Terminations, both 50 and 75 ohm. See complete list in drawing or in table below.
- Rugged, lockable, pistol-grip case.
- All parts precision machined brass with tarnish resistant gold or nickel plating.
- Male center pins are gold plated brass.
- Female contacts are gold plated heat treated beryllium copper.
- Insulation material is high density PTFE.



**Order Example: 72932
(N Adapter Kit)**

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)

For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com

Model 72932 – Type N Adapter Kit

Item	Description	Pomona Part Number	NOM. IMPEDANCE	FREQ. RANGE	VSWR	OPERATING TEMP
1	TYPE N female/male RA	3843	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
2	TYPE N Terminator plug	4240-75	75 Ohms	DC to 500 MHz	1.35 at 500 MHz	- 65° to +165° C
3	TYPE N Terminator plug	4240-50	50 OHMS	DC to 500 MHz	1.35 at 500 MHz	- 65° to +165° C
4	TYPE N female/female	3841	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
5	BNC male/ TYPE N female	3535	50 Ohms	DC to 4 GHz	1.35 to 4 GHz	- 65° to +165° C
6	BNC female, TYPE N male	3288	50 Ohms	DC to 4 GHz	1.35 to 4 GHz	- 65° to +165° C
7	SMA Termination male	4286	50 Ohms	DC to 18GHz	1.25 Max at 18GHz	- 65° to +165° C
8	TYPE N male/ TYPE N male	3842	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
9	TYPE N female/female/female	5089	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
10	SMA female/ TYPE N female	4299	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
11	SMA male/TYPE N female	4298	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C
12	SMA female/TYPE N male	4297	50 Ohms	DC to 11GHz	1.35 to 11GHz	- 65° to +165° C

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Sales: 800-490-2361 Fax: 888-403-3360 Technical Support: 800-241-2060 (technicalsupport@pomonatest.com)

For "Where to Buy" information, visit the Pomona web site at www.pomonaelectronics.com