

## ExStik® II Conductivity Kit

**Waterproof meter incorporates a highly accurate multi-ranging sensor that measures four parameters - Conductivity, TDS, Salinity, and Temperature**  
With calibration standards, sample plastic cups and carrying case included for easy travel

### Features:

- Autoranging meter offers 3 ranges with 8 units of measure including  $\mu\text{S}/\text{cm}$ ,  $\text{mS}/\text{cm}$ , ppm, ppt, mg/L, g/L, °F, and °C
- Simultaneous display of Conductivity or TDS plus Temperature and bargraph
- Memory stores up to 15 labeled readings
- Adjustable Conductivity to TDS ratio factor from 0.4 to 1.0
- Self calibration on power up
- Waterproof to IP57
- Large 3-1/2 digit (2000 count) Digital display with analog bargraph to indicate sample trends
- Data Hold, Auto Power Off and low battery indication
- Automatic Temperature Compensation of 2% per °C
- Auto standard recognition for calibration (84 $\mu\text{S}/\text{cm}$ , 1413 $\mu\text{S}/\text{cm}$ , and 12880 $\mu\text{S}/\text{cm}$ )
- Easy to replace Conductivity cell module
- Plastic sample cup and iron cast weighted base allows for hands-free operation while holding up the meter during measurement stage
- EC410 kit includes EC400 ExStik® Conductivity/TDS/ Salinity Temperature Meter, with sensor, protective cap, 84 $\mu\text{S}/\text{cm}$ , 1413 $\mu\text{S}/\text{cm}$  and 12880 $\mu\text{S}/\text{cm}$  calibration standards (30mL bottle each), weighted base, 3 sample plastic cups with caps, four 3V CR-2032 batteries, 48" (1.2m) neckstrap, and carrying case



Patents Pending

Specifications	Ranges	Max. Resolution	Basic Accuracy
Conductivity	0 to 199.9 $\mu\text{S}/\text{cm}$	0.1 $\mu\text{S}/\text{cm}$	±2% FS
	200 to 1999 $\mu\text{S}/\text{cm}$	1 $\mu\text{S}/\text{cm}$	
	2.00 to 19.99mS/cm	0.01mS/cm	
TDS	0 to 99.9ppm (mg/L)	0.1ppm (mg/L)	±2% FS
	100 to 999ppm (mg/L)	1ppm (mg/L)	
	1.00 to 9.99ppt (g/L)	0.01ppt (g/L)	
Salinity	0 to 99.9ppm (mg/L)	0.1ppm (mg/L)	±2% FS
	100 to 999ppm (mg/L)	1ppm (mg/L)	
	1.00 to 9.99ppt (g/L)	0.01ppt (g/L)	
Temperature	32° to 149°F (0° to 65°C)	0.1°	±1.8°F/1°C
Power	Four SR44W button batteries		
Dimensions	Meter: 1.4 x 6.8 x 1.6" (36 x 173 x 41mm) Kit: 9.5 x 6.8 x 2.8" (241 x 173 x 71mm)		
Weight	Meter: 3.8 oz (110g) Kit: 1.56 lbs (708g)		

### Ordering Information:

EC410 ..... ExStik® Conductivity/TDS/Salinity Kit  
 EC400 ..... ExStik® Conductivity/TDS/Salinity Meter  
 EC405 ..... Spare Conductivity Cell  
 EC-84-P ..... 84 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)  
 EC-1413-P ..... 1413 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)  
 EC-12880-P ..... 12880 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)  
 EX007 ..... Spare sample solution cups (24pk)  
 EX010 ..... Extension Cable, 3ft (1 Meter) with probe weight for ExStik  
 EX050 ..... Extension Cable, 16ft (5 Meters) with probe weight for ExStik  
 ExStik® Conductivity cell is not interchangeable with other ExStik® meters

