

# International IR Rectifier

## 30WQ03FNPbF

SCHOTTKY RECTIFIER

3.5 Amp

$$I_{F(AV)} = 3.5\text{Amp}$$

$$V_R = 30\text{V}$$

### Major Ratings and Characteristics

Characteristics	Values	Units
$I_{F(AV)}$ Rectangular waveform	3.5	A
$V_{RRM}$	30	V
$I_{FSM}$ @tp = 5 $\mu$ s sine	535	A
$V_F$ @3 Apk, $T_J = 125^\circ\text{C}$	0.35	V
$T_J$ range	-40 to 150	$^\circ\text{C}$

### Description/ Features


The 30WQ03FNPbF surface mount Schottky rectifier has been designed for applications requiring low forward drop and small foot prints on PC board. Typical applications are in disk drives, switching power supplies, converters, free-wheeling diodes, battery charging, and reverse battery protection.

- Popular D-PAK outline
- Small foot print, surface mountable
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free ("PbF" suffix)

### Case Styles



D-PAK (TO-252AA)



30WQ03FNPbF

Bulletin PD-21052 rev. B 08/06



Voltage Ratings

Part number	30WQ03FNPbF
V <sub>R</sub> Max. DC Reverse Voltage (V)	30
V <sub>RWM</sub> Max. Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters	30WQ...	Units	Conditions
I <sub>F(AV)</sub> Max. Average Forward Current * See Fig. 5	3.5	A	50% duty cycle @ T <sub>C</sub> = 134°C, rectangular wave form
I <sub>FSM</sub> Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7	535	A	Following any rated load condition and with rated V <sub>RRM</sub> applied
	90		
E <sub>AS</sub> Non-Repetitive Avalanche Energy	8	mJ	T <sub>J</sub> = 25 °C, I <sub>AS</sub> = 2 Amps, L = 4 mH
I <sub>AR</sub> Repetitive Avalanche Current	1.0	A	Current decaying linearly to zero in 1 μsec Frequency limited by T <sub>J</sub> max. V <sub>A</sub> = 1.5 x V <sub>R</sub> typical

Electrical Specifications

Parameters	30WQ...	Units	Conditions
V <sub>FM</sub> Max. Forward Voltage Drop * See Fig. 1 (1)	0.45	V	@ 3A
	0.52	V	@ 6A
	0.35	V	@ 3A
	0.46	V	@ 6A
I <sub>RM</sub> Max. Reverse Leakage Current * See Fig. 2 (1)	2	mA	T <sub>J</sub> = 25 °C
	50	mA	T <sub>J</sub> = 125 °C
V <sub>F(TO)</sub> Threshold Voltage	0.22	V	T <sub>J</sub> = T <sub>J</sub> max.
r <sub>t</sub> Forward Slope Resistance	32.86	mΩ	
C <sub>T</sub> Typical Junction Capacitance	290	pF	V <sub>R</sub> = 5V <sub>DC</sub> , (test signal range 100Khz to 1Mhz) 25 °C
L <sub>S</sub> Typical Series Inductance	5.0	nH	Measured lead to lead 5mm from package body
dv/dt Max. Voltage Rate of Change	10000	V/μs	(Rated V <sub>R</sub> )

(1) Pulse Width < 300μs, Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters	30WQ...	Units	Conditions
T <sub>J</sub> Max. Junction Temperature Range (*)	-40 to 150	°C	
T <sub>stg</sub> Max. Storage Temperature Range	-40 to 150	°C	
R <sub>thJC</sub> Max. Thermal Resistance Junction to Case	4.7	°C/W	DC operation * See Fig. 4
wt Approximate Weight	0.3(0.01)	g(oz.)	
Case Style	D-PAK		Similar to TO-252AA
Marking Device	30WQ03FN		

(\*)  $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th(j-a)}}$  thermal runaway condition for a diode on its own heatsink




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics

30WQ03FNPbF

Bulletin PD-21052 rev. B 08/06




Fig. 5 - Maximum Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics






Fig. 7 - Maximum Non-Repetitive Surge Current

(2) Formula used:  $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$ ;  
 $Pd = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$  (see Fig. 6);  
 $Pd_{REV} = \text{Inverse Power Loss} = V_{R1} \times I_R (1 - D); I_R @ V_{R1} = 80\% \text{ rated } V_R$


Outline Table



Part Marking Information



Tape & Reel Information



Ordering Information Table

Device Code	30	W	Q	03	FN	TRL	PbF
	1	2	3	4	5	6	7
<b>1</b>	-	Current Rating (3.5A)					
<b>2</b>	-	Package Identifier					
		W = D-Pak					
<b>3</b>	-	Schottky "Q" Series					
<b>4</b>	-	Voltage Rating (03 = 30V)					
<b>5</b>	-	FN = TO-252AA (D-Pak)					
<b>6</b>	-	<ul style="list-style-type: none"><li>• none = Tube (50 pieces)</li><li>• TR = Tape &amp; Reel</li><li>• TRL = Tape &amp; Reel (Left Oriented)</li><li>• TRR = Tape &amp; Reel (Right Oriented)</li></ul>					
<b>7</b>	-	<ul style="list-style-type: none"><li>• none = Standard Production</li><li>• PbF = Lead-Free</li></ul>					

Data and specifications subject to change without notice.  
This product has been designed and qualified for AEC Q101 Level and Lead-Free.  
Qualification Standards can be found on IR's Web site.