

# NPN General Purpose Amplifier Transistor Surface Mount

## Features

- Pb-Free Packages are Available

## MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ )

| Rating                         | Symbol        | Value | Unit |
|--------------------------------|---------------|-------|------|
| Collector-Base Voltage         | $V_{(BR)CBO}$ | 60    | Vdc  |
| Collector-Emitter Voltage      | $V_{(BR)CEO}$ | 50    | Vdc  |
| Emitter-Base Voltage           | $V_{(BR)EBO}$ | 7.0   | Vdc  |
| Collector Current - Continuous | $I_C$         | 500   | mAdc |
| Collector Current - Peak       | $I_{C(P)}$    | 1.0   | Adc  |

## THERMAL CHARACTERISTICS


| Characteristic       | Symbol    | Max        | Unit             |
|----------------------|-----------|------------|------------------|
| Power Dissipation    | $P_D$     | 200        | mW               |
| Junction Temperature | $T_J$     | 150        | $^\circ\text{C}$ |
| Storage Temperature  | $T_{stg}$ | -55 ~ +150 | $^\circ\text{C}$ |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.



ON Semiconductor®


<http://onsemi.com>



## MARKING DIAGRAM



SC-59  
CASE 318D



WR = Specific Device Code  
M = Date Code  
▪ = Pb-Free Package  
(Note: Microdot may be in either location)

## ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

Preferred devices are recommended choices for future use and best overall value.

# MSD602-RT1

## 查MSD602-RT1 D 供应商

| Characteristic                                                                                                                                   | Symbol                 | Min       | Max      | Unit            |
|--------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|-----------|----------|-----------------|
| Collector-Emitter Breakdown Voltage<br>( $I_C = 10 \text{ mAdc}$ , $I_E = 0$ )                                                                   | $V_{(BR)CEO}$          | 50        | —        | Vdc             |
| Collector-Base Breakdown Voltage<br>( $I_C = 10 \text{ } \mu\text{Adc}$ , $I_E = 0$ )                                                            | $V_{(BR)CBO}$          | 60        | —        | Vdc             |
| Emitter-Base Breakdown Voltage<br>( $I_E = 10 \text{ } \mu\text{Adc}$ , $I_C = 0$ )                                                              | $V_{(BR)EBO}$          | 7.0       | —        | Vdc             |
| Collector-Base Cutoff Current<br>( $V_{CB} = 20 \text{ Vdc}$ , $I_E = 0$ )                                                                       | $I_{CBO}$              | —         | 0.1      | $\mu\text{Adc}$ |
| DC Current Gain (Note 1)<br>( $V_{CE} = 10 \text{ Vdc}$ , $I_C = 150 \text{ mAdc}$ )<br>( $V_{CE} = 10 \text{ Vdc}$ , $I_C = 500 \text{ mAdc}$ ) | $h_{FE1}$<br>$h_{FE2}$ | 120<br>40 | 240<br>— | —               |
| Collector-Emitter Saturation Voltage<br>( $I_C = 300 \text{ mAdc}$ , $I_E = 30 \text{ mAdc}$ )                                                   | $V_{CE(sat)}$          | —         | 0.6      | Vdc             |
| Output Capacitance<br>( $V_{CB} = 10 \text{ Vdc}$ , $I_E = 0$ , $f = 1.0 \text{ MHz}$ )                                                          | $C_{ob}$               | —         | 15       | pF              |

1. Pulse Test: Pulse Width  $\leq 300 \text{ } \mu\text{s}$ , D.C.  $\leq 2\%$ .

## ORDERING INFORMATION

| Device      | Package            | Shipping <sup>†</sup> |
|-------------|--------------------|-----------------------|
| MSD-602RT1  | SC-59              | 3000 Units / Reel     |
| MSD-602RT1G | SC-59<br>(Pb-Free) | 3000 Units / Reel     |


<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MSD602-RT1

[查询"MSD602-RT1-D"供应商](#)

## PACKAGE DIMENSIONS

SC-59  
CASE 318D-04  
ISSUE G



### NOTES:


1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.

| DIM | MILLIMETERS |      |      | INCHES |       |       |
|-----|-------------|------|------|--------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN    | NOM   | MAX   |
| A   | 1.00        | 1.15 | 1.30 | 0.039  | 0.045 | 0.051 |
| A1  | 0.01        | 0.06 | 0.10 | 0.001  | 0.002 | 0.004 |
| b   | 0.35        | 0.43 | 0.50 | 0.014  | 0.017 | 0.020 |
| c   | 0.09        | 0.14 | 0.18 | 0.003  | 0.005 | 0.007 |
| D   | 2.70        | 2.90 | 3.10 | 0.106  | 0.114 | 0.122 |
| E   | 1.30        | 1.50 | 1.70 | 0.051  | 0.059 | 0.067 |
| e   | 1.70        | 1.90 | 2.10 | 0.067  | 0.075 | 0.083 |
| L   | 0.20        | 0.40 | 0.60 | 0.008  | 0.016 | 0.024 |
| HE  | 2.50        | 2.80 | 3.00 | 0.099  | 0.110 | 0.118 |

### STYLE 1:

- PIN 1. EMITTER
- BASE
- COLLECTOR

## SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

[查询"MSD602-RT1-D"供应商](#)

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
**Phone:** 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Japan:** ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
**Phone:** 81-3-5773-3850

**ON Semiconductor Website:** <http://onsemi.com>

**Order Literature:** <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.