

714-8239

SIP MEC K225, TE 250

查询"1553"供应商

Circular Saws



**SAFETY
RELEASE
SWITCH**

SIP MEC Circular Sawing Machines are manufactured to the highest quality and are the result of over 30 year's experience in the field of metal cutting. The K225 is the latest addition to the range. It's dimensions, features and competitive pricing make it possible for an even greater number of uses and applications to benefit from the speed, accuracy and excellent finish of circular sawing on most metals. Although light enough to be carried around the workshop or even transported in the boot of a car for site work, the K225 is built to exacting machine tool standards with all the traditional know how that has made SIP MEC sawing machines such favourites over the years.

FEATURES:

- Solid cast machine base to absorb vibration.
- Blade totally guarded to the latest standards.
- Head swivels 45° left for precise mitreing.
- Fully equipped with coolant system, length stop, adjustable depth of cut.



The MEC TE 250 is a very popular mid-range machine incorporating all the features of the K225 plus:

- Vice with off cut clamp to hold the workpiece firm on both sides of the cut, eliminating break off burrs.
- Mitres up to 45° both left and right.
- Extra cutting capacity up to 80 mm diameter tube.
- Available in either single or 3 phase versions.

**Pedestals available. See price list.
Advanced Cutting Fluid available . See page 89.**

MODEL	MEC K225	MEC TE 250	
ITEM NO	01553	01555 (230/240V)	01556 (400/415V)
HP	1	1.5 (230/240V)	1.3 / 1.8 (400/415V)
BLADE SPEED RPM	52	52 (230/240V)	52 - 104 (400/415V)
MAX. SAW DIAMETER MM	225	250	
MAX. OPENING OF VICE MM	70	82	
REVOLVING HEAD ANGLE	45° LEFT	45° LEFT / RIGHT	
PACKED OVERALL DIMENSIONS (HxWxL) MM	530x440x380	830x620x600	
WEIGHT KGS	32	73	

PEDESTALS FOR ALL MACHINES, EXCEPT K225 AVAILABLE AS OPTIONAL EXTRA.

CUTTING CAPACITY MM				
MEC K225				
BLADE Ø 225	○	□	▭	●
90°	65	55x55	45x75	30
45°	60	50x50	40x60	30
MEC TE 250				
BLADE Ø 250	○	□	▭	●
90°	80	70x70	65x70	40
45°	70	55x55	50x70	35

