

January 1990

Edition 1.1

查询"2SC3847"供应商

PRODUCT PROFILE

FUJITSU

2SC3847**Silicon High Speed Power Transistor**

2SC3847 800V, 10A

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Conditions	Rating	Unit
Storage Temperature Range	T_{stg}		-55 ~ +150	°C
Junction Temperature	T_J		+150	°C
Collector to Base Voltage	V_{CBO}		1200	V
Emitter to Base Voltage	V_{EBO}		7	V
Collector to Emitter Voltage	V_{CEO}		800	V
Collector Current	I_C		10	A
	I_{CM}	$P_W \leq 25\mu s, D.R. \leq 50\%$	20	
Base Current	I_B		5	A
Collector Power Dissipation	P_C	$T_C = 25^\circ C$	85	W






ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ C$)

Parameter	Symbol	Test Conditions	Limit			Unit
			Min.	Typ.	Max.	
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 1mA, I_E = 0$	1200	-	-	V
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 1mA, I_C = 0$	7	-	-	V
Collector to Emitter Sustaining Voltage	$V_{(BR)CEO}$	$I_C = 10mA, R_{BE} = \infty \Omega$	800	-	-	V
Collector to Emitter Sustaining Voltage	$V_{CEX(SUS)}$	$I_C = 7A, I_{B2} = -1.2A, L = 1mH^*$	900	-	-	V
Collector Cutoff Current	I_{CBO}	$V_{CB} = 1000V, I_E = 0$	-	-	100	μA
		$V_{CB} = 1000V, I_E = 0, T_C = 100^\circ C$	-	-	1	mA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 6V, I_C = 0$	-	-	100	μA
DC Current Gain	h_{FE}	$V_{CE} = 5V, I_C = 4A^{**}$	10	15	30	-
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 4A, I_B = 0.8A^{**}$	-	0.3	1.5	V
Base to Emitter Saturation Voltage	$V_{BE(sat)}$		-	1.0	2.0	V
Output Capacitance	C_{ob}	$V_{CB} = 10V, I_E = 0, f = 1MHz$	-	220	-	pF
Gain Bandwidth Product	f_T	$V_{CE} = 10V, I_C = 0.1A$	-	15	-	MHz
Rise Time	t_r	$V_{CC} = 400V, I_C = 4A, 3I_{B1} = -I_{B2} = 1.2A^*$	-	0.20	0.5	μs
Storage Time	t_{stg}		-	2.50	3.5	μs
Fall Time	t_f		-	0.07	0.3	μs

*1 Test Circuit **2 Pulse $P_W \leq 300\mu s$, Duty Ratio $\leq 6\%$

Copyright© 1990 by FUJITSU LIMITED and Fujitsu Microelectronics, Inc.







查询"2SC3847"供应商
2SC3847








查询"2SC3847"供应商

T-33-13

2SC3847



查询"2SC3847"供应商
2SC3847



查询"2SC3847"供应商
Full Plastic Mold Ring Emitter Transistors

Power Transistor Products

TO-3PF FULL PLASTIC MOLD POWER TRANSISTORS
(RING EMITTER TRANSISTORS)

ELECTRICAL CHARACTERISTICS

Type No.	Maximum Ratings (T _a = 25°C)					Electrical Characteristics (T _a = 25°C)			
	V _{CB0} (V)	V _{CE0} (V)	I _C (A)	I _{CM} * (A)	P _C (W)	V _{CE} (V)	I _C (A)	h _{FE} Min.	t _f (μs)
									Max.
2SC3842	600	400	10	15	70	5	5	10	0.3
2SC3843	600	450	10	20	75	5	6	10	0.2
2SC3844	600	450	15	20	75	5	10	10	0.3
2SC3845	1200	800	3	6	75	5	1	10	0.3
2SC3846	1200	800	6	10	80	5	2	10	0.3
2SC3847	1200	800	10	20	85	5	4	10	0.3
2SC3947	850	500	5	8	70	5	2.5	10	0.3
2SC3948	850	500	10	15	75	5	5	10	0.3
2SC3949	850	500	15	20	80	5	10	10	0.3

* Pulsed P_w ≤ 25μs, D.R. ≤ 50%

Package Outline and Terminal Configuration

