
# **DC/DC converter**


# -12 V/100 mA output

# Absolute Maximum Ratings

Parameter	Symbol	Limits	Unit
Input voltage	Vi	24	V
Output Current	lo	0.1	Α
Operating temperature range	Topr	-15 to +70	°C
Storage temperature range	Tstg	-25 to +85	°C

# Dimensions (mm)






### Electrical Characteristics


Parameter	Symbol	Min.	Тур.	Max.	Unit	Conditions
Input voltage	Vi	8	_	20	٧	
output voltage	Vo	-12.8	-12.0	-11.2	>	
Rated output current	lo	0.01	-	0.1	Α	See Derating Curve.
Line regulation	ΔVo1	ı	2	80	mV	Vi=8V -20VDC lo=0.1A
Load regulation	∆Vo2	_	5	80	mV	lo=0.01 A - 0.1A
Output ripple voltage	Δγ	_	10	80	mVpp	*1
Power conversion efficiency	η	60	70	_	%	
Switching Frequency	f SW	_	250	_	kHz	

<sup>\*1:</sup>Pulsating noise is not included.


# Derating Curve



# Conversion Efficiency




# Sample Application Circuit



Verify proper operation under actual conditions before use. In particular, confirm that the load current does not exceed the maximum rating.

Pin No.	Terminal name		
1	Vo		
2	GND		
3	GND		
4	GND		
5	GND		
6	GND		
7	GND		
8	Skipped		
9	Vin		

# Load Regulation



### External Component Settings

C1: Input Capacitor

Capacitance:  $100\text{-}470\mu\text{F}$ , Rated Voltage: 50V. Low impedance type recommended. Capacitance:  $470\text{-}1000\mu\text{F}$ , Rated Voltage: 50V Use a fast-acting, 2A fuse

C2: Output Capacitor
FUSE: Fuse

Capacitance: 470-1000µ
Use a fast-acting, 2A fus

# Power Module Usage Precautions

查询"BP5122"供应商 Safety Precautions

- 1) The products are designed and manufactured for use in ordinary electronic equipment (i.e. AV/OA/ telecommunication/amusement equipment, home appliances). Please consult with the Company's (ROHM) sales staff if intended for use in devices requiring high reliability (e.g. medical/transport/ aircraft/spacecraft equipment, nuclear power/fuel controllers, automotive/safety devices) and whose malfunction may result in injury or death. In this case, failsafe measures must be taken, including the following:
  - [a] Installation of protection circuits in order to improve system safety
  - [b] Incorporation of redundant circuits in the case of single-circuit failure
- 2) The products are designed for use under normal conditions. Application in special environments can cause a deterioration in product performance. Therefore, verification and confirmation of product performance, prior to use, is recommended. The following environments are considered to be 'special':
  - [a] Outdoors, exposed to direct sunlight or dust
  - [b] In contact with liquids, such as water, oils, chemicals, or organic solvents
  - [c] In areas where exposure to the sea air or corrosive gases (i.e. Cl<sub>2</sub>, H<sub>2</sub>S, NH<sub>3</sub>, SO<sub>2</sub>, NO<sub>2</sub>) can occur
  - [d] In places where the products may be in contact with static electricity or electromagnetic waves
  - [e] In proximity to heat-producing items, plastic cords, or flammable materials
  - [f] In contact with sealing or coating products, such as resin
  - [g] In contact with unclean solder or exposed to water or water-soluble cleaning agents used after soldering
  - [h] In areas where dew condensation occurs
- 3) The products are not designed to be radiation resistant
- 4) The Company is not responsible for any problems resulting from use of the products under conditions not recommended herein.
- 5) The Company should be notified of any product safety issues. Moreover, product safety issues should be periodically monitored by the customer.

# Application Notes

- A sufficient margin must be allowed if changes are made to the peripheral circuit due to variations in the
  inherent tolerances of the external components as well as transient and static characteristics. In addition,
  please be aware that the Company has not conducted investigations on whether or not particular changes
  in the example application circuits would result in patent infringement.
- 2) The application examples, their constants, and other types of information contained herein are applicable only when the products are used in accordance with standard methods.
  - Therefore, if mass production is intended, sufficient consideration to external conditions must be made.

# Notes Regarding Industrial Property /

- 1) The specifications included herein contain information related to the Company's industrial property. Their use other than pertaining to the relevant products is forbidden. Duplication and/or disclosure to a third party without express written permission is strictly prohibited.
- 2) Product information and data, including application examples, contained in the specifications are for reference purposes only; the Company does not guarantee the industrial/intellectual property rights or any other rights of a third party. Accordingly, the Company shall not bear responsibility for:
  - [a] Infringement of the intellectual property rights of a third party
  - [b] Problems arising from the use of the products listed herein
- 3) The Company prohibits the purchaser from exercising or using the intellectual/industrial property rights or any rights belonging to or are controlled by the Company, other than the right to use, sell, or dispose of the products.

#### **Notes**

- No technical content pages of this document may be reproduced in any form or transmitted by any
  means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or
  otherwise dispose of the same, no express or implied right or license to practice or commercially
  exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

#### About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.

