

# International IOR Rectifier

## 30WQ06FNPbF

SCHOTTKY RECTIFIER

3.5 Amp

$I_{F(AV)} = 3.5\text{Amp}$   
 $V_R = 60\text{V}$

### Major Ratings and Characteristics


Characteristics	Values	Units
$I_{F(AV)}$ Rectangular waveform	3.5	A
$V_{RRM}$	60	V
$I_{FSM}$ @tp = 5 $\mu$ s sine	490	A
$V_F$ @3 Apk, $T_J = 125^\circ\text{C}$	0.53	V
$T_J$	-40 to 150	$^\circ\text{C}$

### Description/ Features

The 30WQ06FNPbF surface mount Schottky rectifier has been designed for applications requiring low forward drop and small foot prints on PC board. Typical applications are in disk drives, switching power supplies, converters, free-wheeling diodes, battery charging, and reverse battery protection.

- Popular D-PAK outline
- Small foot print, surface mountable
- Low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free ("PbF" suffix)

### Case Styles



D-PAK (TO-252AA)

30WQ06FNPbF

Bulletin PD-21054 rev. B 08/06



Voltage Ratings

Part number	30WQ06FNPbF
$V_R$ Max. DC Reverse Voltage (V)	60
$V_{RWM}$ Max. Working Peak Reverse Voltage (V)	

Absolute Maximum Ratings

Parameters	30WQ...	Units	Conditions
$I_{F(AV)}$ Max. Average Forward Current * See Fig. 5	3.5	A	50% duty cycle @ $T_C = 133^\circ\text{C}$ , rectangular wave form
$I_{FSM}$ Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 7	490	A	5 $\mu\text{s}$ Sine or 3 $\mu\text{s}$ Rect. pulse
	70		10ms Sine or 6ms Rect. pulse
$E_{AS}$ Non-Repetitive Avalanche Energy	6.0	mJ	$T_J = 25^\circ\text{C}$ , $I_{AS} = 1$ Amp, $L = 12$ mH
$I_{AR}$ Repetitive Avalanche Current	1.0	A	Current decaying linearly to zero in 1 $\mu\text{sec}$ Frequency limited by $T_J$ max. $V_A = 1.5 \times V_R$ typical

Electrical Specifications

Parameters	30WQ...	Units	Conditions
$V_{FM}$ Max. Forward Voltage Drop * See Fig. 1 (1)	0.61	V	@ 3A
	0.76	V	@ 6A
	0.53	V	@ 3A
	0.65	V	@ 6A
$I_{RM}$ Max. Reverse Leakage Current * See Fig. 2 (1)	2	mA	$T_J = 25^\circ\text{C}$
	30	mA	$T_J = 125^\circ\text{C}$
$V_{F(TO)}$ Threshold Voltage	0.38	V	$T_J = T_J$ max.
$r_t$ Forward Slope Resistance	34.31	m $\Omega$	
$C_T$ Typical Junction Capacitance	145	pF	$V_R = 5V_{DC}$ (test signal range 100Khz to 1Mhz) $25^\circ\text{C}$
$L_S$ Typical Series Inductance	5.0	nH	Measured lead to lead 5mm from package body
dv/dt Max. Voltage Rate of Change	10000	V/ $\mu\text{s}$	(Rated $V_R$ )

(1) Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters	30WQ...	Units	Conditions
$T_J$ Max. Junction Temper. Range (*)	-40 to 150	$^\circ\text{C}$	
$T_{stg}$ Max. Storage Temperature Range	-40 to 150	$^\circ\text{C}$	
$R_{thJC}$ Max. Thermal Resistance Junction to Case	4.7	$^\circ\text{C}/\text{W}$	DC operation * See Fig. 4
wt Approximate Weight	0.3(0.01)	g(oz.)	
Case Style	D-PAK		Similar to TO-252AA
Marking Device	30WQ06FN		

(\*)  $\frac{dP_{tot}}{dT_J} < \frac{1}{R_{th(j-a)}}$  thermal runaway condition for a diode on its own heatsink




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Values of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Maximum Thermal Impedance  $Z_{thJC}$  Characteristics

30WQ06FNPbF

Bulletin PD-21054 rev. B 08/06




Fig. 5 - Maximum Allowable Case Temperature Vs. Average Forward Current




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Maximum Non-Repetitive Surge Current

- (2) Formula used:  $T_C = T_J - (P_d + P_{d_{REV}}) \times R_{thJC}$ ;  
 $P_d = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$  (see Fig. 6);  
 $P_{d_{REV}} = \text{Inverse Power Loss} = V_{R1} \times I_R (1 - D)$ ;  $I_R @ V_{R1} = 80\% \text{ rated } V_R$

Outline Table

**NOTES:**  
 1- DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994  
 2- DIMENSION ARE SHOWN IN INCHES (MILLIMETERS)  
 3- LEAD DIMENSION UNCONTROLLED IN 1.5  
 4- DIMENSION D1, E1, L3 & H AS ESTABLISH A MINIMUM MOUNTING SURFACE FOR THERMAL PAD  
 5- SECTION C-C DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN .005 AND 0.10 [0.13 AND 0.25] FROM THE LEAD TIP  
 6- DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005 [0.13] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.  
 7- DIMENSION B & C1 APPLIED TO BASE METAL ONLY.  
 8- DATUM A & B TO BE DETERMINED AT DATUM PLANE A.  
 9- OUTLINE CONFORMS TO JEDEC OUTLINE TO-252AA.

S Y D O	DIMENSIONS		N C E
	MILLIMETERS	INCHES	
A	2.18 2.39	.086 .094	
A1	- 0.15	-.006	
b	0.84 0.89	.035 .036	
b1	0.69 0.79	.028 .031	7
b2	0.76 1.14	.030 .046	
b3	4.95 5.46	.195 .215	4
c	0.48 0.61	.018 .024	
c1	0.41 0.56	.016 .022	7
c2	0.48 0.89	.018 .035	
D	5.97 6.22	.235 .245	4
D1	5.21	.205	4
E	6.55 6.73	.260 .265	6
E1	4.32	.170	4
F	2.29 BSC	.090 BSC	
H	9.40 10.41	.370 .410	
L	1.40 1.78	.055 .070	
L1	2.74 BSC	.108 BSC	
L2	0.51 BSC	.020 BSC	
L3	0.89 1.27	.035 .050	4
L4	- 1.02	-.040	
L5	1.14 1.52	.045 .060	3
#	0° 10°	0° 10°	
#1	0° 15°	0° 15°	
#2	25° 35°	25° 35°	

**LEAD ASSIGNMENTS**  
 HEXCEL  
 1- GATE  
 2- DRAIN  
 3- SOURCE  
 4- DRAIN

**IGBT & CoPAK**  
 1- GATE  
 2- COLLECTOR  
 3- EMITTER  
 4- COLLECTOR

**Modified JEDEC outline TO-252AA**  
 Dimensions in millimeters and (inches)

Part Marking Information

EXAMPLE: THIS IS A 30WQ06FN  
 LOT CODE 8024  
 ASSEMBLED ON WW 02, 2000

INTERNATIONAL  
 RECTIFIER  
 LOGO


ASSEMBLY  
 LOT CODE

PART NUMBER  
 DATE CODE  
 P = LEAD-FREE  
 YEAR 0 = 2000  
 WEEK 02  
 X = SITE ID

30WQ06FNPbF

Bulletin PD-21054 rev. B 08/06

Tape & Reel Information



### Ordering Information Table

Device Code						
<b>30</b>	<b>W</b>	<b>Q</b>	<b>06</b>	<b>FN</b>	<b>TRL</b>	<b>PbF</b>
①	②	③	④	⑤	⑥	⑦
<b>1</b>	-	Current Rating (3.5A)				
<b>2</b>	-	Package Identifier				
		W = D-Pak				
<b>3</b>	-	Schottky "Q" Series				
<b>4</b>	-	Voltage Rating (06 = 60V)				
<b>5</b>	-	FN = TO-252AA (D-Pak)				
<b>6</b>	-					
		• none = Tube (50 pieces)				
		• TR = Tape & Reel				
		• TRL = Tape & Reel (Left Oriented)				
		• TRR = Tape & Reel (Right Oriented)				
<b>7</b>	-					
		• none = Standard Production				
		• PbF = Lead-Free				

Data and specifications subject to change without notice.  
This product has been designed and qualified for AEC Q101 Level and Lead-Free.  
Qualification Standards can be found on IR's Web site.