



SAW Components

SAW filter

Base-station RF

Series/type:	B5109
Ordering code:	B39172B5109U410
Date:	December 23, 2008
Version:	2.0



SAW Components

B5109

SAW filter

1732.50 MHz

Data sheet




Application

- Low-loss base-station RF filter
- Low amplitude ripple
- No matching required for operation at 50Ω
- Usable passband 45 MHz




Features

- Package size 3.0 x 3.0 x 1.1 mm³
- Package code DCC6C
- RoHS compatible
- Approximate weight 0.037 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**



Pin configuration

- 2 Input unbalanced
- 5 Output unbalanced
- 1,3,4,6 To be grounded




SAW Components
B5109
SAW filter
1732.50 MHz
Data sheet

Characteristics

Temperature range for specification: $T = -40\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ. @ 25 °C	max.	
Center frequency	f_C	—	1732.50	—	MHz
Minimum insertion attenuation	$\alpha_{\min}$				
	$f_C \pm 22.5\text{ MHz}$	—	1.7	2.5	dB
Maximum insertion attenuation	$\alpha_{\max}$				
	$f_C \pm 22.5\text{ MHz}$	—	2.2	3.5	dB
Passband width					
	$\alpha_{\text{rel}} \leq 1.8\text{ dB}$ $B_{1.8\text{dB}}$	45	62	—	MHz
Amplitude ripple (p-p)	$\Delta\alpha$				
	$f_C \pm 22.5\text{ MHz}$	—	0.5	1.8	dB
VSWR					
Input	$f_C \pm 22.5\text{ MHz}$	—	1.7:1	2.0:1	
Output	$f_C \pm 22.5\text{ MHz}$	—	1.5:1	2.0:1	
Relative attenuation (relative to $\alpha_{\min}$)	α_{rel}				
10 ... 1680 MHz		20	23	—	dB
1680 ... 1690 MHz		4	10	—	dB
1690 ... 1694 MHz		1.5	6.0	—	dB
1771 ... 1778 MHz		1.5	9.5	—	dB
1778 ... 1785 MHz		5	22	—	dB
1785 ... 1805 MHz		10	28	—	dB
1805 ... 1850 MHz		25	28	—	dB
1850 ... 1880 MHz		30	33	—	dB
1880 ... 3200 MHz		20	27	—	dB
3200 ... 5200 MHz		4	7	—	dB



SAW Components	B5109
SAW filter	1732.50 MHz
Data sheet	SMD

Maximum ratings

Operable temperature range	T	−40/+85	°C	
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	0	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	machine model, 1 pulse
	V _{ESD}	225 ²⁾	V	human body model, 1 pulse
Input power				
1710 ... 1755 MHz	P _{IN}	10	dBm	CW

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulse.

²⁾ acc. to JESD22-A114B (human body model), 1 negative & 1 positive pulse.



SAW Components

B5109


SAW filter

1732.50 MHz


Data sheet



Transfer function



Transfer function (wideband)





SAW Components

B5109

SAW filter



1732.50 MHz

Data sheet





Smith charts

S₁₁ function



S₂₂ function





SAW Components	B5109
SAW filter	1732.50 MHz
Data sheet	SMD

References

Type	B5109
Ordering code	B39172B5109U410
Marking and package	C61157-A7-A67
Packaging	F61074-V8168-Z000
Date codes	L_1126
S-parameters	B5109_NB.s2p B5109_WB.s2p See file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2008. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSSP, CTVS, DSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIM-DAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.