


Bandpass Filter 234251B



1. Features

- IF bandpass filter
- Low-Loss Filter
- Single-ended operation
- Ceramic Surface Mount Device(SMD) Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : S1365


Dimensions shown are nominal in millimeters

Body : Al₂O₃

Lid : Kovar, Ni Plated

Termination : Au plating 0.3 ~ 1.0um, over a 1.27 ~ 8.89um Ni Plating

Pin Configuration	
11	Input
5	Output
6, 12	Ground
Other	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	234251B	
		Rev. Date	2008-10-13	
		Rev.	NJ8019-CS01	1/5



3. Specifications

Fo = 78.0 MHz

Terminating source impedance : 50Ω and matching network


Terminating load impedance : 50Ω and matching network

Operating temperature range : -25℃ ~ +85℃		Minimum	Typical	Maximum
Center Frequency (Fc)	MHz	-	78.0	-
Insertion Loss	dB	-	19.0	21.0
1dB Bandwidth	MHz	41.3	41.9	-
3dB Bandwidth	MHz	-	42.95	-
40dB Bandwidth	MHz	-	48.2	48.7
Amplitude Ripple (Fo +/- 19.8 MHz)	dB	-	0.7	1.0
Group Delay Variation (Fo +/- 19.8 MHz)	nsec	-	30	60
Absolute Delay	usec	-	0.94	-
Ultimate Rejection	dB	40	45	-
Temperature Coefficient of Frequency (TCF)	ppm/°C	-	- 72	-

Room temperature : + 25 ℃		Minimum	Typical	Maximum
Insertion Loss	dB	-	19.0	20.5
Amplitude Ripple (Fo +/- 20.12 MHz)	dB	-	0.7	1.0
Group Delay Variation (Fo +/- 20.12 MHz)	nsec	-	30	60


Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration
- 3) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 4) All attenuation measurements are measured relative to insertion loss

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	234251B	
		Rev. Date	2008-10-13	
		Rev.	NJ8019-CS01	2/5

4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



L1 = 82 nH, L2 = 47 nH
 L3 = 120 nH, C1 = 36 pF


5. Marking Configuration

ITF¹⁾ 08A001²⁾



234251B³⁾

●⁴⁾

- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number
- 4) Pad Number 1 Index

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	234251B	
		Rev. Date	2008-10-13	
		Rev.	NJ8019-CS01	3/5

6. Typical Performance (at +25°C)







ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	234251B	
Rev. Date	2008-10-13	
Rev.	NJ8019-CS01	4/5

Bandpass Filter 234251B

查询2012年供应商



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	234251B	
Rev. Date	2008-10-13	
Rev.	NJ8019-CS01	5/5