





multimec® 3C/3E



- Technical Data:**
- through-hole or SMD
 - 50mA/24VDC
 - single pole/momentary
 - 10.000.000 operations life time
 - IP67 sealing
 - temperature range: low temp: -40/+65°C high temp: -40/+160°C

STANDARD 3C		VARIABLE HEIGHTS 3E	
Dimensions (Through-hole)	Dimensions (SMD)	Dimensions (Through-hole)	Dimensions (SMD)
 PCB layout 	 PCB layout 	 PCB layout 	 PCB layout

HOW TO ORDER

3 C

Switch

Mounting

- T** through-hole
S surface mount

- L 6** low temp.
H 9 high temp.

Optional actuator colour available for low temp. versions only:

Standard versions:
3CTL6
3CTL9
3CTH9
3CSH9

- L 0** blue
L 2 green
L 3 grey
L 4 yellow
L 8 red
L 9 black

3 E

Switch

Mounting

- T** through-hole
S surface mount

- L 9** low temp.
H 9 high temp.

Standard versions:
3ETL9
3ETH9
3ESH9

Standard overall height

08.0
09.5
10.4
12.0
15.0

Custom heights:

3E is available in any height from 08.0 to 15.0 mm.
Min. order qty. for custom heights is 2.000 pcs. / A start-up charge will apply.

Ordering example: 3CTL6 and 3ETL9 - 09.5