

MS5 SERIES

85°C 5mm Height.


◆ FEATURES

- RoHS compliance.

MS5

105°C Version

MH5



◆規格表 SPECIFICATIONS

Items	Characteristics																								
Category Temperature Range	-40~+85℃																								
Rated Voltage Range	4~50V.DC																								
Capacitance Tolerance	±20% (20℃, 120Hz)																								
Leakage Current(MAX) (tan δ)	I=0.01CV or 3 μ A whichever is greater. (After 2 minutes application of rated voltage) I=Leakage Current(μ A) C=Rated Capacitance(μ F) V=Rated Voltage(V)																								
Dissipation Factor(MAX)	<table><tr><td>Rated Voltage (V)</td><td>4</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>tan δ</td><td>0.35</td><td>0.26</td><td>0.22</td><td>0.18</td><td>0.16</td><td>0.14</td><td>0.12</td></tr></table> (20℃, 120Hz)	Rated Voltage (V)	4	6.3	10	16	25	35	50	tan δ	0.35	0.26	0.22	0.18	0.16	0.14	0.12								
Rated Voltage (V)	4	6.3	10	16	25	35	50																		
tan δ	0.35	0.26	0.22	0.18	0.16	0.14	0.12																		
Endurance	After applying rated voltage with rated ripple current for 1000 hrs at 85℃, the capacitors shall meet the following requirements. <table><tr><td>Capacitance Change</td><td>Within ±25% of the initial value.</td></tr><tr><td>Dissipation Factor</td><td>Not more than 200% of the specified value.</td></tr><tr><td>Leakage Current</td><td>Not more than the specified value.</td></tr></table>	Capacitance Change	Within ±25% of the initial value.	Dissipation Factor	Not more than 200% of the specified value.	Leakage Current	Not more than the specified value.																		
Capacitance Change	Within ±25% of the initial value.																								
Dissipation Factor	Not more than 200% of the specified value.																								
Leakage Current	Not more than the specified value.																								
Low Temperature Stability mpedance Ratio(MAX)	<table><tr><td>Rated Voltage (V)</td><td>4</td><td>6.3</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td></tr><tr><td>Z(-25℃)/Z(20℃)</td><td>7</td><td>6</td><td>4</td><td>4</td><td>3</td><td>2</td><td>2</td></tr><tr><td>Z(-40℃)/Z(20℃)</td><td>15</td><td>12</td><td>10</td><td>8</td><td>6</td><td>4</td><td>4</td></tr></table> (120Hz)	Rated Voltage (V)	4	6.3	10	16	25	35	50	Z(-25℃)/Z(20℃)	7	6	4	4	3	2	2	Z(-40℃)/Z(20℃)	15	12	10	8	6	4	4
Rated Voltage (V)	4	6.3	10	16	25	35	50																		
Z(-25℃)/Z(20℃)	7	6	4	4	3	2	2																		
Z(-40℃)/Z(20℃)	15	12	10	8	6	4	4																		

◆MULTIPLIER FOR RIPPLE CURRENT

Frequency coefficient

Frequency (Hz)		60 (50)	120	500	1k	10k $\leq$
Coefficient	0.1 $\sim$ 1 μ F	0.50	1.0	1.20	1.30	1.50
	1.5 $\sim$ 6.8 μ F	0.65	1.0	1.20	1.30	1.50
	10 $\sim$ 68 μ F	0.8	1.0	1.20	1.30	1.50
	100 $\sim$ 470 μ F	0.8	1.0	1.10	1.15	1.20


◆PART NUMBER

					
Rated Voltage	Series	Rated Capacitance	Capacitance Tolerance	Option	Lead Forming
					Case Size



◆ DIMENSIONS

(mm)



φ D	3	3.5	4	5	6.3	8
φ d	0.4		0.45			
F	1.0		1.5	2.0	2.5	

◆ STANDARD SIZE, RATED RIPPLE CURRENT

Size φ D×L(mm), Ripple Current (mA r.m.s./85°C, 120Hz)

WV (V.DC) Cap (μF)	4 (0G)		6.3 (0J)		10 (1A)		16 (1C)	
	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
4.7							● 4×5	11
6.8					● 4×5	10	* 4×5	13
10			● 4×5	14	● 4×5	16	* 4×5	18
15			* 4×5	18	4×5	22	5×5	26
22	● 4×5	20	4×5	22	5×5	30	5×5	35
33	* 4×5	27	5×5	34	5×5	45	6.3×5	51
47	4×5	37	5×5	37	6.3×5	50	6.3×5	65
68	5×5	45	6.3×5	55	6.3×5	59	6.3×5	70
100	5×5	62	6.3×5	62	6.3×5	80	8×5	92
220	6.3×5	74	8×5	120	8×5	145		
330	8×5	145	8×5	145				
470	8×5	181						

WV (V.DC) Cap (μF)	25 (1E)		35 (1V)		50 (1H)	
	Size	Ripple	Size	Ripple	Size	Ripple
0.1					● 4×5	1
0.15					● 4×5	1.5
0.22					● 4×5	2.5
0.33					● 4×5	4
0.47					● 4×5	6
0.68					● 4×5	7
1					● 4×5	8.6
1.5					● 4×5	8.7
2.2			● 4×5	9	* 4×5	9.1
3.3	● 4×5	11	* 4×5	12	4×5	13
4.7	* 4×5	13	4×5	14	5×5	20
6.8	4×5	19	5×5	20	6.3×5	26
10	5×5	27	5×5	27	6.3×5	31
15	5×5	33	6.3×5	35	6.3×5	39
22	6.3×5	46	6.3×5	46	8×5	60
33	6.3×5	54	8×5	65	8×5	80
47	6.3×5	65	8×5	85		
68	8×5	90				
100	8×5	120				

3mm DIA. is available for marked ●, and 3.5mm DIA. is available for marked * when specified.