


## Dual High-Voltage Trench MOS Barrier Schottky Rectifier

Ultra Low  $V_F = 0.40\text{ V}$  at  $I_F = 5\text{ A}$ 

## FEATURES

- Trench MOS Schottky technology
- Low forward voltage drop, low power losses
- High efficiency operation
- Meets MSL level 1, per J-STD-020, LF COMPLIANT maximum peak of 245 °C (for TO-263AB package)
- Solder bath temperature 275 °C maximum, 10 s, per JESD 22-B106 (for TO-220AB, ITO-220AB and TO-262AA package)
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC

RoHS  
COMPLIANT

## TYPICAL APPLICATIONS

For use in high frequency inverters, switching power supplies, freewheeling diodes, OR-ing diode, dc-to-dc converters and reverse battery protection.

## MECHANICAL DATA

**Case:** TO-220AB, ITO-220AB, TO-263AB and TO-262AA

Molding compound meets UL 94 V-0 flammability rating

Base P/N-E3 - RoHS compliant, commercial grade

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test

**Polarity:** As marked

**Mounting Torque:** 10 in-lbs maximum

## PRIMARY CHARACTERISTICS

|                              |          |
|------------------------------|----------|
| $I_{F(AV)}$                  | 2 x 15 A |
| $V_{RRM}$                    | 60 V     |
| $I_{FSM}$                    | 150 A    |
| $V_F$ at $I_F = 15\text{ A}$ | 0.61 V   |
| $T_J$ max.                   | 150 °C   |

MAXIMUM RATINGS ( $T_A = 25\text{ °C}$  unless otherwise noted)

| PARAMETER                                                                                                                  | SYMBOL         | VT3060G       | VFT3060G | VBT3060G | VIT3060G | UNIT |
|----------------------------------------------------------------------------------------------------------------------------|----------------|---------------|----------|----------|----------|------|
| Maximum repetitive peak reverse voltage                                                                                    | $V_{RRM}$      | 60            |          |          |          | V    |
| Maximum average forward rectified current<br>(fig. 1)                                                                      | $I_{F(AV)}$    | 30<br>15      |          |          |          | A    |
| Peak forward surge current 8.3 ms single half sine-wave<br>superimposed on rated load                                      | $I_{FSM}$      | 150           |          |          |          | A    |
| Non-repetitive avalanche energy<br>at $T_J = 25\text{ °C}$ , $L = 60\text{ mH}$ per diode                                  | $E_{AS}$       | 120           |          |          |          | mJ   |
| Peak repetitive reverse current<br>at $t_p = 2\text{ }\mu\text{s}$ , 1 kHz, $T_J = 38\text{ °C} \pm 2\text{ °C}$ per diode | $I_{RRM}$      | 1.0           |          |          |          | A    |
| Isolation voltage (ITO-220AB only)<br>from terminal to heatsink $t = 1\text{ min}$                                         | $V_{AC}$       | 1500          |          |          |          | V    |
| Operating junction and storage temperature range                                                                           | $T_J, T_{STG}$ | - 55 to + 150 |          |          |          | °C   |

## VT3060G, VFT3060G, VBT3060G &amp; VIT3060G

Vishay General Semiconductor

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

| PARAMETER                                              | TEST CONDITIONS       |                                                                           | SYMBOL   | TYP.         | MAX.      | UNIT                |
|--------------------------------------------------------|-----------------------|---------------------------------------------------------------------------|----------|--------------|-----------|---------------------|
| Breakdown voltage                                      | $I_R = 1.0\text{ mA}$ | $T_A = 25\text{ }^{\circ}\text{C}$                                        | $V_{BR}$ | 60 (minimum) | -         | V                   |
| Instantaneous forward voltage per diode <sup>(1)</sup> | $I_F = 5\text{ A}$    | $T_A = 25\text{ }^{\circ}\text{C}$                                        | $V_F$    | 0.49         | -         | V                   |
|                                                        | $I_F = 7.5\text{ A}$  |                                                                           |          | 0.53         | -         |                     |
|                                                        | $I_F = 15\text{ A}$   |                                                                           |          | 0.65         | 0.73      |                     |
|                                                        | $I_F = 5\text{ A}$    | $T_A = 125\text{ }^{\circ}\text{C}$                                       |          | 0.40         | -         |                     |
|                                                        | $I_F = 7.5\text{ A}$  | $T_A = 125\text{ }^{\circ}\text{C}$                                       |          | 0.46         | -         |                     |
|                                                        | $I_F = 15\text{ A}$   |                                                                           |          | 0.61         | 0.69      |                     |
| Reverse current per diode <sup>(2)</sup>               | $V_R = 60\text{ V}$   | $T_A = 25\text{ }^{\circ}\text{C}$<br>$T_A = 125\text{ }^{\circ}\text{C}$ | $I_R$    | -<br>14      | 850<br>40 | $\mu\text{A}$<br>mA |

**Notes:**(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle(2) Pulse test: Pulse width  $\leq 40\text{ ms}$ **THERMAL CHARACTERISTICS** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

| PARAMETER                                          | SYMBOL          | VT3060G    | VFT3060G   | VBT3060G   | VIT3060G   | UNIT                 |
|----------------------------------------------------|-----------------|------------|------------|------------|------------|----------------------|
| Typical thermal resistance per diode<br>per device | $R_{\theta JC}$ | 3.2<br>1.9 | 6.2<br>5.0 | 3.2<br>1.9 | 3.2<br>1.9 | $^{\circ}\text{C/W}$ |

**ORDERING INFORMATION** (Example)

| PACKAGE   | PREFERRED P/N  | UNIT WEIGHT (g) | PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
|-----------|----------------|-----------------|--------------|---------------|---------------|
| TO-220AB  | VT3060G-E3/4W  | 1.88            | 4W           | 50/tube       | Tube          |
| ITO-220AB | VFT3060G-E3/4W | 1.76            | 4W           | 50/tube       | Tube          |
| TO-263AB  | VBT3060G-E3/4W | 1.39            | 4W           | 50/tube       | Tube          |
| TO-263AB  | VBT3060G-E3/8W | 1.39            | 8W           | 800/reel      | Tape and reel |
| TO-262AA  | VIT3060G-E3/4W | 1.45            | 4W           | 50/tube       | Tube          |


**RATINGS AND CHARACTERISTICS CURVES**( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

Figure 1. Maximum Forward Current Derating Curve




Figure 2. Forward Power Dissipation Characteristics Per Diode




Figure 3. Typical Instantaneous Forward Characteristics Per Diode




Figure 5. Typical Transient Thermal Impedance Per Diode




Figure 4. Typical Reverse Characteristics Per Diode




Figure 6. Typical Junction Capacitance Per Diode


## VT3060G, VFT3060G, VBT3060G &amp; VIT3060G

Vishay General Semiconductor




## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)


TO-220AB




ITO-220AB




TO-262AA



TO-263AB



Mounting Pad Layout



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.