




EMI Filter with ESD Protection for SIM Card Applications

CM1623

Features


- 4-channel EMI filtering with integrated ESD protection
- Pi-style EMI filters in a capacitor-resistor-capacitor (C-R-C) network
- $\pm 15\text{kV}$ ESD protection on each channel (IEC 61000-4-2 Level 4, contact discharge)
- 8-lead UDFN package with 0.40mm pitch
- Tiny UDFN package size: 1.7mm x 1.35mm x 0.5mm
- Increased robustness against vertical impacts during manufacturing process
- RoHS compliant, lead-free finish

Electrical Schematic



* See Package Pinout Diagram
for expanded pin information.

PACKAGE / PINOUT DIAGRAMS



Notes:

1) These drawings are not to scale.

Pin Information

PIN DESCRIPTIONS

PIN	NAME	DESCRIPTION	PIN	NAME	DESCRIPTION
1	RST	Filter + ESD Channel 1	8	RST	Filter + ESD Channel 1
2	CLK	Filter + ESD Channel 2	7	CLK	Filter + ESD Channel 2
3	DATA	Filter + ESD Channel 3	6	DATA	Filter + ESD Channel 3
4	VCC	V External	5	VCC	V External
GND PAD	GND	Device Ground			

Ordering Information

PART NUMBERING INFORMATION

Pins	Package	Lead-free Finish	
		Ordering Part Number ¹	Part Marking
8	UDFN-8	CM1623-04DE	P23

Note 1: Parts are shipped in Tape and Reel form unless otherwise specified.

Specifications

ABSOLUTE MAXIMUM RATINGS

PARAMETER	RATING	UNITS
Storage Temperature Range	-65 to +150	°C
DC Power per Resistor	100	mW
DC Package Power Rating	500	mW

STANDARD OPERATING CONDITIONS

PARAMETER	RATING	UNITS
Operating Temperature Range	-40 to +85	°C

ELECTRICAL OPERATING CHARACTERISTICS (SEE NOTE 1)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
R1	Reset Channel Resistance		80	100	120	Ω
R2	Clock Channel Resistance		37.6	47	56.4	Ω
R3	Data Channel Resistance		80	100	120	Ω
C1	Capacitance on Pins 1, 2, and 3	At 1 MHz, $V_{IN}=0V$	16	20	24	pF
C2	Capacitance on Pins 4 and 5	At 1 MHz, $V_{IN}=0V$		18		pF
I_{LEAK}	Diode Leakage Current (Reverse Bias)	$V_{DIODE}=3.3V$		0.1	1.0	μA
V_{SIG}	Signal Clamp Voltage: a) Positive Clamp b) Negative Clamp	$I_{LOAD} = 10mA$ $I_{LOAD} = -10mA$	5.6 -1.5	6.8 -0.8	9.0 -0.4	V V
V_{ESD}	ESD Peak Discharge Voltage Protection on All Pins In-system ESD Withstand Voltage: a) Contact Discharge per IEC 61000-4-2 Level 4 b) Air Discharge per IEC 61000-4-2 Level 4	$T_A=25^{\circ}C$; Note 2	± 15 ± 15	± 15 ± 15		kV kV kV

Note 1: All parameters specified at $T_A=25^{\circ}C$ unless otherwise noted.

Note 2: Standard IEC 61000-4-2 with $C_{Discharge} = 150pF$, $R_{Discharge} = 330\Omega$.

Performance Information

Typical Filter Performance ($T_A=25^{\circ}\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 1. Insertion Loss vs. Frequency, Filter 1 (Pins 1 and 8)




Figure 2. Insertion Loss vs. Frequency, Filter 2 (Pins 2 and 7)

Performance Information (Cont'd)

Typical Filter Performance ($T_A=25^\circ\text{C}$, DC Bias=0V, 50 Ohm Environment)




Figure 3. Insertion Loss vs. Frequency, Filter 3 (Pins 3 and 6)




Figure 4. Insertion Loss vs. Frequency, Filter 4 (Pins 4 and 5)




Figure 5. Diode Capacitance vs. Input Voltage (Normalized to Capacitance at 0VDC and 25°C)


Mechanical Details

UDFN-08 Mechanical Specifications

Dimensions for the CM1623 supplied in a 8-lead, 0.4mm pitch UDFN package are presented below.

PACKAGE DIMENSIONS						
Package	UDFN					
JEDEC No.	MO-229C [†]					
Leads	8					
Dim.	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A	0.45	0.50	0.55	0.018	0.020	0.022
A1	0.00	0.02	0.05	0.000	0.001	0.002
A3	0.127 REF			0.005 REF		
b	0.15	0.20	0.25	0.006	0.008	0.010
D	1.60	1.70	1.80	0.063	0.067	0.071
D2	1.10	1.20	1.30	0.043	0.047	0.051
E	1.25	1.35	1.45	0.049	0.053	0.057
E2	0.30	0.40	0.50	0.012	0.016	0.020
e	0.40 BSC			0.016 BSC		
K	0.22			0.009		
L	0.15	0.25	0.35	0.006	0.010	0.014
# per tape and reel	3000 pieces					
Controlling dimension: millimeters						


[†]This package is compliant with JEDEC standard MO-229C with the exception of the "D", "D2", "E", "E2", "K" and "L" dimensions as called out in the table above.



**Dimensions for 8-Lead, 0.4mm pitch
UDFN Package**


Tape and Reel Specifications

PART NUMBER	PACKAGE SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P_0	P_1
CM1623	1.70 X 1.35 X 0.50	1.95 X 1.60 X 0.60	8mm	178mm (7")	3000	4mm	4mm



CM1623

[查询"CM1623-D"供应商](#)

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855
Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local
Sales Representative