

查询"LM6-PBL1-3B-N1"供应商

Cree® SMD LED

Model # LM6-PBL1-3B-N1

Data Sheet

120-degree, 3.3 x 3.5-mm, SMT LED in blue color with water-transparent lens and black coated surface

Applications

- Indoor and Outdoor Displays
- Backlighting
- Coupling into Light Guides
- RGB Full-Color Displays

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$)

Items	Symbol	Absolute Maximum Rating	Unit
		R	
Forward Current ^{Note 1}	I_F	3 x 40	mA
Peak Forward Current ^{Note 2}	I_{FP}	3 x 100	mA
Reverse Voltage	V_R	5	V
Power Dissipation	P_D	3 x 160	mW
Operation Temperature	T_{opr}	-40 ~ +100	°C
Storage Temperature	T_{stg}	-40 ~ +100	°C
Junction Temperature	T_J	110	°C
Junction/ambient 1 chip on ^{Note 3}	R_{THJA}	450	°C/W
Junction/ambient 3 chips on ^{Note 3}	R_{THJA}	680	°C/W
Junction/solder point 1 chip on	R_{THJS}	300	°C/W
Junction/solder point 3 chips on	R_{THJS}	480	°C/W

Notes:

1. Single-color light.
2. Pulse width $<=0.1$ msec, duty $<=1/10$.
3. R_{TH} test condition: mounted on PC Board FR 4 (pad size $>=16$ mm²)

Typical Electrical & Optical Characteristics ($T_A = 25^\circ\text{C}$)

Characteristics	Condition	Symbol	Minimum	Typical	Maximum	Unit
Dominant Wavelength	$I_F = 3 \times 20$ mA	λ_{DOM}	460	470	480	nm
Viewing Angle at 50%	$I_F = 3 \times 20$ mA	$2\theta_{1/2}$		120		deg
Forward Voltage	$I_F = 3 \times 20$ mA	V_F		3.4	4.0	V
Luminous Intensity	$I_F = 3 \times 20$ mA	I_v	355	600		mcd
Reverse Current (max)	$V_R = 5$ V	I_R			10	μA


查询"LM6-PBL1-3B-N1"供应商

Standard Bins for LM6-PBL1-3B-N1 ($I_F = 3 \times 20 \text{ mA}$)

Lamps are sorted to luminous intensity (I_v) and chromaticity coordinates (x, y) bins shown.

Orders for LM6-PBL1-3B-N1 may be filled with any or all bins contained as below.

All luminous intensity (I_v) and chromaticity coordinates (x, y) values shown and specified are at $I_F = 3 \times 20 \text{ mA}$.



Important Notes:

1. All ranks will be included per delivery; rank ratio will be based on the dice distribution.
2. Tolerance of measurement of luminous intensity is $\pm 10\%$.
3. Tolerance of measurement of the dominant wavelength is $\pm 1 \text{ nm}$.
4. Tolerance of measurement of V_F is $\pm 0.05 \text{ V}$.
5. Packaging methods are available for selection; please refer to the "Cree LED Lamp Packaging Standard" document.
6. Please refer to the "Cree LED Lamp Reliability Test Standards" document for reliability test conditions.
7. Please refer to the "Cree LED Lamp Soldering & Handling" document for information about how to use this LED product safely.

查询"LM6-PBL1-3B-N1"供应商
Graphs




FIG.1 FORWARD CURRENT VS.
FORWARD VOLTAGE.




FIG.2 REVERSE CURRENT VS.
REVERSE VOLTAGE.




FIG.3 RELATIVE LUMINOUS
INTENSITY VS. FORWARD CURRENT




FIG.4 RELATIVE LUMINOUS INTENSITY VS.
WAVELENGTH.




FIG.5 MAXIMUM FORWARD DC CURRENT VS.
SOLDER POINT TEMPERATURE




FIG.6 FAR FIELD PATTERN.





FIG.7 MAXIMUM FORWARD DC CURRENT VS.
AMBIENT TEMPERATURE

查询"LM6-PBL1-3B-N1"供应商
Mechanical Dimensions

All dimensions are in mm.



Notes

RoHS Compliance

The levels of environmentally sensitive, persistent biologically toxic (PBT), persistent organic pollutants (POP), or otherwise restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS), as amended through April 21, 2006.

Vision Advisory Claim


Users should be cautioned not to stare at the light of this LED product. The bright light can damage the eye.

[查询"LM6-PBL1-3B-N1"供应商](#)

Kit Number System

Cree LED lamps are tested and sorted into performance bins. A bin is specified by ranges of color, forward voltage, and brightness. Sorted LEDs are packaged for shipping in various convenient options. Please refer to the "Cree LED Lamp Packaging Standard" document for more information about shipping and packaging options.

Cree LEDs are sold by order codes in combinations of bins called kits. Order codes are configured in the following manner:



* Contact your Cree sales representative for ordering information.

Standard Available Kits*

Kit Number	Description
LM6-PBL1-3B-N1-00001	SMD 120 Blue 470nm, FULL RANK, Tape & Reel

* Please contact your Cree representative about the availability of non-standard kits.