


20 PIN DIP ETHERNET 10/100 BASE DUAL PORT TRANSFORMER**P/N: 20PT1026A DATA SHEET**

Page : 1/1

Feature

- IEEE 802.3 Ethernet compatible, 100 BASE-TX.
- 20 PIN DIP Package compatible with popular IC chips.
- Design for multiport repeater and Ethernet switching Hub application.
- Customer designs available for specific application.
- Operating temperature range : 0°C to +70°C.
- Storage temperature range: -25°C to +125°C.

Electrical Specifications @ 25°C

Part Number	Turns Ratio (±5%)		OCL(î H Min) @100KHz/0.1Vrms 8mA DC/Bias	L.L (î H Max)	Cw/w (pF Max)	Rise Time (ns TYP)	DCR (TX /RX) (Û Max)	HI-POT (Vrms)
	TX	RX						
20PT1026A	1CT:1CT	1:1	350	0.5	28	2.5	0.9/1.1	1500

Continue

Part Number	Insertion Loss (dB Max)	Return Loss (dB Min)			Cross talk (dB Min)		DCMR (dB Min)		
	0.3-100MHz	0.3-30MHz	30-60MHz	60-80MHz	0.3-60MHz	60-100MHz	0.3-30MHz	30-60MHz	60-100MHz
20PT1026A	-1.15	-18	-14	-12	-40	-35	-38	-33	-30

Schematic**Mechanical**