

## 5 x 20 mm Medium Acting Fuse



- Designed to Japanese Standard JIS C6575.
- Available in Cartridge, Axial and Radial Lead Format.
- Available in ratings of 500mA to 10A.

### ELECTRICAL CHARACTERISTICS:

| % of Ampere Rating | Opening Time              |
|--------------------|---------------------------|
| 130%               | 1 hour, <b>Minimum</b>    |
| 160%               | 1 hour, <b>Maximum</b>    |
| 200%               | 2 minutes, <b>Maximum</b> |

AGENCY APPROVALS: MITI B Approval.

### INTERRUPTING RATING:

500 amperes at 125 VAC

100 amperes at 250 VAC

**PACKAGING:** For Axial Leads add packaging suffix XE. For Radial Leads add packaging suffix XW. For tape and reel options contact Littelfuse.

### ORDERING INFORMATION:

| Catalog Number | Ampere Rating | Voltage Rating | Nominal Resistance Cold Ohms | Nominal Melting I <sup>2</sup> t A <sup>2</sup> Sec |
|----------------|---------------|----------------|------------------------------|-----------------------------------------------------|
| 0232.500*      | .500          | 250            | 0.60                         | 1.11                                                |
| 0232.630*      | .630          | 250            | 0.46                         | 2.18                                                |
| 0232.800*      | .800          | 250            | 0.48                         | 3.59                                                |
| 0232.001.      | 1             | 250            | 0.0957                       | 1.41                                                |
| 0232 1.25      | 1.25          | 250            | 0.0707                       | 4.22                                                |
| 0232 01.6      | 1.6           | 250            | 0.0567                       | 7.14                                                |
| 0232 002.      | 2             | 250            | 0.0385                       | 8.47                                                |
| 0232 02.5      | 2.5           | 250            | 0.0297                       | 14.25                                               |
| 0232 003.      | 3             | 250            | 0.0257                       | 17.65                                               |
| 0232 3.15      | 3.15          | 250            | 0.0235                       | 22.55                                               |
| 0232 004.      | 4             | 250            | 0.018                        | 38.75                                               |
| 0232 005.      | 5             | 250            | 0.0145                       | 58.25                                               |
| 0232 06.3      | 6.3           | 250            | 0.0105                       | 92.85                                               |
| 0232 008.      | 8             | 250            | .0076                        | 187.5                                               |
| 0232 010.      | 10            | 250            | .0061                        | 298.5                                               |

\*Japanese Standards for 5 x 20 mm fuses do not include ratings below 1 ampere.

