

## Preliminary

# 60W 9xxnm 20% Fill Factor High Power Laser Diode Bar on Passive Cu Block Cooler

## BPC60C-9xx-02

The Bookham BPC60C-9xx-02 20% fill factor laser diode bar on passive cooler series has been designed to provide the increased brightness and reliability required for collimated pumping of next generation solid-state lasers and direct applications. The proprietary E2 front mirror passivation process, developed at our Zurich site, prevents Catastrophic Optical Damage (COD) to the laser diode facet even at extremely high output powers. The laser diode bars are mounted on an expansion matched CuW submount onto a Cu block package providing very high reliability in CW and pulsed (1-Hz type) applications.

### Features:

- Mounted 10mm x 2.4mm laser diode bar
- Passive 1" x 1" Cu block cooler
- 20% fill factor (100µm emitter / 500µm pitch)
- 60W operating power
- Highly reliable single quantum well MBE structure
- Telecom-grade AuSn mounting technology
- Standard wavelengths at 915nm, 940nm, and 980nm (others available on request)
- RoHS compliant 

### Applications:

- Collimated solid-state laser pumping
- Direct applications such as material processing
- Printing
- Medical



## Characteristics


Parameter	Symbol	Typical	Unit
CW Output Power	$P_{op}$	60	W
Center Wavelength <sup>[1]</sup> BPC60C-915-02 BPC60C-940-02 BPC60C-980-02	$\lambda_{c915}$ $\lambda_{c940}$ $\lambda_{c980}$	$915 \pm 10$ $940 \pm 10$ $980 \pm 10$	nm
Spectral Width (FWHM)	$\Delta\lambda$	3	nm
Wavelength Shift with Temperature	$d\lambda_c/dT_{op}$	0.3	nm/°C
Beam Divergence Parallel to Junction (90% of Power) Perpendicular to Junction (FWHM) Perpendicular to Junction (90% of Power)	$\theta_{//}$ $\theta_{\perp}$ $\theta_{\perp}$	7 26 60	deg
Polarization	—	TE	—
Threshold Current	$I_{th}$	7	A
Slope Efficiency	$\eta_D = P_{op}/(I_{op} - I_{th})$	1	W/A
Conversion Efficiency	$H = P_{op}/(V_{op} \times I_{op})$	60	%
Series Resistance	$R_s$	5	mΩ
Operating Current	$I_{op}$	65	A
Operating Voltage	$V_{op}$	1.5	V
Operating Temperature	$T_{op}$	$25 \pm 5$	°C

[1] Reduced wavelength window / extended range available on request (900-1060nm).

## Bar Dimensions

Parameter	Symbol	Typical	Unit
Bar Width	$b$	10	mm
Resonator Length	$l$	2.4	mm
Number of Emitters	$n$	19	—
Emitter Spacing	$p$	500	μm
Emission Width	$w$	100	μm
Fill Factor	$f$	20	%

## Passive Cu Block Cooler Dimensions (mm)



## RoHS Compliance



Bookham is fully committed to environment protection and sustainable development and has set in place a comprehensive program for removing polluting and hazardous substances from all of its products. The relevant evidence of RoHS compliance is held as part of our controlled documentation for each of our compliant products. RoHS compliance parts are available to order, please refer to the ordering information section for further details.

### Ordering Information:

BPC60C-915-02	60W 915nm 20% Fill Factor Laser Diode Bar on Passive Cu Block Cooler
BPC60C-940-02	60W 940nm 20% Fill Factor Laser Diode Bar on Passive Cu Block Cooler
BPC60C-980-02	60W 980nm 20% Fill Factor Laser Diode Bar on Passive Cu Block Cooler

## Contact Information

### Bookham (Switzerland) AG

Binzstrasse 17  
8045 Zurich  
Switzerland

• Tel: +41 44 455 8787  
• Fax: +41 44 455 8586

[www.bookham.com](http://www.bookham.com)  
highpower@bookham.com

### EMEA Sales Contact

Gunnar Stolze  
• Tel: +41 79 635 3777

### North America Sales Contact

Michael Cutler  
• Tel: +1 678 763 0777

### ASIA Sales Contact

Patrick Lee  
• Tel: +852 9197 7014

### Japan Sales Contact

Japan Laser Corporation  
• Tel: +813 5285 0861

### Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by Bookham before they become applicable to any particular order or contract. In accordance with the Bookham policy of continuous improvement specifications may change without notice. The publication of information in this data sheet does not imply freedom from patent or other protective rights of Bookham or others. Further details are available from any Bookham sales representative.



THIS PRODUCT COMPLIES  
WITH 21CFR 1040.10