


SKiiP 192GD170-374CTV ...

查询"SKiiP192GD170-374CTV"供应商



SKiiP[®] 2

6-pack - integrated intelligent Power System

Power section

SKiiP 192GD170-374CTV


Features

- SKiiP technology inside
- Low loss IGBTs
- CAL diode technology
- Integrated current sensor
- Integrated temperature sensor
- Integrated heat sink
- IEC 60721-3-3 (humidity) class 3K3/IE32 (SKiiP[®] 2 System)
- IEC 68T.1 (climate) 40/125/56 (SKiiP[®] 2 power section)

1) with assembly of suitable MKP capacitor per terminal (SEMIKRON type is recommended)

Absolute Maximum Ratings		$T_s = 25\text{ °C}$ unless otherwise specified	
Symbol	Conditions	Values	Units
IGBT			
V_{CES}	Operating DC link voltage	1700	V
$V_{CC}^{1)}$		1200	V
V_{GES}		± 20	V
I_C	$T_s = 25\text{ (70) °C}$	175 (131)	A
Inverse diode			
$I_F = -I_C$	$T_s = 25\text{ (70) °C}$	175 (131)	A
I_{FSM}	$T_j = 150\text{ °C}$, $t_p = 10\text{ ms}$; sin.	1440	A
I^2t (Diode)	Diode, $T_j = 150\text{ °C}$, 10 ms	10	kA ² s
$T_j, (T_{stg})$		- 40 (- 25) ... + 150 (125)	°C
V_{isol}	AC, 1 min. (mainterminals to heat sink)	4000	V


Characteristics		$T_s = 25\text{ °C}$ unless otherwise specified			
Symbol	Conditions	min.	typ.	max.	Units
IGBT					
V_{CESat}	$I_C = 140\text{ A}$, $T_j = 25\text{ (125) °C}$		3,3 (4,3)	3,9	V
V_{CEO}	$T_j = 25\text{ (125) °C}$		1,7 (2)	2 (2,3)	V
r_{CE}	$T_j = 25\text{ (125) °C}$		11,5 (16,7)	13,7 (18,8)	mΩ
I_{CES}	$V_{GE} = 0\text{ V}$, $V_{CE} = V_{CES}$, $T_j = 25\text{ (125) °C}$		(10)	1	mA
$E_{on} + E_{off}$	$I_C = 140\text{ A}$, $V_{CC} = 900\text{ V}$ $T_j = 125\text{ °C}$, $V_{CC} = 1200\text{ V}$			121	mJ
				178	mJ
$R_{CC' + EE'}$	terminal chip, $T_j = 125\text{ °C}$		0,5		mΩ
L_{CE}	top, bottom		15		nH
C_{CHC}	per phase, AC-side		0,8		nF
Inverse diode					
$V_F = V_{EC}$	$I_F = 140\text{ A}$, $T_j = 25\text{ (125) °C}$		2,4 (2,2)	2,9	V
V_{TO}	$T_j = 25\text{ (125) °C}$		1,3 (1)	1,6 (1,3)	V
r_T	$T_j = 25\text{ (125) °C}$		7,5 (8,5)	9,5 (10,5)	mΩ
E_{rr}	$I_C = 140\text{ A}$, $V_{CC} = 900\text{ V}$ $T_j = 125\text{ °C}$, $V_{CC} = 1200\text{ V}$			15	mJ
				17	mJ
Mechanical data					
M_{dc}	DC terminals, SI Units	6		8	Nm
M_{ac}	AC terminals, SI Units	13		15	Nm
w	SKiiP [®] 2 System w/o heat sink		2,7		kg
w	heat sink		6,6		kg
Thermal characteristics (P16 heat sink; 295 m³/h); " r " reference to temperature sensor					
$R_{th(j-s)I}$	per IGBT			0,114	K/W
$R_{th(j-s)D}$	per diode			0,4	K/W
$R_{th(s-a)}$	per module			0,036	K/W
Z_{th}	R_i (mK/W) (max. values)	tau _i (s)			
		1	2	3	4
$Z_{th(j-r)I}$		13	88	14	1
$Z_{th(j-r)D}$		44	308	48	1
$Z_{th(r-a)}$		11,1	18,3	3,5	3,1
					204
					60
					6
					0,02



Case S 3

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee, expressed or implied is made regarding delivery, performance or suitability.

查询"SKiiP192GD170-374CTV"供应商



SKiiP® 2

6-pack - integrated intelligent Power System

6-pack integrated gate driver

SKiiP 192GD170-374CTV

Gate driver features


- CMOS compatible inputs
- Wide range power supply
- Integrated circuitry to sense phase current, heat sink temperature and DC-bus voltage (option)
- Short circuit protection
- Over current protection
- Over voltage protection (option)
- Power supply protected against under voltage
- Interlock of top/bottom switch
- Isolation by transformers
- Fibre optic interface (option for GB-types only)
- IEC 68T.1 (climate) 25/85/56 (SKiiP® 2 gate driver)

Absolute Maximum Ratings			
Symbol	Conditions	Values	Units
V _{S1}	stabilized 15 V power supply	18	V
V _{S2}	unstabilized 24 V power supply	30	V
V _{iH}	input signal voltage (high)	15 + 0,3	V
dv/dt	secondary to primary side	75	kV/μs
V _{isolIO}	input / output (AC, r.m.s., 2s)	4000	Vac
V _{isol12}	output 1 / output 2 (AC, r.m.s., 2s)	1500	Vac
f _{max}	switching frequency	20	kHz
T _{op} (T _{stg})	operating / storage temperature	- 25 ... + 85	°C

Characteristics				(T _a = 25 °C)	
Symbol	Conditions	min.	typ.	max.	Units
V _{S1}	supply voltage stabilized	14,4	15	15,6	V
V _{S2}	supply voltage non stabilized	20	24	30	V
I _{S1}	V _{S1} = 15 V	340+380*f/f _{max} +3,5*(I _{AC} /A)			mA
I _{S2}	V _{S2} = 24 V	250+260*f/f _{max} +2,6*(I _{AC} /A)			mA
V _{iT+}	input threshold voltage (High)	11,2			V
V _{iT-}	input threshold voltage (Low)	5,4			V
R _{IN}	input resistance	10			kΩ
t _{d(on)IO}	input-output turn-on propagation time	1,2			μs
t _{d(off)IO}	input-output turn-off propagation time	3			μs
t _{pERRRESET}	error memory reset time	9			μs
t _{TD}	top / bottom switch : interlock time	2,3			μs
I _{analogOUT}	8 V corresponds to max. current of 15 V supply voltage	150			A
I _{Vs1outmax}	(available when supplied with 24 V)	50			mA
I _{A0max}	output current at pin 13/20/22/24/26	5			mA
V _{0l}	logic low output voltage	0,6			V
V _{0H}	logic high output voltage	30			V
I _{TRIPSC}	over current trip level (I _{analog OUT} = 10 V)	188			A
I _{TRIPLG}	ground fault protection	43			A
T _{tp}	over temperature protection	110	120		°C
U _{DCTRIP}	trip level of U _{DC} -protection (U _{analog OUT} = 9 V); (option)	1200			V

For electrical and thermal design support please use SEMISEL.
Access to SEMISEL is via SEMIKRON website <http://www.semikron.com>.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee, expressed or implied is made regarding delivery, performance or suitability.



Case S 3