

[查询"53025"供应商](#)

TECHNICAL DATA

RTD Compound

Hand Applied Metal Cutting Lubricant

Description

ROCOL RTD Compound is a soft paste for use in reaming, tapping and drilling and other metal cutting operations. ROCOL RTD Compound is suitable for all metals including hardened steels, nimonic and titaniums. Containing extreme pressure additives, ROCOL RTD Compound significantly reduces friction giving superb cutting performance.

Outstanding Features

- Extends tool life
- Improves surface finish
- Allows increases removal rates
- Reduces production costs

Directions for use

Apply directly to the tool or workpiece by brush, or by dipping tool into the compound.

Technical Data

Appearance : Brown Paste Odour : Mild Sulphur

Solvents : None

Shell 4 Ball

Weld Load : 800kg

Load-Wear Index : 315kg

Tapping Torque (316 Stainless Steel) : 8.6 NM

*Corrosion (Steel Plate at
175°C
for 5 minutes) : None*

*Storage :
0°
to
40°.
Normal storage*

Pack Sizes : 50g, 500g, 15kg

Health and Safety

Further Technical Data and Safety Data Sheets are available from the Customer Service Department, ROCOL Ltd., ROCOL House, Swillington, Leeds, LS26 8BS, England.

Telephone: 0113 232 2700, (When calling from outside UK: 44 113 232 2700);

[查询"53025"供应商](#)

Fax: 0113 232 2760, (When faxing from outside UK: 44 113 232 2760).

Issue: 5302a 290300