

A1084-A/B

Positioning Products



Miniaturized GPS receiver for passive and active antennas

Many GPS applications, such as portable devices or telematics units, require a built-in antenna. However, an external antenna connector is often desired for GPS performance or reliability reasons. This is what the new A1084-A GPS receiver supports with its second antenna pin and on board antenna switch, whilst the A1084-B supports both passive and active antennas on a single antenna pin. This very compact SiRFStar III based GPS receiver comes completely shielded with a lid and with benchmark-setting GPS performance on a very small footprint.

- Benchmarking sensitivity ■ -159 dBm tracking
- Fastest TTFF (Time To First Fix) ■ < 35 s under cold start conditions (typical)
- Ultra-low power consumption ■ 86 mW average in tracking mode
- Smallest footprint ■ 15 x 15 mm²
- Antenna ■ Passive and active antenna supported
- Dual antenna support ■ RF switch on A1084-A

Positioning Receiver Portfolio

[查询"A1084-A"供应商](#)

With the mission to support our customers in implementing GPS functionality into their systems, Vincotech is offering a large product portfolio to cover almost all integration possibilities in an easy way. A dedicated R&D team located in the Munich region, Germany, develops sensitive positioning solutions based on state of the art technologies. All GPS products are manufactured in our ISO9001 and TS16949 certified factory in the EU. Our modules comply to the RoHS standard and are 100% electrically and functionally tested prior to packaging. This way we constantly guarantee high quality products.


PRODUCTS SHOWN IN ACTUAL SIZE

GPS Receivers



A1080-A A1082-A A1084-A/B A1088-A

Smart Antenna Modules



A1035-D A1035-E A1035-H

GPS Receivers													Smart Antenna Modules														
	Supply voltage / V	Current draw @ I fix per sec / mA	Operating temperature / °C	Low Power Mode Trickle Power	Low Power Mode Push-To-Fix	Low Power Mode Keep Ephemeris Alive	AGPS Ephemeris Push	Active antenna	Passive antenna	2nd antenna input Antenna switch	Internal antenna supply	Firmware update (Flash) ROM	SBAS support	Back-up battery option	Shielding lid	AEC-Q compliant components	Size / mm ²	Antenna type	Circular polarisation	Linear polarisation	Plug-in module	SMD solderable	External antenna pin	Shielding lid	Size / mm ²	Based on GPS receiver	
A1080-A	3.3	23	-30/85	■	■		■	■			■	■	■	■			19x16	A1035-D	patch	■		■			■	35x35	A1080-A
A1080-B	3.3	23	-40/85	■	■		■	■			■	■	■	■			19x16	A1035-E	patch	■		■			21x21	A1082-A	
A1082-A	1.8	35	-30/85			■		■						*			14x12	A1035-H	patch	■			■	■	■	30x17	A1084-A
A1084-A	3.3	26	-30/85	■	■		■	■	■	■	■		■	■	■	■	15x15	A1085-A**	chip		■	■	■	■	■	31x17	A1080-A
A1084-B	3.3	26	-30/85	■	■		■	■	■	■	■		■	■	■	■	15x15	A1086-A**	meander		■	■	■	■	t.b.d.	25x15	A1084-A
A1088-A	3.3	30	-40/85	■	■		■	■			■	■	■	■	■	■	28x19	A1086-B**	meander		■	■	■	■	t.b.d.	25x15	A1084-A

*SRAM backup possible with Enable pin
**product planned



Technical Details A1084-A/B

PERFORMANCE

Channels	20 parallel tracking
Correlators	200,000 plus
Frequency	L1 – 1,575 MHz
Sensitivity	
Tracking	-159 dBm
Acquisition (cold start)	-142 dBm
Position accuracy (horizontal)	
< 2.5 m CEP autonomous	
< 2.0 m CEP SBAS	
Time To First Fix	
Hot start ¹⁾	< 1 s
Warm start ²⁾	< 32 s
Cold start ³⁾	< 35 s

COMMUNICATION

Standard GPS software	
NMEA message switchable	GGA, GSA, GSV, VTG, RMC, GLL
Baud rate	4,800 (default) to 115,200
Serial ports	
Tx0	NMEA output
Rx0	NMEA input

1) The receiver has estimates of time/date/position and valid almanac and ephemeris data.
2) The receiver has estimates of time/date/position and almanac.
3) The receiver has no estimate of time/date/position, and no recent almanac.
4) An external current limiter is suggested to avoid damage in fault conditions.

The information provided herein is believed to be reliable at press time. Vincotech assumes no responsibility for inaccuracies or omission. Vincotech assumes no responsibility for the use of this information, and all such information shall be entirely at the users own risk. Prices and specifications are subject to change without notice. Vincotech does not authorize or warrant any of its products for use in lifesupport devices and/or systems.

ENVIRONMENT

Temperature	
Operating	-30° to +85°C
Storage	-40° to +85°C
Humidity	
	Non condensing

POWER

Supply voltage	3.0 to 3.6 VDC
Current draw	
Acquisition	31 mA (typical)
Tracking	26 mA (typical)
Standby	20 µA (typical)
Antenna supply via VANT	
Voltage range	up to 5.0V
Max. allowed current ⁴⁾	50 mA

MECHANICAL

Dimensions	15.2 x 15.2 x 2.4 mm ³
	0.6" x 0.6" x 0.1"
Weight	1.2 g / 0.042 oz.

YOUR PARTNER

Vincotech GmbH
Biberger Straße 93
82008 Unterhaching/Germany

Phone +49 (0)89 8780 67-0
Fax +49 (0)89 8780 67-300

www.vincotech.com/gps

 **incotech**
power.position.service