



SPECIFICATION FOR APPROVAL

查询"SD1205R90Y1"供应商
REF :



PAGE: 1

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SD1205□□□□1□-□□□
		ABC'S ITEM NO.	


I . MECHANICAL DIMENSIONS :



A	: 12.50±0.30	m/m
B	: 12.50±0.30	m/m
C	: 5.00±0.50	m/m
D	: 1.90±0.20	m/m
E	: 2.50 nom.	m/m
E1	: 3.00 ref.	m/m
E2	: 2.00 ref.	m/m
F	: 7.50±0.25	m/m
F1	: 6.40 ref.	m/m
F2	: 5.20 ref.	m/m
H	: 10.50 ref.	m/m
I	: 4.15 ref.	m/m
J	: 3.00 ref.	m/m
K	: 13.00 ref.	m/m
M	: 4.70 ref..	m/m
N	: 4.50 ref.	m/m
P	: 7.50 ref.	m/m




II . SCHEMATIC DIAGRAM :




III . MATERIALS LIST :

- a . Core : Ferrite ER core
- b . Core : Ferrite SB core
- c . Wire : Ultra-fine rectangular
Enamelled copper wire (class F)
- d . Terminal : Cu/Sn
- e . Adhesive : Epoxy resin
- f . Adhesive : Epoxy resin
- g . Remark : Products comply with RoHS' requirements



Peak Temp : 260°C max.
Max time above 230°C : 50sec max.
Max time above 200°C : 70sec max.



IV . GENERAL SPECIFICATION :

- a . Temp. rise : 40°C max.
- b . Storage temp. : -40°C ~ +125°C
- c . Operating temp. : -40°C ~ +105°C
- d . Resistance to solder heat : 260°C. 10 secs.

AR-001A



千如電子集團
ABC ELECTRONICS GROUP.



PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SD1205□□□□1□-□□□
		ABC'S ITEM NO.	


V . ELECTRICAL CHARACTERISTICS :

DWG No.	Initial inductance L0 (uH)	Inductance at flat point L1 (uH)	Flat point ref. (A)	Irms (A)	Isat (A)	DC Resistance max. (mΩ)
SD1205R90Y1□-□□□	0.90±25%	0.75±25%	5.0	18.0	20.0	2.5
SD12051R4Y1□-□□□	1.40±25%	1.25±25%	5.0	15.0	16.0	3.4
SD12052R0Y1□-□□□	2.00±25%	1.80±25%	4.0	12.0	13.0	4.6
SD12053R2Y1□-□□□	3.50±25%	3.20±25%	2.0	8.6	9.0	9.0
SD12054R6Y1□-□□□	4.80±25%	4.60±25%	2.0	8.2	7.2	10.5
SD12056R4Y1□-□□□	6.80±25%	6.40±25%	3.0	7.8	6.0	11.0
SD12058R2Y1□-□□□	8.60±25%	8.20±25%	3.0	7.2	5.4	12.0
SD1205100Y1□-□□□	10.50±25%	10.00±25%	2.0	6.5	4.7	13.5


- 1). □ : Packaging Information... ☐A: Bulk ☐B: Tpaing Reel
- 2). "- □□□ ":Reference code
- 3). L : 1V / 100 KHZ,HP-4274A ; RDC : CH-502AC
- 4). Measured frequency of inductance is 100 KHz / 1V
- 5). Isat base on inductance drop 20% max. of L1 value
- 6). Irms base on temp. rise 40℃ max.

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SD1205□□□□1□-□□□
		ABC'S ITEM NO.	

@ Inductance VS. DC Superposition Characteristics



@ Inductance VS. DC Superposition Characteristics



SPECIFICATION FOR APPROVAL



REF: 查询"SD1205R90Y1"供应商

PAGE: 4

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SD1205□□□□1□-□□□
		ABC'S ITEM NO.	

VI . PACKAGING INFORMATION :

(1) Configuration



(2) Dimensions

Unit:m/m

Style	A	B	C	D	G	N	T
13 - 24	330	21±0.8	13	24	26 ⁺⁰	50 ⁻⁰	30.4

(3) Q'TY & G.W. Per package

Series	Inner : Reel			Outer : Carton		
	Q'TY (pcs)	G.W. (gw)	Style	Q'TY (pcs)	G.W. (Kg)	Size (cm)
SD1205	600	2,150	13 - 24	2,400	11.30	40 x 40 x 24

AR-001A

ABC 千如電子集團
ABC ELECTRONICS GROUP.


SPECIFICATION FOR APPROVAL

查询"SD1205R90Y1"供应商
REF :

PAGE: 5

PROD.	SHIELDED SMD	ABC'S DWG NO.	SD1205□□□□1□-□□□
NAME	POWER INDUCTOR	ABC'S ITEM NO.	

VII . DWGING NUMBER EXPRESSION :



Appendix code 1 : Product Classification

L : Lead Free Standard products comply with RoHS' requirements

1 ~ 9 : Lead Free Special products comply with RoHS' requirements

Appendix code 2 : Package Information

Code	Inner package	Inner package Q'TY	Remark
A	T.B.D.	T.B.D.	
B	T / R (Reel package)	600 pcs	

AR-001A

SPECIFICATION FOR APPROVAL

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SD1205□□□□1□-□□□
		ABC'S ITEM NO.	

VIII . RELIABILITY TEST :

Test item	Specification	Test condition
Solderability	More than 90% of the terminal electrode Shall be covered With fresh solder.	Preheat : $150\pm 25^{\circ}\text{C}$ for 60 seconds Solder : Sn96.5 / Ag3 / Cu0.5 or equivalent Solder temp. : $235\pm 5^{\circ}\text{C}$ Flux : Rosin Dip time : 4 ± 1 seconds
Thermal shock test (Temp. cycle)	Inductance shall not change more than $\pm 20\%$	Room temp. $\longrightarrow$ $-25\pm 2^{\circ}\text{C}$ 15 minutes $\longrightarrow$ 30 minutes Room temp. $\longrightarrow$ $85\pm 2^{\circ}\text{C}$ 15 minutes $\longrightarrow$ 30 minutes Total : 50 cycles
Humidity Resistance test		Temperature : $40\pm 2^{\circ}\text{C}$ Humidity : 90 ~ 95% Applied current : Per spec. Time : 500 hours
High temp. Resistance test		Temperature : $105\pm 2^{\circ}\text{C}$ Applied current : Per spec. Time : 500 hours

SPECIFICATION FOR APPROVAL

REF: [查询"SD1205R90Y1"供应商](#)

PAGE: 7

PROD. NAME	SHIELDED SMD POWER INDUCTOR	ABC'S DWG NO.	SD1205□□□□1□-□□□
		ABC'S ITEM NO.	

IX . UL CARD :

OBMW2		January 7, 1988			
Component-Magnet Wire				E104048 (S)	
MITSUBISHI CABLE INDUSTRIES LTD					
4-3 IKEJIRI ITAMI , HYOGO 664 JAPAN					
Mtl		Coat Typ		ANSI	Temp
Dsg	BC	Oyercoat		Type	Class
EDW-R52	Medis	Ester-imide		—	155
Marking : Company name and type designation on package or reels.					
See General Information Preceding These Recognitions.					
For use only in equipment where the acceptability of the combination is determined by Underwriters Laboratories Inc.					
Report : January 5, 1988.					
302279005	H7642	Underwriters Laboratories Inc.®		D11/0149909	

This datasheet has been downloaded from:

www.EEworld.com.cn

Free Download

Daily Updated Database

100% Free Datasheet Search Site

100% Free IC Replacement Search Site

Convenient Electronic Dictionary

Fast Search System

www.EEworld.com.cn