

Power Transformers

Horizontal

4766 - 4770





LOW VOLTAGE RECTIFIER Transformer
with horizontal mounting frames.

[查询"4770-03"供应商](#)

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 2-hole horizontal mounting.
- 5 sizes are available, covering the range: 10 to 50 VA.
- CSA listed (LR 47366).



MECHANICAL



Dimensions, inches

P/N	DIMENSIONS			PIN SPACING A
	L	W	H	
4766	3.25	2.00	2.00	2.81
4767	3.25	2.25	2.00	2.81
4768	3.69	2.13	2.31	3.13
4769	4.00	2.25	2.63	3.56
4770	4.00	2.50	2.63	3.56

ELECTRICAL SPECIFICATION

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4766-01	6.3	7.25	1.20
4766-02	6.3	7.14	2.00
4766-03	10.0	11.00	1.00
4766-04	14.0	16.00	1.00
4766-05	20.0	22.00	0.50
4766-06	28.0	32.00	0.50
4766-07	30.0	34.20	0.50
4766-08	36.0	39.40	0.30
4766-09	44.0	50.60	0.25
4766-10	50.0	57.00	0.30
4767-01	8.5	9.60	2.00
4767-02	36.0	40.00	0.50
4767-03	16.0	17.60	1.00
4768-01	6.3	6.90	4.00
4768-02	8.5	9.50	3.00
4768-03	10.0	10.80	2.00
4768-04	12.6	13.80	2.00
4768-05	20.0	22.00	1.00
4768-06	25.0	27.50	1.00
4768-07	28.0	30.80	1.00
4768-08	44.0	48.10	0.50
4768-09	50.0	55.00	0.50

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4769-01	14.0	15.30	2.00
4769-02	18.0	19.60	1.50
4770-01	8.5	9.04	4.00
4770-02	10.0	10.50	3.00
4770-03	16.0	17.00	2.20
4770-04	16.0	17.40	3.00
4770-05	20.0	21.40	2.00
4770-06	25.0	26.80	1.50
4770-07	33.0	35.00	1.00
4770-08	36.0	39.50	1.00
4770-09	44.0	47.40	1.00
4770-10	50.0	54.50	1.00
4770-11	60.0	65.20	0.50
4770-12	80.0	85.50	0.50
4770-13	100.0	107.00	0.50
4770-14	120.0	129.50	0.30

ISSUE: C 4760.CHP 950712



FILTRAN LTD
An ISO 9001 Registered Company

229 Colonnade Road, Nepean, Ontario, Canada K2E 7K3
Tel: (613) 226-1626 Fax: (613) 226-7124 www.filtran.com

pdf.dzsc.com