

Power Transformers


Fully Enclosed 4801 - 4807




LOW VOLTAGE RECTIFIER Transformers with fully enclosed vertical end models.

[查询"4802-04"供应商](#)

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 4-hole vertical mounting.
- 7 sizes are available, covering the range: 30 to 100 VA.
- CSA listed (LR 47366).



MECHANICAL



Dimensions, Inches

P/N	DIMENSIONS			H	D E F G			
	L	W						
4801	2.50	2.13	3.00	2.00	1.19	0.375	0.190	
4802	2.50	2.38	3.00	2.00	1.44	0.375	0.190	
4803	2.50	2.63	3.00	2.00	1.68	0.375	0.190	
4804	2.50	2.88	3.00	2.00	1.94	0.375	0.190	
4805	2.50	3.13	3.00	2.00	2.19	0.375	0.190	
4806	2.50	3.38	3.00	2.00	2.44	0.375	0.190	
4807	2.50	3.63	3.00	2.00	2.69	0.375	0.190	

ELECTRICAL SPECIFICATION

Part No.	Secondary Voltages (A-A)			Current Amps
	F.L. Volts	N.L. Volts		
4801-01	5.0	5.40		3.00
4802-01	5.0	5.43		6.00
4802-02	6.3	6.90		4.00
4802-03	12.6	13.80		2.00
4802-04	25.0	27.50		1.00
4802-05	28.0	30.80		1.00
4802-06	36.0	39.50		1.00
4802-07	50.0	51.80		5.00
4802-08	60.0	65.20		0.50
4803-01	5.0	5.35		8.00
4803-02	6.3	6.70		6.00
4803-03	10.0	10.70		4.00
4803-04	16.0	17.40		3.00
4803-05	18.0	19.40		3.00
4803-06	25.0	26.80		1.50
4803-07	33.0	35.00		1.00
4803-08	50.0	54.50		1.00
4803-09	80.0	85.50		0.50
4803-10	100.0	107.00		0.50
4804-01	5.0	5.35		10.00
4804-02	6.3	6.74		8.00
4804-03	10.0	10.70		5.00
4804-04	10.0	10.70		5.00
4804-05	11.0	11.80		5.00
4804-06	12.6	13.40		4.00
4804-07	14.0	15.10		4.00

Part No.	Secondary Voltages (A-A)			Current Amps
	F.L. Volts	N.L. Volts		
4804-08	24.0	25.60		2.00
4804-09	28.0	29.80		2.00
4804-10	30.0	31.60		1.50
4805-01	6.3	6.70		10.00
4805-02	20.0	20.80		3.00
4805-03	36.0	38.30		2.00
4805-04	60.0	63.50		1.00
4805-05	120.0	127.00		0.50
4806-01	5.0	5.30		15.00
4806-02	6.3	6.80		12.00
4806-03	10.0	10.60		8.00
4806-04	12.6	13.60		6.00
4806-05	25.0	26.80		3.00
4806-06	28.0	29.60		3.00
4807-01	5.0	5.30		20.00
4807-02	10.0	10.70		10.00
4807-03	12.6	13.30		8.00
4807-04	14.0	15.10		6.00
4807-05	16.0	17.40		5.00
4807-06	18.0	18.70		5.00
4807-07	25.0	26.60		4.00
4807-08	30.0	32.00		3.00
4807-09	44.0	46.00		2.00
4807-10	50.0	53.20		2.00
4807-11	80.0	85.20		0.50
4807-12	100.0	106.50		1.00

ISSUE: C 4801.CHP 9507/12

FILTRAN LTD
An ISO 9001 Registered Company

229 Colonnade Road, Nepean, Ontario, Canada K2E 7K3
Tel: (613) 226-1626 Fax: (613) 226-7124 www.filtran.com

pdf.dzsc.com

