

查询"CSMF36C"供应商

CSMF03V3C
CSMF05C
CSMF12C

CSMF15C
CSMF24C
CSMF36C

**SURFACE MOUNT
5-LINE SILICON TVS/ZENER ARRAY
3.3 VOLTS THRU 36 VOLTS**

Specified by
STAND-OFF VOLTAGE

ULTRAMini™



SOT-363 CASE

MARKING CODES

CSMF03V3C: CF03
CSMF05C: CF05
CSMF12C: CF12
CSMF15C: CF15
CSMF24C: CF24
CSMF36C: CF36

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$ unless otherwise noted)

Peak Pulse Power (8x20u sec Waveform)

ESD Voltage (HBM)

Operating and Storage Junction Temperature Range

SYMBOL

P_{pp} 100 W
 V_{ESD} 25 kV
 T_J, T_{stg} -55 to +150 $^\circ\text{C}$

UNITS

ELECTRICAL CHARACTERISTICS PER DIODE: ($T_A=25^\circ\text{C}$ unless otherwise noted)

TYPE NO.	Maximum Reverse Stand-Off Voltage	Minimum Reverse Breakdown Voltage		Maximum Reverse Leakage Current		Maximum Clamping Voltage 8 x 20 μs		Maximum Clamping Voltage 8 x 20 μs		Maximum Off State Junction Capacitance ($V_R=0\text{V}$, $f=1\text{MHz}$)
	V_{WRM} (V)	V_{BR} (V)	I_{BR} (mA)	I_R (μA)	V_R (V)	V_{cl} (V)	I_{PP} (A)	V_{cl} (V)	I_{PP} (A)	C_J (pF)
CSMF03V3C	3.3	4.7	10	250	3.3	7.5	5.0	9	9	160
CSMF05C	5	6.2	1.0	0.5	5	9	5.0	10	9	90
CSMF12C	12	13.3	1.0	0.5	12	17	3.0	20	5	60
CSMF15C	15	16.6	1.0	0.5	15	23	3.0	25	4	46
CSMF24C	24	26.7	1.0	0.5	24	35	1.0	45	2	38
CSMF36C	36	38	1.0	0.5	36	40	1.0	50	2	27

R0 (19-December 2005)

Central™
Semiconductor Corp.

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CSMF03V3C Series is a 5 Line TVS/Zener Array packaged in an ULTRAMini SOT-363 surface mount case. These devices are designed to protect sensitive electronic equipment, such as computers, networking communication, cell phones and instrumentation from over-voltage transients and ESD damage. Available in voltages ranging from 3.3V to 36V.

FEATURES

- Very low Clamping Voltage
- Low Leakage Current
- 100W Power Dissipation
- SMD SOT-363 Package
- IEC61000-4-2 ESD 20kV air, 15kV Contact Compliance


APPLICATIONS:

- Hand Held Portable Applications
- Networks, Servers and Telecom
- Desktop and Notebook Computers
- Instrumentation



SURFACE MOUNT
5-LINE SILICON TVS/ZENER ARRAY
3.3 VOLTS THRU 36 VOLTS


SOT-363 - CASE - MECHANICAL OUTLINE



SYMBOL	DIMENSIONS			
	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.073	0.085	1.85	2.15
B		0.051		1.30
C		0.026		0.65
D	0.075	0.091	1.90	2.30
E	0.043	0.055	1.10	1.40
F	0.006	0.012	0.15	0.30
G	0.000	0.004	0.00	0.10
H	0.010	-	0.25	-
I	0.004	0.010	0.10	0.25
J	0.031	0.039	0.80	1.00

SOT-363 (REV: R1)

Pin Configuration



Lead code:

- 1) Cathode D1
- 2) Anode D1, D2, D3, D4, D5
- 3) Cathode D2
- 4) Cathode D3
- 5) Cathode D4
- 6) Cathode D5

Circuit Diagram

