

查询"CTHC1812F-561K"供应商

CTHC1812 Series

From 1.0 μH to 1000 μH 

CHARACTERISTICS

Description: High current, ferrite core, wire-wound molded chip inductor

Applications: TV's, VCR's, disk drives, computer peripherals, telecommunication devices and electronic control boards for automobiles

Operating Temperature: -25°C to +85°C

Inductance Tolerance: $\pm 10\%$

Testing: Inductance and Q are tested on an HP4285A at specified frequency

Packaging: Tape & Reel

Part Marking: Inductance code or inductance code plus tolerance.

Miscellaneous: RoHS Compliant available.

Additional Information: Additional electrical & physical information available upon request

Samples available. See website for ordering information.

SPECIFICATIONS

Parts are available in $\pm 10\%$ tolerance only.
CTHC1812E Please specify "F" for RoHS compliant

Central Tech Part Number	Inductance (μH)	L Test Freq. (MHz)	Q Fact. Min.	Q Test Freq. (MHz)	SRF Min. (MHz)	DCR Max. (Ω)	Rated DC (mA)
CTHC1812_-1R0K	1.0	7.96	10	7.96	200	.11	1050
CTHC1812_-1R2K	1.2	7.96	10	7.96	160	.12	1000
CTHC1812_-1R5K	1.5	7.96	10	7.96	130	.15	950
CTHC1812_-1R8K	1.8	7.96	10	7.96	100	.16	900
CTHC1812_-2R2K	2.2	7.96	10	7.96	80	.18	850
CTHC1812_-2R7K	2.7	7.96	10	7.96	60	.20	800
CTHC1812_-3R3K	3.3	7.96	10	7.96	45	.22	750
CTHC1812_-3R9K	3.9	7.96	10	7.96	40	.24	700
CTHC1812_-4R7K	4.7	7.96	10	7.96	35	.27	650
CTHC1812_-5R6K	5.6	7.96	10	7.96	30	.30	650
CTHC1812_-6R8K	6.8	7.96	10	7.96	28	.35	600
CTHC1812_-8R2K	8.2	7.96	10	7.96	25	.40	600
CTHC1812_-100K	10	2.52	10	2.52	22	.50	550
CTHC1812_-120K	12	2.52	10	2.52	21	.60	500
CTHC1812_-150K	15	2.52	10	2.52	20	.70	450
CTHC1812_-180K	18	2.52	10	2.52	19	.80	400
CTHC1812_-220K	22	2.52	10	2.52	18	.90	370
CTHC1812_-270K	27	2.52	10	2.52	16	1.2	330
CTHC1812_-330K	33	2.52	10	2.52	14	1.4	300
CTHC1812_-390K	39	2.52	10	2.52	12	1.6	280
CTHC1812_-470K	47	2.52	10	2.52	12	1.9	260
CTHC1812_-560K	56	2.52	10	2.52	11	2.2	240
CTHC1812_-680K	68	2.52	10	2.52	10	2.6	220
CTHC1812_-820K	82	2.52	10	2.52	9.0	3.5	200
CTHC1812_-101K	100	0.796	20	0.796	8.0	4.0	180
CTHC1812_-121K	120	0.796	20	0.796	7.5	4.5	160
CTHC1812_-151K	150	0.796	20	0.796	7.0	6.5	140
CTHC1812_-181K	180	0.796	20	0.796	6.5	7.5	120
CTHC1812_-221K	220	0.796	20	0.796	5.5	9.0	120
CTHC1812_-271K	270	0.796	20	0.796	5.0	11	100
CTHC1812_-331K	330	0.796	20	0.796	4.0	13	90
CTHC1812_-391K	390	0.796	20	0.796	3.8	23	80
CTHC1812_-471K	470	0.796	20	0.796	3.5	26	75
CTHC1812_-561K	560	0.796	20	0.796	2.8	30	70
CTHC1812_-681K	680	0.796	20	0.796	2.6	40	65
CTHC1812_-821K	820	0.796	20	0.796	2.5	45	60
CTHC1812_-102K	1000	0.796	20	0.796	2.3	50	55

PHYSICAL DIMENSIONS

Size	A	B	C	D	E
mm	4.5 $\pm$ 0.3	3.2 $\pm$ 0.2	3.2 $\pm$ 0.2	1.4 $\pm$ 0.4	0.9 $\pm$ 0.2
inches	0.18 $\pm$ 0.012	0.12 $\pm$ 0.001	0.12 $\pm$ 0.001	0.06 $\pm$ 0.016	0.04 $\pm$ 0.001

05.31.07

Manufacturer of Passive and Discrete Semiconductor Components

800-684-5322 Inside US

949-453-1811 Outside US

Copyright © 2007 by CT Magnetics, DBA Central Technologies. All rights reserved.

CT Magnetics reserves the right to make improvements or change specifications without notice

