


SAW Bandpass Filter 250202B

1. Features

- IF bandpass filter
- High attenuation
- Single-ended operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters
Base : Fe(SPCC), Au plating over Ni plated
Cap : Cu & Cr Alloy, Ni Plated
Termination : Kovar, Au Plated

Pin Configuration	
1	Input
4	Output
2, 5	Ground
Other	Case ground

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250202B	
		Rev. Date	2005-08-26	
		Rev.	NW5007-CS02	1/5

SAW Bandpass Filter 250202B

3. Specifications

Fo = 139.5 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

Operating temperature range : -10℃ ~ +60℃		Minimum	Typical	Maximum
Center Frequency	MHz	139.45	139.5	139.55
Insertion Loss	dB	-	23.0	25.0
1dB Bandwidth	MHz	2.4	2.45	-
3dB Bandwidth	MHz	2.45	2.56	-
40dB Bandwidth	MHz	-	3.08	3.1
Amplitude Ripple (Fo +/- 1.1 MHz)	dB	-	0.6	1.0
Group Delay Variation (Fo +/- 1.1 MHz)	nsec	-	150	300
Absolute Delay	usec	-	4.55	-
Ultimate Rejection	dB	45	50	-
Temperature Coefficient of Frequency	ppm/℃ ²	-	-0.03	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration
- 3) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 4) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250202B	
		Rev. Date	2005-08-26	
		Rev.	NW5007-CS02	2/5

SAW Bandpass Filter 250202B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



L1 = 33 nH, L4 = 27 nH
L2 = L3 = 10 nH

5. Marking Configuration

ITF¹⁾05A001²⁾
250202B³⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250202B	
		Rev. Date	2005-08-26	
		Rev.	NW5007-CS02	3/5

SAW Bandpass Filter 250202B







6. Typical Performance (at +25℃)



	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	250202B	
		Rev. Date	2005-08-26	
		Rev.	NW5007-CS02	4/5

SAW Bandpass Filter 250202B



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

250202B

Rev. Date

2005-08-26

Rev.

NW5007-CS02

5/5