


SAW Bandpass Filter 271101B



1. Features

- IF bandpass filter
- High attenuation
- Single-ended operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D2012

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated

Cap : Cu & Cr Alloy, Ni Plated

Termination : Kovar, Au Plated

Pin Configuration

1	Input
5	Output
2, 4	Ground
3, 6	Case ground

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271101B	
		Rev. Date	2004-10-22	
		Rev.	DS4055-CS01	1/5

SAW Bandpass Filter 271101B

3. Specifications

Fo = 70.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	69.9	70.0	70.1
Insertion Loss	dB	-	22.0	25.0
1dB Bandwidth	MHz	10.0	10.6	-
3dB Bandwidth	MHz	10.9	11.0	-
40dB Bandwidth	MHz	-	12.45	12.8
Amplitude Ripple (Fo +/- 5.0 MHz)	dB	-	0.7	1.0
Group Delay Variation (Fo +/- 5.0 MHz)	nsec	-	50	100
Absolute Delay	usec	-	2.3	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271101B	
		Rev. Date	2004-10-22	
		Rev.	DS4055-CS01	2/5

SAW Bandpass Filter 271101B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



5. Marking Configuration

ITF¹⁾ 04A001²⁾

271101B³⁾

1) Manufacturer name

2) Lot Number



3) Part Number

 Integrated Technology Future	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	271101B	
		Rev. Date	2004-10-22	
		Rev.	DS4055-CS01	3/5

SAW Bandpass Filter 271101B







6. Typical Performance (at +25℃)



	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809		Part No. 271101B	
			Rev. Date 2004-10-22	
			Rev. DS4055-CS01	4/5

SAW Bandpass Filter 271101B



ITF Co., Ltd.
102-901, Bucheon Technopark 364,
Samjeong-Dong, Ojeong-Gu, Bucheon-City,
Gyeonggi-Do, Korea 421-809

Part No.

271101B

Rev. Date

2004-10-22

Rev.

DS4055-CS01

5/5