

6MBI75UC-120

IGBT Module U-Series 1200V / 75A 6 in one-package

■ Features

- High speed switching
- Voltage drive
- Low inductance module structure

■ Applications

- Inverter for Motor drive
- AC and DC Servo drive amplifier
- Uninterruptible power supply
- Industrial machines, such as Welding machines

■ Maximum ratings and characteristics

● Absolute maximum ratings (at Tc=25°C unless otherwise specified)

Item	Symbol	Conditions	Rating	Unit	
Collector-Emitter voltage	V _{CES}		1200	V	
Gate-Emitter voltage	V _{GES}		±20	V	
Collector current	I _c	Continuous	T _c =25°C	100	A
			T _c =80°C	75	
	I _{cp}	1ms	T _c =25°C	200	
			T _c =80°C	150	
			-I _c	75	
-I _c pulse		150			
Collector Power Dissipation	P _c	1 device	390	W	
Junction temperature	T _j		+150	°C	
Storage temperature	T _{stg}		-40 to +125		
Isolation voltage	V _{iso}	AC:1min.	2500	VAC	
Screw Torque	Mounting	*2	3.5	N·m	

*1 : All terminals should be connected together when isolation test will be done.

*2 : Recommendable value : 2.5 to 3.5 N·m(M5)

● Electrical characteristics (at Tj=25°C unless otherwise specified)

Item	Symbols	Conditions	Characteristics			Unit	
			Min.	Typ.	Max.		
Zero gate voltage collector current	I _{CES}	V _{GE} =0V, V _{CES} =1200V	-	-	1.0	mA	
Gate-Emitter leakage current	I _{GES}	V _{CES} =0V, V _{GE} =±20V	-	-	200	nA	
Gate-Emitter threshold voltage	V _{GE(th)}	V _{CES} =20V, I _c =75mA	4.5	6.5	8.5	V	
Collector-Emitter saturation voltage	V _{CE(sat)} (chip)	V _{GE} =15V, I _c =75A	T _j =25°C	-	1.75	2.10	V
			T _j =125°C	-	2.00	-	
Input capacitance	C _{ies}	V _{CES} =10V, V _{GE} =0V, f=1MHz	-	8	-	nF	
Turn-on time	t _{on}	V _{CC} =600V	-	0.36	1.20	μs	
	t _r	I _c =75A	-	0.21	0.60		
	t _{r(i)}	V _{GE} =±15V	-	0.03	-		
Turn-off time	t _{off}	R _G =9.1 Ω	-	0.37	1.00	μs	
	t _f		-	0.07	0.30		
Forward on voltage	V _F (chip)	V _{GE} =0V I _F =75A	T _j =25°C	-	1.60	1.90	V
			T _j =125°C	-	1.70	-	
Reverse recovery time	t _{rr}	I _F =75A	-	-	0.35	μs	
Lead resistance, terminal-chip*3	R _{lead}	Without shunt resistance	-	5.7	-	mΩ	
Shunt resistance	R _{shunt}	Resistance of R1,R2,R3 *4	-	2.4	-		

*3: Biggest internal terminal resistance among arm.

*4: R1, R2,R3 is shown in equivalent circuit (p5)

● Thermal resistance characteristics


Items	Symbols	Conditions	Characteristics			Unit
			Min.	Typ.	Max.	
Thermal resistance	R _{th(j-c)}	IGBT	-	-	0.32	°C/W
	R _{th(j-c)}	FWD	-	-	0.49	°C/W
Contact Thermal resistance	R _{th(c-f)} *5	With thermal compound	-	0.05	-	°C/W

*5 : This is the value which is defined mounting on the additional cooling fin with thermal compound.




Characteristics (Representative)


Collector current vs. Collector-Emitter voltage (typ.)
Tj= 25°C / chip




Collector current vs. Collector-Emitter voltage (typ.)
Tj= 125°C / chip




Collector current vs. Collector-Emitter voltage (typ.)
VGE=15V / chip




Collector-Emitter voltage vs. Gate-Emitter voltage (typ.)
Tj=25°C / chip



Capacitance vs. Collector-Emitter voltage (typ.)
VGE=0V, f= 1MHz, Tj= 25°C




Dynamic Gate charge (typ.)
Vcc=600V, Ic=75A, Tj= 25°C




[查询"6MBI75UC-120"供应商](#)


Switching time vs. Collector current (typ.)
 $V_{cc}=600V, V_{GE}=\pm 15V, R_g=9.1\Omega, T_j=25^\circ C$




Switching time vs. Collector current (typ.)
 $V_{cc}=600V, V_{GE}=\pm 15V, R_g=9.1\Omega, T_j=125^\circ C$




Switching time vs. Gate resistance (typ.)
 $V_{cc}=600V, I_c=75A, V_{GE}=\pm 15V, T_j=25^\circ C$




Switching loss vs. Collector current (typ.)
 $V_{cc}=600V, V_{GE}=\pm 15V, R_g=9.1\Omega$



Switching loss vs. Gate resistance (typ.)
 $V_{cc}=600V, I_c=75A, V_{GE}=\pm 15V, T_j=125^\circ C$




Reverse bias safe operating area (max.)
 $+V_{GE}=15V, -V_{GE} \le 15V, R_g \ge 9.1\Omega, T_j \le 125^\circ C$




[查询"6MBI75UC-120"供应商](#)


Forward current vs. Forward on voltage (typ.)
chip



Reverse recovery characteristics (typ.)
Vce=600V, VGE=±15V, Rg=9.1Ω




Transient thermal resistance (max.)



[查询"6MBI75UC-120"供应商](#)

Outline Drawings, mm



□ shows theoretical dimension.
() shows reference dimension.

Equivalent Circuit Schematic

